



PIER LIGHT SERIES
DAMP / WET LOCATION
TIERS

PROJECT: _____
 QUANTITY: _____ TYPE: _____



PL1613GV
 AZ - Anodic Bronze



PL1613GV
 MB - Matte Black



PL1613GV
 PT - Platinum Silver



PL1613GV
 MW - Matte White

| SERIES | LUMENS ¹ | CCT | DRIVER / DIMMING ² | ACCESSORIES | MOUNTING ⁷ | FINISH ¹¹ | WET KIT |
|---|--|--|--|--|---|---|------------------------------|
| PL1411GV PL1613GV PL2015GV | 15L 1500 Lm 27L 2700 Lm 37L 3700 Lm 45L 4500 Lm | 80 CRI 27K 2700K 30K 3000K 35K 3500K 40K 4000K 90 CRI 27HK 2700K 30HK 3000K 35HK 3500K 40HK 4000K | EX³ Electronic Driver, 120V/277V DO10X 1%, 0-10V, 120V/277V DS2W1⁴ ELV/MLV, 120V DLTE1⁵ Lutron® 2-Wire Forward Phase (MLV), 120V DL3EX⁶ 1%, Lutron® EcoSystem®, Fades to Black, 120V/277V | FJ2⁸ 4" Frosted Tail | WALL MOUNT CP104 Small Driver Canopy CP104KO Small Driver Canopy w/ Knockouts CP106 Large Driver Canopy CP6/RMD Remote Mount Driver SP90⁹ Straight Arm PA⁹ Mounting Arm Style CEILING MOUNT RDC5 Small Driver Canopy CP13 Large Driver Canopy HM⁹ Hang Straight AT⁹ Hang Straight All Thread PM⁹ Rigid Pendant Mount CD⁹ Cord / Cable Mount CM⁹ Cord Mount EMCR¹⁰ 10W Large Driver Canopy EM EMRM 7W Remote EM EMEN 7W Remote with Enclosure | MW¹² Matte White MB¹² Matte Black PT¹² Platinum Silver CC Custom Color See Page 5 for Full Range of Color Options (83-90083) | WLKA Wet Location Kit |

EXAMPLE: PL1411GV15L27KDO10XFJ2/CP104PA23PT

NOTES:
 1 Nominal Source Lumens at 35K 2 Contact Factory for Additional Options 3 37L Max with CP104 4 37L Max with CP104/RDC5, 45L Max with CP106/CP13
 5 Available with CP106/CP13 Only 6 Standard Enclosure 7 See Mounting Page for Details on Components and Finishes 8 See Mounting Page for Available Arm Options
 9 Specify Length in Inches: See Mounting Page for Available Lengths 10 EMCR Replaces RDC5 or CP13 11 See Color Page for More Options/Consult Factory for Special Finishes
 12 Standard Finishes





PIER LIGHT SERIES


DAMP / WET LOCATION

TIERS

| LUMENS / WATTAGE DATA | | | | |
|-----------------------|----------------------------|-------------------------------|--------------|-----|
| PART NUMBER | SOURCE LUMENS ¹ | DELIVERED LUMENS ² | SYSTEM WATTS | LPW |
| PL1411GV15L | 1500 | 635 | 10 | 64 |
| PL1411GV27L | 2700 | 1103 | 18 | 61 |
| PL1411GV37L | 3700 | 1626 | 26 | 63 |
| PL1411GV45L | 4500 | 1849 | 30 | 62 |

¹ Nominal Source Lumens at 35K ² Nominal Delivered Lumens at 35K

HOUSING DIMENSIONS



Dimensioned with **PL1411GV**

| SERIES | A | B |
|----------|------|------|
| PL1411GV | 14.0 | 11.7 |
| PL1613GV | 16.0 | 11.7 |
| PL2015GV | 20.0 | 11.7 |

APPLICATION

The Pier Light RLM has a nautical design for decorative lighting.

FEATURES

Spectrum Lighting's RLM classics are reproductions of classic lighting fixtures reimaged with modern LED light sources and materials. The wide range of options for illumination, mounting, enclosures, guards and finishes allows for creative fixture specification and design. LED module and driver are serviceable for future replacement. Available in three sizes.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. Variety of standard and custom finishes are available. Interior painted same finish as exterior.

ELECTRONICS

GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 80+. Higher CRI, R9 and custom LED configurations are available; consult factory. Choice of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Fixture shades are spun in our factory from 0.063 high purity aluminum. Wall mount canopies are die-cast aluminum with stainless steel hardware. Wall arms are formed 3/4 NPT aluminum pipe and may be field cut.

CODE COMPLIANCE

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Wet Location Option. Manufactured and tested to UL standards No. 1598/8750.

SERIES SIZES

PL1411GV



PL1613GV



PL2015GV



WALL MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & DIMENSIONS.)

PA_
MOUNTING ARM STYLE



PL1613GV SHOWN WITH CPT04PA23

CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

HM / AT / PM
HANG STRAIGHT / ALL THREAD / PENDANT



PL1613GV SHOWN WITH RDC5PM

CD
CORD / CABLE MOUNT



PL1613GV SHOWN WITH RDC5CD

CM
CORD MOUNT



PL1613GV SHOWN WITH RDC5CM





PIER LIGHT SERIES
DAMP / WET LOCATION
TIERS / PHOTOMETRIC DATA

PL1411GV-45L35K-EX-FJ2

| CANDLEPOWER CURVE | INTENSITY | ZONAL LUMENS | SINGLE UNIT: PERFORMANCE INITIAL FOOTCANDLES BASED ON IES BEAM ANGLE | MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT |
|---|------------|--------------------|--|--|
| <p>Delivered Lumens: 1,848 Luminaire Watts: 30 LER: 61.60</p> | 0.00° | | | |
| | 0.00° 749 | 0° - 20° 227 12% | Mounting Height | Ceiling Height |
| | 20.00° 496 | 20° - 50° 660 36% | FC at Center on Floor | Fixture Spacing |
| | 40.00° 330 | 50° - 80° 623 34% | 5.5' | 8' |
| | 60.00° 223 | 80° - 90° 121 7% | 6.5' | 5' |
| | 80.00° 141 | 0° - 90° 1,631 88% | 7.5' | 7' |
| | 90.00° 82 | 90° - 120° 200 11% | 8.5' | 9' |
| | 100.00° 74 | 120° - 150° 16 1% | 10.0' | Delivered Illuminance Rating: (DIR) |
| | 110.00° 62 | Total 1,848 100% | 12.0' | 51 FC per W/Sq. Ft. |
| | 120.00° 24 | | 14.0' | 39 FC per W/Sq. Ft. |
| | 140.00° 2 | | 16.0' | 2' Suspension Length |
| | 160.00° 1 | | | Square rooms used for multiple units: |
| | 180.00° 1 | | | - RCR 2: Length & Width = Ceiling Ht. - 4.5' x 5.00 |
| | | | | - RCR 4: Length & Width = Ceiling Ht. - 4.5' x 2.50 |
| | | | * Average Footcandles at 2.5' Above Floor | |
| | | | * Exceeds spacing criteria by 79% | |
| | | | ** Exceeds spacing criteria by 17% | |
| | | | *** Exceeds spacing criteria by -2% | |
| | | | Lamp Multiplier: 15L x 0.322, 27L x 0.564, 37L x 0.826 | |
| | | | CCT Multiplier: 40K x 1.03, 30K x 0.985, 27K x 0.971 | |




MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION. NOTE: THIS IS TYPICAL OF RLM SPECIFICATION FOR MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.




WALL MOUNTING


CP104 - SMALL DRIVER CANOPY (STANDARD)
MAY BE USED AS SPLICE BOX FOR DIRECT FEED
NOT AVAILABLE W/ PA16 & PA16F




CP106 - LARGE DRIVER CANOPY
MAY BE USED AS SPLICE BOX FOR DIRECT FEED



CP6/RMD - REMOTE MOUNT DRIVER
MOUNTS DIRECTLY TO WALL OR OCTAGON STYLE J-BOX




CUSTOM AND OTHER WALL ARMS AVAILABLE - CONTACT FACTORY. ARMS MAY BE FIELD CUT ON WALL SIDE - FIXTURE SIDE THREADED 3/4" NPT REQUIRES SEALANT FOR WET LOCATION.




CEILING MOUNTING


RDC5 - SMALL DRIVER CANOPY (STANDARD)
MOUNTS TO 4" OCTO J-BOX



CP13 - LARGE DRIVER CANOPY




HM*
HANG STRAIGHT
45° SWIVEL 5/8" OD STEM - 3/8" IP




ORDER: HM (Length)
SPECIFY LENGTH:
HM3 - 3" HM24 - 24"
HM6 - 6" HM36 - 36"
HM12 - 12" HM48 - 48"
HM18 - 18" HM72 - 72"
HMLC(XX)
Custom Length
(Specify in Inches)

PM*
RIGID PENDANT MOUNT
RIGID 5/8" OD STEM - 3/8" IP




ORDER: PM (Length)
SPECIFY LENGTH:
PM3 - 3" PM24 - 24"
PM6 - 6" PM36 - 36"
PM12 - 12" PM48 - 48"
PM18 - 18" PM72 - 72"
PMLC(XX)
Custom Length
(Specify in Inches)

AT**
HANG STRAIGHT ALL THREAD
45° SWIVEL 5/8" OD STEM - 1/4" IP



ORDER: AT (Length)
SPECIFY LENGTH:
AT12 - 12"
AT24 - 24"
AT36 - 36"
AT48 - 48"
AT60 - 60"
AT72 - 72"

CD
CORD / CABLE MOUNT
SJ CORD WITH 1/16 SS CABLE



ORDER: CD (Length)
SPECIFY LENGTH:
CD36 - 36"
CD72 - 72"
CD144 - 144"
CDLC(XX)
Custom Length
(Specify in Inches)

CM
CORD MOUNT
SJ CORD WITH STRAIN RELIEF




ORDER: CM (Length)
SPECIFY LENGTH:
CM36 - 36"
CM72 - 72"
CM144 - 144"
CMLC(XX)
Custom Length
(Specify in Inches)

*MAXIMUM ONE PIECE STEM LENGTH IS 72". **MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS.
**ORDER IN 12" INCREMENTS, ODD SIZES MAY BE FIELD CUT


EMERGENCY BATTERY OPTIONS

EMCR - LARGE DRIVER CANOPY FOR 10W EMERGENCY BATTERY
(FOR ROUND CEILING MOUNT TYPES)




REMOTE EMERGENCY BATTERY OPTIONS

EMRM* - 7W REMOTE EMERGENCY BATTERY
(50' MAX)



| A | B | C |
|-----|------|------|
| 1.3 | 12.6 | 13.0 |

EMEN* - 7W REMOTE EMERGENCY BATTERY WITH ENCLOSURE (50' MAX)



| A | B | C |
|-----|------|-----|
| 2.0 | 17.0 | 6.2 |

*OTHER EM BATTERY SIZES AVAILABLE, CONTACT FACTORY.



COLOR OPTIONS - POWDER COAT PAINT FINISHES

NOTE: NO PRINTED IMAGE CAN EQUAL THE EXACT COLOR OF FINISH ON METAL.
SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.



STANDARD CORD / STEM / CANOPY FINISHES


| FIXTURE COLOR | STANDARD CORD COLOR | STANDARD CANOPY / STEM COLOR |
|--|---------------------|------------------------------|
| Matte White, Textured White | Matte White | Matte White |
| Gloss White | Matte White | Gloss White |
| Matte Black, Gloss Black, Textured Black | Matte Black | Matte Black |
| All Others | Matte Black | Same Color as Fixture |
| Custom Color | Contact Factory | Contact Factory |

PAINT TIMES


| TIER | COST | AVERAGE PAINT TIME* |
|---------------------------------|-----------------|---------------------|
| Tier 1 - Standard Finishes | \$ | ⓪ |
| Tier 2 - Typical Finishes | \$\$ | ⓪⓪ |
| Tier 3 - Special Metal Finishes | \$\$\$ | ⓪⓪⓪ |
| Custom Color | Contact Factory | Contact Factory |

*CONTACT FACTORY FOR SPECIFIC PRODUCT LEAD TIMES


TIER 1 - STANDARD FINISHES



TIER 2 - TYPICAL FINISHES



TIER 3 - SPECIAL METAL FINISHES



CUSTOM COLOR FINISHES

CONTACT FACTORY

CC
Custom Color



*UNAVAILABLE FOR WET LOCATION

