



| A        | B        | C        | D        | S1       | S2       |
|----------|----------|----------|----------|----------|----------|
| 5.6      | .80      | 14.4     | 10.5     | 8.42     | 9.3      |
| 142.2 mm | 20.32 mm | 365.8 mm | 266.7 mm | 213.9 mm | 236.2 mm |

## SGE9XT - TRIM FLANGE / NON-IC RATED

### APPLICATION

Versatile 9" Round aperture recessed LED downlight with a wide range of lumens and optical controls.

### FEATURES

Two-stage optical system for smooth light distribution and focus control. Quick change LED module with interchangeable optics for job site adjustment and fixture maintenance. Shallow plenum design. Tool-less driver and j-box access. Posi-lock trim retention torsion springs.

### TRIM FINISH

A variety of architectural powdercoat and anodized finishes are available. Matte White flange is standard.

### ELECTRONICS

LED system features Xicato LED module with proprietary phosphor technology that provides consistent, stable color with CCT control of +/- 100K over life of the light engine. Base CRI is 83 with 2-step MacAdam Ellipse binning. High CRI is 98 with 1x2-step MacAdam Ellipse binning. Variety of electronic 120V/277V and dimming drivers.

### CONSTRUCTION

Housing/frame constructed of #20 ga. galvanized steel to resist corrosion. Self-Flanged one piece trim spun from 0.063" thick high purity aluminum and finished to specification.

### CODE COMPLIANCE

BAA Compliant. Non-IC rated. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Optional Wet location. Manufactured and tested to UL standards No. 1598/8750.

| WATTAGE / LUMENS DATA |                            |              |
|-----------------------|----------------------------|--------------|
| PART NUMBER           | SOURCE LUMENS <sup>1</sup> | SYSTEM WATTS |
| SGE9XT10L             | 1000                       | 11.1         |
| SGE9XT13L             | 1300                       | 15.0         |
| SGE9XT20L             | 2000                       | 23.7         |
| SGE9XT30L             | 3000                       | 34.6         |
| SGE9XT40L             | 4000                       | 39.9         |
| SGE9XT50L             | 5000                       | 54.0         |

| SERIES | LUMENS <sup>1</sup> | CCT        | OPTICS  | DRIVER / DIMMING / VOLTAGE <sup>3</sup>  | OPTIONS <sup>6</sup> | TRIM  | FINISH   | TRIM OPTIONS  |   |             |            |             |            |
|--------|---------------------|------------|---|--|----------------------|---|----------|---|---|-------------|------------|-------------|------------|
| SGE9XT | 83 CRI              |            | XN <sup>2</sup> 10°<br>ND 26°<br>MD 45°<br>WD 50°<br>XW 55° | E_ Electronic Driver<br>DS10_ 10% 0-10V<br>DO10_ 1% 0-10V<br>DS2W1 1%, ELV/MLV, 120V<br>DL3E_ 4 1% Lutron® EcoSystem®, Fade<br>EL10_ 1%, eldoLED<br>ED01_ 0.1%, eldoLED<br>DALI_ DALI Control<br>DMXS_ 5 DMX Standard Configuration<br>DMXC_ 5 DMX Non-Standard Custom | 1 120V<br>2 277V     | BH27 <sup>7</sup> 27" Solid Bars<br>H12 12" - 24" Expandable Bars<br>HO6 6" - 12" Expandable Bars<br>CB24 24" C-Channel Bars<br>EM Integral Emergency Battery<br>FS Fusing<br>EB Black Housing<br>CR Corrosion Resistant<br>PR <sup>8</sup> Deep Ceiling Extension<br>GR Goof Ring<br>AMB Anti Microbial Finish | AR9466XT | SG <sup>9</sup> Semi-Diffuse<br>HZ Haze Full Diffuse<br>MW Matte White<br>MB Matte Black<br>PT Platinum Silver<br>OB Oil Rubbed Bronze<br>CH Charcoal<br>AC Anodic Champagne<br>AS Anodic Sapphire<br>AM Anodic Malachite<br>SN Sun Gold<br>CO Copper Metallic<br>GH Graphite<br>AMB Anti Microbial Finish<br>CC <sup>10</sup> Custom Color | SO <sup>11</sup> Micro Prism Solite™ Lens<br>GL Clear Glass Lens<br>FG Frosted Glass Lens<br>GS Gasket<br>WL Wet Location<br>PF <sup>12</sup> Polished Flange |             |            |             |            |
|        | 10L 1000 Lm         | 27K 2700K  |   |  |                      |   |          |   |   | 20L 2000 Lm | 35K 3500K  | 30L 3000 Lm | 40K 4000K  |
|        | 13L 1300 Lm         | 30K 3000K  |   |  |                      |   |          |   |   | 40L 4000 Lm | 35HK 3500K | 50L 5000 Lm | 40HK 4000K |
|        | 98 CRI              |            |   |  |                      |   |          |   |   |             |            |             |            |
|        | 10L 1000 Lm         | 27HK 2700K |   |  |                      |   |          |   |   | 13L 1300 Lm | 30HK 3000K | 20L 2000 Lm | 35HK 3500K |
|        | 30L 3000 Lm         | 40HK 4000K |   |  |                      |   |          |   |   |             |            |             |            |

### EXAMPLE: SGE9XT13L35KNDE1/BH27/AR9466XTSG

NOTES:  
 1 Nominal Source Lumens at Any CCT 2 XN 13L Max at 83 and 98 CRI 3 Contact Factory for Additional Options 4 50L Not Available with Lutron Drivers 5 Contact Factory 6 See Product Options Page for Details  
 7 Standard Bar Hangers 8 Contact Factory 9 Standard Finish 10 Contact Factory for Special Finishes 11 Standard Lens 12 Flange and Reflector Same Finish

PROJECT: \_\_\_\_\_

QUANTITY: \_\_\_\_\_ TYPE: \_\_\_\_\_

