



**EMBLEM SIGN**  
**DAMP / WET LOCATION**  
**SIGN LIGHTS**

PROJECT: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_ TYPE: \_\_\_\_\_



EB1214GV  
 MB - Matte Black



EB1214GV  
 AZ - Anodic Bronze



EB1214GV  
 PT - Platinum Silver



EB1214GV  
 RD - Red Baron

SERIES	LUMENS <sup>1</sup>	CCT	DRIVER / DIMMING <sup>2</sup>	ACCESSORIES <sup>4</sup>	MOUNTING <sup>7</sup>	FINISH <sup>11</sup>	WET KIT
EB0709GV EB0910GV EB1214GV	15L 1500 Lm 27L 2700 Lm	80 CRI 27K 2700K 30K 3000K 35K 3500K 40K 4000K  90 CRI 27HK 2700K 30HK 3000K 35HK 3500K 40HK 4000K	EX Electronic Driver, 120V/277V 1%, 0-10V, 120V/277V DS2W1 ELV/MLV, 120V DLTE1 <sup>1</sup> Lutron <sup>®</sup> 2-Wire Forward Phase (MLV), 120V DL3EX <sup>3</sup> 1%, Lutron <sup>®</sup> EcoSystem <sup>®</sup> , Fades to Black, 120V/277V	ENCLOSURES TF1 <sup>6</sup> 3" Frosted Dome TG1 <sup>6</sup> 3" Dome Wire Guard MF1 3" Frosted Mini MG1 3" Short Wire Guard FJ1 3" Frosted Tall FG1 3" Tall Wire Guard	WALL MOUNT CP104 Small Driver Canopy CP104KO Small Driver Canopy w/ Knockouts CP106 Large Driver Canopy CP6/RMD Remote Mount Driver SP90 <sup>8</sup> Straight Arm PA <sup>8</sup> Mounting Arm Style  CEILING MOUNT RDC5 Small Driver Canopy CP13 Large Driver Canopy HM <sup>9</sup> Hang Straight AT <sup>9</sup> Hang Straight All Thread PM <sup>9</sup> Rigid Pendant Mount EMCR <sup>10</sup> 10W Large Driver Canopy EM EMRM 7W Remote EM EMEN 7W Remote with Enclosure	MW <sup>12</sup> Matte White MB <sup>12</sup> Matte Black PT <sup>12</sup> Platinum Silver CC Custom Color  See Page 5 for Full Range of Color Options (83-90083)	WLKA Wet Location Kit

EXAMPLE: EB1214GV15L35KEXTF1/CP104PA36BL

**NOTES:**  
 1 Nominal Source Lumens at 35K 2 Contact Factory for Additional Options 3 Available with CP106/CP13 Only 4 Enclosure, Wire Guard Required - Choose One Option  
 5 Standard Enclosure 6 TG1 Not Available With EB0709 7 See Mounting Page for Details on Components and Finishes 8 See Mounting Page for Available Arm Options  
 9 Specify Length in Inches: See Mounting Page for Available Lengths 10 EMCR Replaces RDC5 or CP13 11 See Color Page for More Options/Consult Factory for Special Finishes  
 12 Standard Finishes






# EMBLEM SIGN DAMP / WET LOCATION SIGN LIGHTS

LUMENS / WATTAGE DATA				
PART NUMBER	SOURCE LUMENS <sup>1</sup>	DELIVERED LUMENS <sup>2</sup>	SYSTEM WATTS	LPW
EB1214GV15L	1500	1251	10	125
EB1214GV27L	2700	2184	18	121

<sup>1</sup> Nominal Source Lumens at 35K    <sup>2</sup> Nominal Delivered Lumens at 35K

## HOUSING DIMENSIONS



Dimensioned with **EB1214GV**

SERIES	A	B
EB0709GV	7.1	9.7
EB0910GV	8.8	9.8
EB1214GV	12.4	12.1

## APPLICATION

Emblem Sign light is perfect for a variety of sign and surface lighting applications.

## FEATURES

Spectrum Lighting's RLM Classics are inspired by vintage lighting fixtures redesigned with modern LED light sources and materials. The wide range of options for illumination, mounting, enclosures, guards and finishes allows for creative fixture specification and design. LED module and driver are serviceable for future replacement. Available in three sizes.

## FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. Variety of standard and custom finishes are available. Matte White interior standard.

## ELECTRONICS

GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 80+. Higher CRI, R9 and custom LED configurations are available; consult factory. Choice of electronic 120V/277V and dimming drivers.

## CONSTRUCTION

Fixture shades are spun in our factory from 0.063 high purity aluminum. Wall mount canopies are die-cast aluminum with stainless steel hardware. Wall arms are formed 3/4 NPT aluminum pipe and may be field cut.

## CODE COMPLIANCE

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Wet Location Option. Manufactured and tested to UL standards No. 1598/8750.

## SERIES SIZES

**EB0709GV**



**EB0910GV**



**EB1214GV**



## ENCLOSURES

**TF1**  
3" FROSTED DOME



**MF1**  
3" FROSTED MINI



**FJ1**  
3" FROSTED TALL



**TC1**  
3" FROSTED DOME  
WIRE GUARD - FITS TF1



**MG1**  
3" FROSTED MINI  
WIRE GUARD - FITS MF1



**FG1**  
3" FROSTED TALL  
WIRE GUARD - FITS FJ1



## WALL MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & DIMENSIONS.)

**PA\_**  
MOUNTING ARM STYLE



EB1214GV SHOWN WITH CPT04PA23

## CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

**HM / AT / PM**  
HANG STRAIGHT / ALL THREAD / PENDANT



EB1214GV SHOWN WITH RDC5PM





**EMBLEM SIGN**  
**DAMP / WET LOCATION**  
**SIGN LIGHTS / PHOTOMETRIC DATA**

EB1214GV-27L-35K-EX-TF1-MWI

CANDLEPOWER CURVE	INTENSITY	ZONAL LUMENS	SINGLE UNIT: PERFORMANCE INITIAL FOOTCANDLES BASED ON IES BEAM ANGLE				MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT											
			Mounting Height AFF	FC at Center on Floor	Beam Diameter	FC at Beam Edge	Ceiling Height	Fixture Spacing	RCR 2		RCR 4							
	0.00°																	
	0.00° 920	0° - 10°	89	4%	5.50'	30 fc	9.8'	10 fc	8'	8'	25	0.24	20	0.24				
	5.00° 919	0° - 20°	336	15%	6.50'	22 fc	11.6'	7 fc	12'	10'	22	0.20	17	0.20				
	10.00° 917	0° - 30°	649	30%	7.50'	16 fc	13.4'	5 fc	16'	12'	14	0.14	7	0.09				
	15.00° 908	0° - 40°	977	45%	8.50'	13 fc	15.2'	4 fc	Delivered Illuminance Rating: (DIR)									
	20.00° 891	0° - 60°	1,589	73%	10.00'	9 fc	17.9'	3 fc	106 FC per W/Sq. Ft.    84 FC per W/Sq. Ft.									
	30.00° 840	0° - 80°	1,928	88%	12.00'	6 fc	21.4'	2 fc	2' Suspension Length Square rooms used for multiple units: - RCR 2: Length & Width = Ceiling Ht. - 4.5' x 5.00' - RCR 4: Length & Width = Ceiling Ht. - 4.5' x 2.50' * Average Footcandles at 2.5' Above Floor ** Exceeds spacing criteria by 69% *** Exceeds spacing criteria by -1% **** Exceeds spacing criteria by -23%									
	40.00° 761	0° - 90°	2,018	92%	14.00'	5 fc	25.0'	1 fc	Lamp Multiplier: 15L x 0.573									
	50.00° 651	Total	2,183	100%	16.00'	4 fc	28.6'	1 fc	CCT Multiplier: 27K x 0.971, 30K x 0.985, 40K x 1.03									
	60.00° 273																	
	70.00° 66																	
	80.00° 42																	
	90.00° 19																	

Delivered Lumens: 2,183  
 Luminaire Watts: 18  
 LER: 121.28

CP at 0deg (Nadir): 920  
 CRI: 85+

Beam Angle: 93.07  
 Spacing Ratio: 1.35

Lamp Multiplier: 15L x 0.573  
 CCT Multiplier: 27K x 0.971, 30K x 0.985, 40K x 1.03




# MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION. NOTE: THIS IS TYPICAL OF RLM SPECIFICATION FOR MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.




## WALL MOUNTING


**CP104 - SMALL DRIVER CANOPY (STANDARD)**  
MAY BE USED AS SPLICE BOX FOR DIRECT FEED  
NOT AVAILABLE W/ PA16 & PA16F




**CP106 - LARGE DRIVER CANOPY**  
MAY BE USED AS SPLICE BOX FOR DIRECT FEED



**CP6/RMD - REMOTE MOUNT DRIVER**  
MOUNTS DIRECTLY TO WALL OR OCTAGON STYLE J-BOX




CUSTOM AND OTHER WALL ARMS AVAILABLE - CONTACT FACTORY. ARMS MAY BE FIELD CUT ON WALL SIDE - FIXTURE SIDE THREADED 3/4" NPT REQUIRES SEALANT FOR WET LOCATION.




## CEILING MOUNTING

**RDC5 - SMALL DRIVER CANOPY (STANDARD)**  
MOUNTS TO 4" OCTO J-BOX



**CP13 - LARGE DRIVER CANOPY**




**HM\***  
HANG STRAIGHT  
45° SWIVEL 5/8" OD STEM - 3/8" IP




ORDER: HM (Length)  
SPECIFY LENGTH:  
HM3 - 3" HM24 - 24"  
HM6 - 6" HM36 - 36"  
HM12 - 12" HM48 - 48"  
HM18 - 18" HM72 - 72"  
HMLC(XX)  
Custom Length  
(Specify in Inches)

**PM\***  
RIGID PENDANT MOUNT  
RIGID 5/8" OD STEM - 3/8" IP



ORDER: PM (Length)  
SPECIFY LENGTH:  
PM3 - 3" PM24 - 24"  
PM6 - 6" PM36 - 36"  
PM12 - 12" PM48 - 48"  
PM18 - 18" PM72 - 72"  
PMLC(XX)  
Custom Length  
(Specify in Inches)

**AT\*\***  
HANG STRAIGHT ALL THREAD  
45° SWIVEL 5/8" OD STEM - 1/4" IP




ORDER: AT (Length)  
SPECIFY LENGTH:  
AT12 - 12"  
AT24 - 24"  
AT36 - 36"  
AT48 - 48"  
AT60 - 60"  
AT72 - 72"

FIELD CUT THREADED PIPE TO LENGTH NEEDED. CUT PIPE COVER UP SHORTER THAN THREADED PIPE. SUPPLY COVER OVER THREADED PIPE.

\*MAXIMUM ONE PIECE STEM LENGTH IS 72". \*\*MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS.  
\*\*ORDER IN 12" INCREMENTS, ODD SIZES MAY BE FIELD CUT


## EMERGENCY BATTERY OPTIONS

**EMCR - LARGE DRIVER CANOPY FOR 10W EMERGENCY BATTERY**




## REMOTE EMERGENCY BATTERY OPTIONS

**EMRM\* - 7W REMOTE EMERGENCY BATTERY (50' MAX)**



A	B	C
1.3	12.6	13.0

**EMEN\* - 7W REMOTE EMERGENCY BATTERY WITH ENCLOSURE (50' MAX)**



A	B	C
2.0	17.0	6.2

\*OTHER EM BATTERY SIZES AVAILABLE. CONTACT FACTORY.



# COLOR OPTIONS - POWDER COAT PAINT FINISHES

NOTE: NO PRINTED IMAGE CAN EQUAL THE EXACT COLOR OF FINISH ON METAL.  
SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.



## STANDARD CORD / STEM / CANOPY FINISHES

FIXTURE COLOR	STANDARD CORD COLOR	STANDARD CANOPY / STEM COLOR
Matte White, Textured White	Matte White	Matte White
Gloss White	Matte White	Gloss White
Matte Black, Gloss Black, Textured Black	Matte Black	Matte Black
All Others	Matte Black	Same Color as Fixture
Custom Color	Contact Factory	Contact Factory

## PAINT TIMES

TIER	COST	AVERAGE PAINT TIME*
Tier 1 - Standard Finishes	\$	⌚
Tier 2 - Typical Finishes	\$\$	⌚⌚
Tier 3 - Special Metal Finishes	\$\$\$	⌚⌚⌚
Custom Color	Contact Factory	Contact Factory

\*CONTACT FACTORY FOR SPECIFIC PRODUCT LEAD TIMES


## TIER 1 - STANDARD FINISHES



## TIER 2 - TYPICAL FINISHES



## TIER 3 - SPECIAL METAL FINISHES



## CUSTOM COLOR FINISHES

CONTACT FACTORY

**CC**  
Custom Color



\*UNAVAILABLE FOR WET LOCATION

