



# 12" OPAL ACRYLIC

## WA SERIES



### WA1212LX

#### APPLICATION

12" opal acrylic pendant for wide general illumination.

#### FEATURES

WA1212LX opal acrylic refractor glows evenly with no glare or hot spots. Ideal for libraries, churches, retail or any area where smooth, glare free illumination is required. Single mid-powered LED Modules. A wide variety of mounting options. LED module and driver are serviceable for future replacement and maintenance.

#### FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. Variety of standard and custom finishes are available. All exposed materials are chromate pretreated to resist corrosion.

#### ELECTRONICS


LED system features high brightness white Nichia LEDs. 3-step MacAdam Ellipse binning and CRI 80 minimum. Higher CRI, R9 and custom LED configurations are available; consult factory. Variety of electronic 120V/277V and dimming devices. Motion, daylight and wireless controls available. LED module is 2 circuit with 2 drivers for multicircuit option as well as safety

#### CONSTRUCTION

Fixture shades are spun in our factory from 0.060" high purity aluminum. Lens is UV stabilized matte white acrylic.

#### CODE COMPLIANCE

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.



A	B
13.12 333.3 mm	13.9 353.1 mm

LUMENS / WATTAGE DATA				
PART NUMBER	SOURCE LUMENS <sup>1</sup>	DELIVERED LUMENS <sup>2</sup>	SYSTEM WATTS	LPW
WA1212LX65L	6500	5969	56.3	106
WA1212LX100L	10000	8933	88.0	102

SERIES	LUMENS <sup>1</sup>	CCT	DRIVER / DIMMING <sup>3</sup>	OPTIONS <sup>4</sup>	MOUNTING <sup>5</sup>	REFRACTOR	FINISH <sup>8</sup>
WA1212LX	65L 6500 Lm 100L 10000 Lm	27K 2700K 30K 3000K 35K 3500K 40K 4000K	EX Electronic Driver, 120V/277V DS10X 10%, 0-10V, 120V/277V DO10X 1%, 10-0V, 120V/277V DO103 1%, 0-10V, 347V	FS Fusing 2CIR 2 Circuit SC2 Safety Cable, Lens to Fixture	CP113 <sup>6</sup> Driver Housing	WA1315 Matte Opal Acrylic	MW <sup>9</sup> Matte White MB <sup>9</sup> Matte Black PT <sup>9</sup> Platinum Silver CC Custom Color
					RM Remote Driver		
					HM <sup>7</sup> Hang Straight AT <sup>7</sup> Hang Straight All Thread PM <sup>7</sup> Rigid Pendant Mount CD <sup>7</sup> Cord / Cable Mount HC Hook & Cord		
					EMERGENCY BATTERY OPTIONS		
					EMRM 7W Remote EM EMEN 7W Remote with Enclosure		

**EXAMPLE:** WA1212LX100L30KEX/CP113HM36/WA1315/MW

**NOTES:**  
 1 Nominal Source Lumens at 35K 2 Nominal Delivered Lumens at 35K with WA1315MW 3 Contact Factory for Additional Options 4 See Product Options Page for Details 5 See Mounting Page for Details on Components and Finishes  
 6 CP113 Required 7 Specify Length in Inches: See Mounting Page for Available Lengths 8 See Color Page for More Options / Consult Factory for Special Finishes 9 Standard Finishes



PROJECT: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_ TYPE: \_\_\_\_\_



# 12" OPAL ACRYLIC

## WA SERIES / FIXTURE OPTIONS



### STANDARD FINISHES

**MW**  
MATTE WHITE



**MB**  
MATTE BLACK




**PT**  
PLATINUM SILVER



### MOUNTING TYPES

**HM / AT / PM**  
HANG STRAIGHT / ALL THREAD / PENDANT




A	B
11.1	3.3
281.9 mm	84.8 mm

**CD**  
CORD / CABLE MOUNT



A	B
11.1	3.3
281.9 mm	84.8 mm

**HC**  
HOOK CORD



A
4.0
101.6 mm



# 12" OPAL ACRYLIC

## WA SERIES / PHOTOMETRIC DATA



WA1212LEDLX-100L-35K-E1-WA1315-MW

CANDLEPOWER CURVE	INTENSITY	ZONAL LUMENS	SINGLE UNIT: PERFORMANCE INITIAL FOOTCANDLES BASED ON IES BEAM ANGLE		MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT							
	0.00°	0° - 10°	119	1%	Mounting Height AFF	FC at Center on Floor	Ceiling Height	Fixture Spacing	RCR 1		RCR 3	
	0.00° 1,238	0° - 20°	460	5%	8.0'	19 fc	17'	18'	FC +	W/Sq. Ft.	FC +	W/Sq. Ft.
	20.00° 1,186	0° - 30°	1,004	11%	10.0'	12 fc	21'	22'	21	0.24	15	0.24
	40.00° 1,165	0° - 40°	1,737	19%	12.0'	9 fc	25'	24'	16	0.18	8	0.13
	60.00° 1,100	0° - 60°	3,636	41%	14.0'	6 fc	Delivered Illuminance Rating: [DIR]		13	0.15	12	0.19
	80.00° 924	0° - 80°	5,714	64%	16.0'	5 fc	3' Suspension Length Square rooms used for multiple units: - RCR 1: Length & Width = Ceiling Ht. - 5.5' x 10.00 - RCR 3: Length & Width = Ceiling Ht. - 5.5' x 3.33					
	90.00° 798	0° - 90°	6,650	74%	20.0'	3 fc	* Average Footcandles at 2.5' Above Floor					
	100.00° 659	Total	8,933	100%	24.0'	2 fc	** Exceeds spacing criteria by 9%					
	110.00° 511				28.0'	2 fc	*** Exceeds spacing criteria by -15%					
	120.00° 368						Lamp Multiplier: 65L x 1, 100L x 1.49					
	140.00° 119						CCT Multiplier: 40K x 1.031, 30K x 0.979, 27K x 0.959					
	160.00° 0											
	180.00° 0											

Delivered Lumens: **8,933**  
Luminaire Watts: **88**  
LER: **101.51**

CP at 0deg (Nadir): 1,238  
CRI: 80

Lamp Multiplier: 65L x 1, 100L x 1.49  
CCT Multiplier: 40K x 1.031, 30K x 0.979, 27K x 0.959






# MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES, CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION. NOTE: THIS IS TYPICAL OF LUMEN MAX SPECIFICATION FOR PENDANT MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.




## MOUNTING TYPES

<p><b>HM*</b> HANG STRAIGHT 45° SWIVEL 5/8" OD STEM - 3/8" IP</p>  <p>ORDER: <b>HM</b> (Length) SPECIFY LENGTH: <b>HM3</b> - 3"    <b>HM24</b> - 24" <b>HM6</b> - 6"    <b>HM36</b> - 36" <b>HM12</b> - 12"    <b>HM48</b> - 48" <b>HM18</b> - 18"    <b>HM72</b> - 72" <b>HMLC(XX)</b> Custom Length (Specify in Inches)</p>	<p><b>PM*</b> RIGID PENDANT MOUNT RIGID 5/8" OD STEM - 3/8" IP</p>  <p>ORDER: <b>PM</b> (Length) SPECIFY LENGTH: <b>PM3</b> - 3"    <b>PM24</b> - 24" <b>PM6</b> - 6"    <b>PM36</b> - 36" <b>PM12</b> - 12"    <b>PM48</b> - 48" <b>PM18</b> - 18"    <b>PM72</b> - 72" <b>PMLC(XX)</b> Custom Length (Specify in Inches)</p>	<p><b>AT**</b> HANG STRAIGHT ALL THREAD 45° SWIVEL 5/8" OD STEM - 1/4" IP</p>  <p>ORDER: <b>AT</b> (Length) SPECIFY LENGTH: <b>AT12</b> - 12" <b>AT24</b> - 24" <b>AT36</b> - 36"</p> 	<p><b>CD</b> CORD / CABLE MOUNT SJ CORD WITH 1/16" SS CABLE</p>  <p>ORDER: <b>CD</b> (Length) SPECIFY LENGTH: <b>CD36</b> - 36" <b>CD72</b> - 72" <b>CD144</b> - 144" <b>CDLC(XX)</b> Custom Length (Specify in Inches)</p>	<p><b>HC</b> HOOK &amp; CORD FOR INDEPENDENT MOUNTING</p>  <p>ORDER: <b>HC</b></p>
--	---	--	--	---

\*MAXIMUM ONE PIECE STEM LENGTH IS 72". \*\*MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS.


## CEILING MOUNT CANOPY

**CP113** - DRIVER COMPARTMENT WITH LEADS (REQUIRED)




## REMOTE EMERGENCY BATTERY OPTIONS

**EMRM\*** - 7W REMOTE EMERGENCY BATTERY (50" MAX)



A	B	C
1.3	12.6	13.0

**EMEN\*** - 7W REMOTE EMERGENCY BATTERY WITH ENCLOSURE (50" MAX)



A	B	C
2.0	17.0	6.2

\*OTHER EM BATTERY SIZES AVAILABLE, CONSULT FACTORY

## ADDITIONS

**FS** - FUSING

Slow blow type fuse protects fixture against voltage surges. Factory installed.



**LSP10 - SM** - SURGE PROTECTOR

Surge protector absorbs transient electrical spikes and protects fixtures and electronics 120/277v. Re-sets after surge. Factory Installed.



## SAFETY CABLE OPTIONS

**SC1** - SAFETY CABLE

1/16" stainless steel safety cable for added support. Standard kit is 18" and double barrel locks are provided. Approved for California seismic requirements. Rated at 50 lbs.



**SC2** - SAFETY CABLE

1/16" Stainless steel cable holds door to fixture




# COLOR OPTIONS - POWDER COAT PAINT FINISHES

NOTE: NO PRINTED IMAGE CAN EQUAL THE EXACT COLOR OF FINISH ON METAL.  
SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.



## STANDARD CORD / STEM / CANOPY FINISHES

FIXTURE COLOR	STANDARD CORD COLOR	STANDARD CANOPY / STEM COLOR
Matte White, Textured White	Matte White	Matte White
Gloss White	Matte White	Gloss White
Matte Black, Gloss Black, Textured Black	Matte Black	Matte Black
All Others	Matte Black	Same Color as Fixture
Custom Color	Contact Factory	Contact Factory

## PAINT TIMES

TIER	COST	AVERAGE PAINT TIME*
Tier 1 - Standard Finishes	\$	⓪
Tier 2 - Typical Finishes	\$\$	⓪⓪
Custom Color	Contact Factory	Contact Factory

\*CONTACT FACTORY FOR SPECIFIC PRODUCT LEAD TIMES

## TIER 1 - STANDARD FINISHES



## TIER 2 - TYPICAL FINISHES



## CUSTOM COLOR FINISHES

CONTACT FACTORY

**CC**  
Custom Color



\*UNAVAILABLE FOR WET LOCATION

