



A	B	C	D	S1	S2
4.6	.625	14.1	9.3	7.4	9.1
116.8 mm	15.9 mm	358.1 mm	236.2 mm	188.0 mm	231.1 mm

SGW8LEDGV - TRIM FLANGE / NON-IC RATED

APPLICATION

8" Round aperture shallow recessed LED wall wash for general illumination.

FEATURES

Two-stage optical system with medium depth reflector design delivers smooth glare-free general illumination. Tool-less LED module, driver, and J-Box access. Multi-Bar mounting brackets. BH27 Standard mounting bars included. Posi-lock trim retention springs. Integral 0.625" collar, with Deep Ceiling Extension (PR), consult factory.

TRIM FINISH

A variety of architectural powdercoat and anodized finishes are available.

Matte White flange is standard.

ELECTRONICS

GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 85+. Higher CRI, R9 and custom LED configurations are available; consult factory. A variety of electronic 120V/277V and dimming drivers available.

CONSTRUCTION

Housing/frame constructed of #20 ga. galvanized steel to resist corrosion. Self-flanged one piece trim spun from 0.063" thick high purity aluminum and finished to specification. Passive machined aluminum heatsink.

CODE COMPLIANCE

BAA Compliant. Non-IC rated. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.

WATTAGE TO LUMENS UPDATE			
CURRENT PART NUMBER EXAMPLE	PREVIOUS PART NUMBER EXAMPLE	SOURCE LUMENS ¹	SYSTEM WATTS
SGW8LEDGV15L	SGW8LEDGV14W	1500	13.3
SGW8LEDGV27L	SGW8LEDGV26W	2700	22.3
SGW8LEDGV37L	SGW8LEDGV37W	3700	29.1
SGW8LEDGV55L	SGW8LEDGV55W	5500	42.6

SERIES	LUMENS ¹	CCT	DRIVER / VOLTAGE ²	OPTIONS ³	TRIM	FINISH ⁶	TRIM OPTIONS	
SGW8LEDGV	15L	1500 Lm	27K 2700K	E Electronic Driver	1 120V 2 277V	AR8922GV ⁷	SG ⁸ Semi-Diffuse HZ Haze Full Diffuse MW Matte White MB Matte Black PT Platinum Silver OB Oil Rubbed Bronze CH Charcoal AC Anodic Champagne AS Anodic Sapphire AM Anodic Malachite SN Sun Gold CO Copper Metallic GH Graphite AMB Anti Microbial Finish CC Custom Color	
	27L	2700 Lm	30K 3000K	DS10 10% 0-10V				BH27 ⁴ 27" Solid Bars
	37L	3700 Lm	35K 3500K	DO10 1% 0-10V	H12 12" - 24" Expandable Bars			GS Gasket
	40K	4000K	4000K	DS2W1 1% ELV/MLV, 120V	H06 6" - 12" Expandable Bars			
	55L	5500 Lm	50K 5000K	DLTE1 1% Lutron® 2-Wire Forward Phase, 120V DL3E 1% Lutron® EcoSystem®, Fade EL10 1% eldoLED ED01 0.1% eldoLED DALI DALI Control	CB24 24" C-Channel Bars EM Integral Emergency Battery FS Fusing EB Black Housing CR Corrosion Resistant PR ⁵ Deep Ceiling Extension GR Goof Ring AMB Anti Microbial Finish			

EXAMPLE: SGW8LEDGV37L30KE1BH27/AR8922GVMWSK

NOTES:
1 Nominal Source Lumens at 35K 2 Contact Factory for Additional Options 3 See Product Options Page For Details 4 Standard Bar Hangers 5 Contact Factory 6 Contact Factory for Special Finishes
7 Matte White Flange Standard 8 Standard Finish 9 Standard Lens



PROJECT: _____
TYPE: _____



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.