

ETPH

PAR LED LAMPHOLDER

Spectrum's PAR LED Lampholder for accent lighting.

PROJECT: _____

QUANTITY: _____ TYPE: _____



FEATURES

SERIES

Fixture can be used with long neck PAR30 lamps as well as PAR16, PAR20, and PAR38 lamps. ET-PH-BET has socket position for long neck lamps.

Vertical slide adjustment slot allows numerous fixture heights. Precise, rigid aiming and full 350° horizontal rotation.

Integral ON/OFF switch and track polarity indicator are standard.

PAR Lamp not included (sold separately).

LAMP

(1) 50W PAR20, 75W PAR16, 75W PAR30 or 250W PAR38; 120V, E26 medium base.

LISTING

cULus Certified. Suitable for dry locations.

PRODUCT SELECTOR GUIDE

SERIES	LAMP TYPE	ADAPTOR	FINISH
ET	PH	BET	

EXAMPLE

ET	PH	BET	MW
----	----	-----	----


SERIES	LAMP TYPE	ADAPTOR	FINISH
ET	PH PAR Holder	BET Basix 1 CIR/1 NEUT 120V	MW Matte White MB Matte Black



COPYRIGHT 2023 SPECTRUM LIGHTING, INC.


FIXTURE DIMENSIONS

0° POSITION




A
2.5 63.5 mm

45° TILT




A	B	C
2.17 55.118 mm	2.97 75.438 mm	5.37 136.398 mm

90° TILT



A
3.0 76.2 mm

SIDE VIEW



A	B
5.25 133.35 mm	5.37 136.398 mm

FINISH

MW
Matte White



MB
Matte Black



PAINT TIMES

TIER	COST	AVERAGE PAINT TIME*
Tier 1 - Standard Finishes	\$	
Custom Color	Contact Factory	Contact Factory

*CONTACT FACTORY FOR SPECIFIC PRODUCT LEAD TIMES

Performance data examples generated using Green Creative photometric data for bare lamps, identified below:

CANDLEPOWER CURVE TEST ETPH BET xx with bare lamp GreenCreative930FL40 11WPAR30 (34903)	INTENSITY CANDELA 0° AZIMUTH	ZONAL LUMENS	SINGLE UNIT: PERFORMANCE HORIZONTAL FOOTCANDLES INITIAL DOWNLIGHT ONLY	MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES HORIZONTAL FOOTCANDLES AND WATTS/SQ FT																																																																
	0°	0° - 10° 165 16%	<table border="1"> <thead> <tr> <th>Mounting Distance</th> <th>FC at Beam Center</th> <th>Diameter at Beam Angle</th> <th>FC at Beam Edge</th> </tr> </thead> <tbody> <tr><td>8'</td><td>30 fc</td><td>5.3'</td><td>13 fc</td></tr> <tr><td>10'</td><td>19 fc</td><td>6.6'</td><td>8 fc</td></tr> <tr><td>12'</td><td>13 fc</td><td>8.0'</td><td>6 fc</td></tr> <tr><td>14'</td><td>10 fc</td><td>9.3'</td><td>4 fc</td></tr> <tr><td>16'</td><td>8 fc</td><td>10.6'</td><td>3 fc</td></tr> <tr><td>20'</td><td>5 fc</td><td>13.3'</td><td>2 fc</td></tr> <tr><td>24'</td><td>3 fc</td><td>15.9'</td><td>1 fc</td></tr> <tr><td>28'</td><td>2 fc</td><td>18.6'</td><td>1 fc</td></tr> </tbody> </table>	Mounting Distance	FC at Beam Center	Diameter at Beam Angle	FC at Beam Edge	8'	30 fc	5.3'	13 fc	10'	19 fc	6.6'	8 fc	12'	13 fc	8.0'	6 fc	14'	10 fc	9.3'	4 fc	16'	8 fc	10.6'	3 fc	20'	5 fc	13.3'	2 fc	24'	3 fc	15.9'	1 fc	28'	2 fc	18.6'	1 fc	<table border="1"> <thead> <tr> <th rowspan="2">Ceiling Height</th> <th rowspan="2">Fixture Spacing</th> <th colspan="2">RCR 3</th> <th colspan="2">RCR 5</th> </tr> <tr> <th>FC *</th> <th>W/Sq. Ft.</th> <th>FC *</th> <th>W/Sq. Ft.</th> </tr> </thead> <tbody> <tr><td>12'</td><td>4'</td><td>60</td><td>0.67</td><td>48</td><td>0.61</td></tr> <tr><td>16'</td><td>6'</td><td>28</td><td>0.31</td><td>22</td><td>0.28</td></tr> <tr><td>20'</td><td>8'</td><td>16</td><td>0.18</td><td>13</td><td>0.16</td></tr> </tbody> </table>	Ceiling Height	Fixture Spacing	RCR 3		RCR 5		FC *	W/Sq. Ft.	FC *	W/Sq. Ft.	12'	4'	60	0.67	48	0.61	16'	6'	28	0.31	22	0.28	20'	8'	16	0.18	13	0.16
	Mounting Distance	FC at Beam Center		Diameter at Beam Angle	FC at Beam Edge																																																															
	8'	30 fc		5.3'	13 fc																																																															
	10'	19 fc		6.6'	8 fc																																																															
	12'	13 fc		8.0'	6 fc																																																															
	14'	10 fc		9.3'	4 fc																																																															
	16'	8 fc		10.6'	3 fc																																																															
	20'	5 fc		13.3'	2 fc																																																															
	24'	3 fc		15.9'	1 fc																																																															
	28'	2 fc		18.6'	1 fc																																																															
Ceiling Height	Fixture Spacing	RCR 3		RCR 5																																																																
		FC *	W/Sq. Ft.	FC *	W/Sq. Ft.																																																															
12'	4'	60	0.67	48	0.61																																																															
16'	6'	28	0.31	22	0.28																																																															
20'	8'	16	0.18	13	0.16																																																															
0° 1938	0° - 20° 495 47%	8' 30 fc 5.3' 13 fc	12' 4' 60 0.67 48 0.61																																																																	
5° 1798	0° - 30° 757 72%	10' 19 fc 6.6' 8 fc	16' 6' 28 0.31 22 0.28																																																																	
15° 1178	0° - 40° 892 85%	12' 13 fc 8.0' 6 fc	20' 8' 16 0.18 13 0.16																																																																	
25° 558	0° - 60° 1003 95%	14' 10 fc 9.3' 4 fc	Delivered Illuminance Rating: (DIR) 90 FC per W/Sq. Ft. 79 FC per W/Sq. Ft.																																																																	
35° 209	0° - 80° 1048 99%	16' 8 fc 10.6' 3 fc																																																																		
45° 83	0° - 90° 1053 100%	20' 5 fc 13.3' 2 fc	1' Suspension Length to luminous aperture Square rooms used for multiple units: RCR 3: Length & Width = Ceiling Ht. - 3.5' x 3.33 RCR 5: Length & Width = Ceiling Ht. - 3.5' x 2.00 * Average Initial Footcandles at 2.5' Above Floor																																																																	
55° 49	Total 1055 100%	24' 3 fc 15.9' 1 fc																																																																		
90° 1		28' 2 fc 18.6' 1 fc																																																																		

Delivered Lumens: 1055
Luminaire Watts: 10.94
LER: 96.44

CP at 0° (Nadir): 1938

Beam Angle: 37°
Spacing Ratio: 0.58



CANDLEPOWER CURVE TEST ETPH BET xx with bare lamp GreenCreative930FL40 15.5WPAR38 (34921)	INTENSITY CANDELA 0° AZIMUTH	ZONAL LUMENS	SINGLE UNIT: PERFORMANCE HORIZONTAL FOOTCANDLES INITIAL DOWNLIGHT ONLY	MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES HORIZONTAL FOOTCANDLES AND WATTS/SQ FT																																																																
	0°	0° - 10° 258 18%	<table border="1"> <thead> <tr> <th>Mounting Distance</th> <th>FC at Beam Center</th> <th>Diameter at Beam Angle</th> <th>FC at Beam Edge</th> </tr> </thead> <tbody> <tr><td>8'</td><td>46 fc</td><td>5.2'</td><td>19 fc</td></tr> <tr><td>10'</td><td>29 fc</td><td>6.6'</td><td>12 fc</td></tr> <tr><td>12'</td><td>20 fc</td><td>7.9'</td><td>9 fc</td></tr> <tr><td>14'</td><td>15 fc</td><td>9.2'</td><td>6 fc</td></tr> <tr><td>16'</td><td>11 fc</td><td>10.5'</td><td>5 fc</td></tr> <tr><td>20'</td><td>7 fc</td><td>13.1'</td><td>3 fc</td></tr> <tr><td>24'</td><td>5 fc</td><td>15.7'</td><td>2 fc</td></tr> <tr><td>28'</td><td>4 fc</td><td>18.4'</td><td>2 fc</td></tr> </tbody> </table>	Mounting Distance	FC at Beam Center	Diameter at Beam Angle	FC at Beam Edge	8'	46 fc	5.2'	19 fc	10'	29 fc	6.6'	12 fc	12'	20 fc	7.9'	9 fc	14'	15 fc	9.2'	6 fc	16'	11 fc	10.5'	5 fc	20'	7 fc	13.1'	3 fc	24'	5 fc	15.7'	2 fc	28'	4 fc	18.4'	2 fc	<table border="1"> <thead> <tr> <th rowspan="2">Ceiling Height</th> <th rowspan="2">Fixture Spacing</th> <th colspan="2">RCR 3</th> <th colspan="2">RCR 5</th> </tr> <tr> <th>FC *</th> <th>W/Sq. Ft.</th> <th>FC *</th> <th>W/Sq. Ft.</th> </tr> </thead> <tbody> <tr><td>12'</td><td>4'</td><td>83</td><td>0.96</td><td>67</td><td>0.87</td></tr> <tr><td>16'</td><td>6'</td><td>38</td><td>0.44</td><td>31</td><td>0.40</td></tr> <tr><td>20'</td><td>8'</td><td>22</td><td>0.25</td><td>18</td><td>0.23</td></tr> </tbody> </table>	Ceiling Height	Fixture Spacing	RCR 3		RCR 5		FC *	W/Sq. Ft.	FC *	W/Sq. Ft.	12'	4'	83	0.96	67	0.87	16'	6'	38	0.44	31	0.40	20'	8'	22	0.25	18	0.23
	Mounting Distance	FC at Beam Center		Diameter at Beam Angle	FC at Beam Edge																																																															
	8'	46 fc		5.2'	19 fc																																																															
	10'	29 fc		6.6'	12 fc																																																															
	12'	20 fc		7.9'	9 fc																																																															
	14'	15 fc		9.2'	6 fc																																																															
	16'	11 fc		10.5'	5 fc																																																															
	20'	7 fc		13.1'	3 fc																																																															
	24'	5 fc		15.7'	2 fc																																																															
	28'	4 fc		18.4'	2 fc																																																															
Ceiling Height	Fixture Spacing	RCR 3		RCR 5																																																																
		FC *	W/Sq. Ft.	FC *	W/Sq. Ft.																																																															
12'	4'	83	0.96	67	0.87																																																															
16'	6'	38	0.44	31	0.40																																																															
20'	8'	22	0.25	18	0.23																																																															
0° 2915	0° - 20° 773 54%	8' 46 fc 5.2' 19 fc	12' 4' 83 0.96 67 0.87																																																																	
5° 2873	0° - 30° 1123 79%	10' 29 fc 6.6' 12 fc	16' 6' 38 0.44 31 0.40																																																																	
15° 1947	0° - 40° 1280 90%	12' 20 fc 7.9' 9 fc	20' 8' 22 0.25 18 0.23																																																																	
25° 778	0° - 60° 1383 97%	14' 15 fc 9.2' 6 fc	Delivered Illuminance Rating: (DIR) 87 FC per W/Sq. Ft. 77 FC per W/Sq. Ft.																																																																	
35° 244	0° - 80° 1419 100%	16' 11 fc 10.5' 5 fc																																																																		
45° 85	0° - 90° 1422 100%	20' 7 fc 13.1' 3 fc	1' Suspension Length to luminous aperture Square rooms used for multiple units: RCR 3: Length & Width = Ceiling Ht. - 3.5' x 3.33 RCR 5: Length & Width = Ceiling Ht. - 3.5' x 2.00 * Average Initial Footcandles at 2.5' Above Floor																																																																	
55° 41	Total 1424 100%	24' 5 fc 15.7' 2 fc																																																																		
90° 0		28' 4 fc 18.4' 2 fc																																																																		

Delivered Lumens: 1424
Luminaire Watts: 15.69
LER: 90.76

CP at 0° (Nadir): 2915

Beam Angle: 36°
Spacing Ratio: 0.61