


FIT SIZE	
SERIES	4"
MINIMUM	4 <sup>5/8</sup>
MAXIMUM	4 <sup>7/8</sup>



A	B	C
4.0	5.4	6.2
101.6 mm	137.2 mm	157.5 mm

Ceiling Cutout: Ø 4<sup>5/8</sup>"

### SGRTW4FX - TRIM FLANGE / NON-IC RATED

#### QUICK SHIP

Quick Ship highlights products that can ship in 3 - 5 working days.

#### APPLICATIONS

FX series 4" diameter retrofit wall wash series. Designed for general downlighting with smooth light distribution.

#### FEATURES

One piece spun housing seals ceiling aperture preventing light leaks. Wide range of apertures. Companion new construction fixtures available. Auto dim thermal protector for long term reliability. Zhaga international standard LED module for ease of maintenance and future replacement. Tool-less LED module and driver access. Includes set of three retrofit clips to accommodate most installations. Goof ring available for oversized or damaged ceiling installations. Fixture will work in up to 1" thick ceiling<sup>1</sup>.

#### TRIM FINISH

A variety of architectural powdercoat and anodized finishes are available. Matte White flange is standard.

#### ELECTRONICS

LED system features high efficacy PHILIPS LEDs. Standard CRI is >80. Drivers are overload and short circuit protected as well as thermally regulated. Sound rating A. L70 at >60,000 hours.

#### CONSTRUCTION

Housing constructed of .060" aluminum and powdercoated white to resist corrosion. Self-flanged one piece trim spun from 0.060" thick high purity aluminum and finished to specification. Passive machined aluminum heatsink.

#### CODE COMPLIANCE

BAA Compliant. Non-IC rated. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Optional Wet location listed trim. LM79/LM80 data available. Manufactured and tested to UL standards No. 1598/8750.

#### LUMENS / WATTAGE DATA

PART NUMBER	SOURCE LUMENS <sup>2</sup>	DELIVERED LUMENS <sup>3</sup>	SYSTEM WATTS	LPW
SGRTW4FX10L	1000	625	9	68
SGRTW4FX15L	1500	938	13	72
SGRTW4FX20L	2000	1250	17	74
SGRTW4FX30L	3000	1875	25	75
SGRTW4FX40L	4000	2500	35	72

SERIES	LUMENS <sup>2</sup>	CCT	DRIVER / VOLTAGE <sup>4</sup>	OPTIONS <sup>5</sup>	TRIM	FINISH	TRIM OPTIONS
SGRTW4FX	10L 1000 Lm	27HK 2700K	DX 1%, 0-10V, 120V/277V	<b>EM</b> Integral Emergency Battery <b>EMRM<sup>6</sup></b> Remote Emergency Battery Pack <b>FS</b> Fusing <b>CR</b> Corrosion Resistant	AR4923FX	<b>MW</b> Matte White <b>MB</b> Matte Black <b>SG</b> Semi-Diffuse <b>PT</b> Platinum Silver <b>CC<sup>7</sup></b> Custom Color	<b>WF</b> White Flange <b>MF<sup>8</sup></b> Matching Flange <b>SK<sup>9</sup></b> Skytex™ Lens <b>SKW</b> Skytex™ Lens Wet Location
	15L 1500 Lm	30K 3000K					
	20L 2000 Lm	35K 3500K					
	30L 3000 Lm	40K 4000K					
	40L 4000 Lm	50K 5000K					

#### QUICK SHIP

**EXAMPLE:** SGRTW4FX30L30KDX/AR4923FXSGMFSK

**NOTES:**  
 1 Consult Factory for Thicker Ceiling 2 Nominal Source Lumens at 35K 3 Nominal Delivered Lumens at 35K with MW,SK 4 Contact Factory for Additional Options 5 See Product Options Page For Details  
 6 Installer Responsible for EM Access 7 Contact Factory for Special Finishes 8 Flange Same Color as Inside of Trim 9 Standard Lens



PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.