



MINI ESPRESSO
DIRECT / INDIRECT
DAMP LOCATION
GV SERIES

PROJECT: _____
QUANTITY: _____ TYPE: _____



ME0713UDGV
GB - Gloss Black
PLI - Purple Interior



ME0713UDGV
PT - Platinum Silver
MWI - Matte White Interior



ME0713UDGV
MB - Matte Black
MWI - Matte White Interior



ME0713UDGV
MW - Matte White
TQI - Turquoise Interior

SERIES		LUMENS ¹		CCT		DRIVER / DIMMING ²		OPTIONS ³		MOUNTING ⁴		INTERIOR ⁷		FINISH ⁷	
ME0713UDGV		15L	1500 Lm	27K	2700K	EX	Electronic Driver, 120V/277V	FS	Fusing	RDC5M	Small Driver Canopy	MWI ⁶	Matte White	MW ⁶	Matte White
		27L	2700 Lm	30K	3000K	D010X	1%, 0-10V, 120V/277V			CD3X ⁵	3 Cable Mount with Cord	CCI	Custom Color	MB ⁸	Matte Black
				35K	3500K					EMCRM ⁶	10W Canopy Mounted EM	FCI	Fixture Color	PT ⁶	Platinum Silver
				40K	4000K					EMRM	7W Remote EM		Interior	CC	Custom Color
										EMEN	7W Remote with Enclosure				

EXAMPLE: ME0713UDGV27L35EX/RDC5MCD3×36MWIMW

NOTES:

1 Normal Source Lumens at 35K **2** Contact Factory for Additional Options **3** See Product Options Page For Details **4** See Mounting Page for Details on Components and Finishes **5** Specify Length in Inches: See Mounting Page for Available Lengths **6** EMCRM Replaces RDC5M **7** Reference Color Sheet Located on Product Webpage for Full List of Available Colors **8** Standard Finishes



Spectrum Lighting



MINI ESPRESSO DIRECT / INDIRECT DAMP LOCATION GV SERIES

LUMENS / WATTAGE DATA				
PART NUMBER	SOURCE LUMENS	DELIVERED LUMENS	SYSTEM WATTS	LPW
ME0713UDGV15L15L	3000	1896	20	95
ME0713UDGV27L27L	5400	3326	36	92

1 Nominal Source Lumens at 35K 2 Nominal Delivered Lumens at 35K

APPLICATION

Mini Espresso pendant features a unique hourglass shape for direct/indirect lighting.

FEATURES

SpecLume series fixtures offer contemporary style with functional luminaire performance. Fixtures are designed and manufactured in our factory. Passive integral heat sink. LED module and drivers are replaceable and upgradable. CT temps may be mixed to create daylight upright and warm downlight or other combinations.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. See mounting and color pages for standard finishes. Interior is Matte White unless specified. Custom Color interior finish available.

ELECTRONICS

GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 85+. Higher CRI, R9 and custom LED configurations are available; consult factory. Variety of electronic 120V/277V and dimming drivers.


CONSTRUCTION

Fixtures are spun in our factory from 0.063 high purity aluminum. Passive machined aluminum heatsink for optimal thermal management.

CODE COMPLIANCE

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.

HOUSING DIMENSIONS



A	B
7.5 190.5 mm	13.0 330.2 mm

SERIES SIZES

ME0713UDGV



CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

CD3X

3X CORD / CABLE MOUNT




ME0713UDGV SHOWN WITH RDC5CD3X





MINI ESPRESSO
DIRECT / INDIRECT
DAMP LOCATION
GV SERIES / PHOTOMETRIC DATA

ME0713UDGV 27L 27L 35K EX MWI




MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES, CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.
NOTE: THIS IS TYPICAL OF SPECLUME SPECIFICATION FOR PENDANT MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.




CEILING MOUNTING

RDC5M - SMALL DRIVER CANOPY (STANDARD)
MOUNTS TO 4" OCTO J-BOX




CD3X
3X CORD / CABLE MOUNT
SJ CORD WITH 1/16 SS CABLE

ORDER: **CD3X** (Length)
SPECIFY LENGTH:
CD3×36 - 36"
CD3×72 - 72"
CD3×144 - 144"
CD3XLC(XX)
Custom Length
(Specify in inches)




EMERGENCY BATTERY OPTIONS

EMCRM - LARGE DRIVER CANOPY FOR
10W EMERGENCY BATTERY
(FOR ROUND CEILING MOUNT TYPES)




REMOTE EMERGENCY BATTERY OPTIONS

EMRM* - 7W REMOTE EMERGENCY BATTERY
(50' MAX)



A	B	C
1.3	12.6	13.0

EMEN* - 7W REMOTE EMERGENCY BATTERY
WITH ENCLOSURE (50' MAX)



A	B	C
2.0	17.0	6.2

*OTHER EM BATTERY SIZES AVAILABLE, CONSULT FACTORY