




4" SHALLOW SQUARE DOWNLIGHT

GV SERIES / 5500 LUMENS MAX

recessed fixtures



SGE4SQGV - TRIM FLANGE / NON-IC RATED

APPLICATION

4" Square aperture shallow recessed LED downlight designed for general illumination.

FEATURES

Two-stage optical system with medium reflector design delivers smooth glare-free general illumination. Tool-less LED module, driver, and J-Box access. Multi-Bar mounting brackets. BH27 Standard mounting bars included. Posi-lock trim retention springs. Integral 0.625" collar, with Deep Ceiling Extension (PR), consult factory.

TRIM FINISH

A variety of architectural powdercoat and anodized finishes are available.

Matte White flange is standard.

ELECTRONICS

GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 85+. Higher CRI, R9 and custom LED configurations are available; consult factory. A variety of electronic 120V/277V and dimming drivers available.

CONSTRUCTION

Housing/frame constructed of #20 ga. galvanized steel to resist corrosion. Self-flanged one piece trim cast high purity aluminum and finished to specification. Passive machined aluminum heatsink.

CODE COMPLIANCE

BAA Compliant. Non-IC rated. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.

WATTAGE TO LUMENS UPDATE

CURRENT PART NUMBER EXAMPLE	PREVIOUS PART NUMBER EXAMPLE	SOURCE LUMENS ¹	SYSTEM WATTS
SGE4SQGV15L	SGE4SQLEDGV14W	1500	12
SGE4SQGV27L	SGE4SQLEDGV26W	2700	20
SGE4SQGV37L	SGE4SQLEDGV37W	3700	28
SGE4SQGV55L	SGE4SQLEDGV55W	5500	41

SERIES	LUMENS ¹	CCT	DRIVER / DIMMING ²	OPTIONS ³	TRIM	FINISH ⁶	TRIM OPTIONS
SGE4SQGV	15L 1500 Lm	27K 2700K	E Electronic Driver DS10 10% 0-10V DO10 1% 0-10V DS2W1 1%, ELV/MLV, 120V DLTE1 1% Lutron® 2-Wire Forward Phase, 120V DL3E 1% Lutron® EcoSystem®, Fade EL10 1%, eldoLED ED01 0.1%, eldoLED DALI DALI Control	1 120V 2 277V BH27 ⁴ 27" Solid Bars H12 12" - 24" Expandable Bars H06 6" - 12" Expandable Bars CB24 24" C-Channel Bars EM Integral Emergency Battery FS Fusing EB Black Housing CR Corrosion Resistant PR ⁵ Deep Ceiling Extension GR Goof Ring AMB Anti Microbial Finish	CA0244GV ⁷	MW ⁸ Matte White MB Matte Black AC Anodic Champagne AS Anodic Sapphire PT Platinum Silver OB Oil Rubbed Bronze CH Charcoal AS Anodic Sapphire AM Anodic Malachite SN Sun Gold CO Copper Metallic GH Graphite AMB Anti Microbial Finish CC Custom Color	SO ⁹ Micro Prism Solite™ Lens FG Frosted Glass Lens GS Gasket for Flange WL Wet Location
	27L 2700 Lm	30K 3000K					
	37L 3700 Lm	35K 3500K					
	55L 5500 Lm	40K 4000K 50K 5000K					

EXAMPLE: SGE4SQGV37L30KE1BH27/CA0244GV MW

NOTES:
 1 Nominal Source Lumens at 35K 2 Contact Factory for Additional Options 3 See Product Options Page For Details 4 Standard Bar Hangers 5 Contact Factory 6 Contact Factory for Special Finishes
 7 Matte White Flange Standard 8 Standard Finish 9 Standard Lens



PROJECT: _____
 TYPE: _____



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.