

**SR12SQLEDOA**

**APPLICATION**

12" square recessed LED downlight LED features soffit/area light for optimal performance.

**FEATURES**

Efficient, powerful LED light source, designed to exceed 50,000 hours of life (**L70**). Multi-Bar mounting brackets. All LED modules and drivers are replaceable and up-gradeable. New and Retrofit/Remodeler options. Wet location use screws fasteners. (4)

**FINISH**

A variety of architectural powdercoat and anodized finishes are available. Matte White flange is standard.

**ELECTRONICS**

LED module features high brightness white Nichia LEDs. 3-step MacAdam Ellipses binning and CRI 84 minimum. Variety of electronic 120V/277V and dimming drivers.




**CONSTRUCTION**

Housing constructed of .050 5052-H32 aluminum. Trim fabricated from aluminum extrusion and finished to specification.

**CODE COMPLIANCE**

BAA Compliant. Non-IC rated. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Optional Wet location. Manufactured and tested to UL standards No. 1598/8750.

WATTAGE TO LUMENS UPDATE			
CURRENT PART NUMBER EXAMPLE	PREVIOUS PART NUMBER EXAMPLE	SOURCE LUMENS <sup>1</sup>	SYSTEM WATTS
SR12SQLEDOA11L	SR12SQLEDOA14W	1100	14W
SR12SQLEDOA22L	SR12SQLEDOA26W	2200	26W
SR12SQLEDOA33L	SR12SQLEDOA37W	3300	37W
SR12SQLEDOA44L	SR12SQLEDOA47W	4400	47W



SERIES	LUMENS <sup>1</sup>	CCT	DRIVER / VOLTAGE <sup>2</sup>	OPTIONS <sup>3</sup>	TRIM	FINISH <sup>5</sup>	OPTIONS			
SR12SQLEDOA	11L 22L 33L 44L	1100 Lm 2200 Lm 3300 Lm 4400 Lm	30K 35K 40K 50K	3000K 3500K 4000K 5000K	E_ Electronic Driver 1 120V DS10_ 10%, 0-10V 2 277V	BH27 <sup>4</sup> 27" Solid Bars H12 12" - 24" Expandable Bars H06 6" - 12" Expandable Bars CB24 24" C-Channel Bars FS Fusing EM Integral Emergency Battery CR Corrosion Resistant RM Remodeler Housing	FLUSH TRIM FT1212 Flush Extruded Aluminum Door REGRESSED TRIM RT1212 Regressed Extruded Aluminum Door	MW <sup>6</sup> Matte White MB Matte Black PT Platinum CC <sup>6</sup> Custom Color MW <sup>6</sup> Matte White MB Matte Black PT Platinum Silver CC <sup>6</sup> Custom Color	TRIM / FLANGE FINISH MW <sup>6</sup> Matte White MB Matte Black PT Platinum CC <sup>6</sup> Custom Color WF <sup>7</sup> White Flange MF Matching Flange	FO <sup>8</sup> Matte White Acrylic Lens SO 90% Efficient WL <sup>9</sup> Solette Lens Wet Location

**EXAMPLE:** SR12SQLEDOA33L35KE1BH27/FT1212MW/FO

**NOTES:**  
1 Nominal Source Lumens 2 Contact Factory for Additional Options 3 See Product Options Page for Details 4 Standard Bar Hangers 5 Contact Factory for Special Finishes 6 Standard Finish  
7 For use with Non Matte White Trim Finish 8 Standard Lens 9 Trim Secured with 4 Screws



PROJECT: \_\_\_\_\_  
QUANTITY: \_\_\_\_\_ TYPE: \_\_\_\_\_

