




CLOUD 11"/14" ROUND SURFACE LIGHT

GV SERIES / 2700 LUMENS MAX



SERIES	A	B	C
SX1104RDLEDGV	3.9	10.0	11.0
SX1405RDLEDGV	4.7	12.8	13.8

PROJECT:

QUANTITY:

TYPE:

SX-RDLEDGV

APPLICATION

Cloud 11" and 14" surface round light for area illumination.

FEATURES

SpecLume series fixtures offer contemporary style with functional luminaire performance. Fixtures designed and manufactured in our factory. Fixture produces horizontal and vertical illumination. Designed for through wiring. Reflective gloss white reflector behind lamp for enhanced light output. Interchangeable LED module for ease of maintenance. A variety of mounting options are available.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. See mounting and color pages for standard finishes.

ELECTRONICS

GV LED system features high brightness white Samsung LED's. 3 step MacAdam Ellipse binning. Standard CRI: 85+. Higher CRI, R9 and custom LED configurations are available; consult factory. Variety of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Fixtures are spun in our factory from .063 high purity aluminum. Passive aluminum heatsink for optional thermal management. Formed UV stabilized opal white acrylic diffuser.

CODE COMPLIANCE

ARRA Compliant. ETL listed for damp locations. ADA Compliant, excluding: SX1405LEDGV. Manufactured and tested to UL standards No. 1598/8750.

WATTAGE TO LUMENS UPDATE

CURRENT PART NUMBER EXAMPLE	PREVIOUS PART NUMBER EXAMPLE	SOURCE LUMENS ¹	SYSTEM WATTS
SX1405RDLEDGV15L	SX1405RDLEDGV14W	1500	9
SX1405RDLEDGV27L	SX1405RDLEDGV26W	2700	16

SERIES	LUMENS ¹	CCT	DRIVER / DIMMING ²	OPTIONS ³	MOUNTING ⁴	DIFFUSER	FINISH ⁶
SX1104RDLEDGV	15L 1500 Lm	27K 2700K 30K 3000K 35K 3500K 40K 4000K	EX Electronic Driver, 120V/277V DO10X 1% 0-10V Dimming, 120V/277V DS2W1 2 Wire Phase Dimming, 120V	FS Fuse holder and Fuse GS Ceiling Level Gasket TBM Thumb Screw Attachment	HM ⁵ Hang Straight PM ⁵ Rigid Pendant SM Surface Mount WM Wall Mount	OP White Opal Acrylic	MW ⁷ Matte White MB ⁷ Matte Black PT ⁷ Platinum Silver CC Custom Color
SX1405RDLEDGV	15L 1500 Lm 27L 2700 Lm						

EXAMPLE: SX1104RDLEDGV15L35KEXSMOPMW

NOTES:

1 Nominal Source Lumens At 3500K 2 Contact Factory for Additional Options 3 See Product Options Page for Details 4 See Mounting Page for Details on Components and Finishes 5 Specify Length in Inches: See Mounting Page for Available Lengths 6 Reference Color Sheet Located on Product Webpage for Full List of Available Colors 7 Standard Finishes



Spectrum Lighting