

IES INDOOR REPORT**PHOTOMETRIC FILENAME : SGW6LEDOS-30L35KEX-AR6923OSSGSK.IES****DESCRIPTION INFORMATION (From Photometric File)**

IESNA:LM-63-2002
[TEST] 102560753CRT-014
[TESTLAB] Intertek
[ISSUE DATE] 11/11/2016
[UPDATE] 12/15/2016
[LAB-REF LUMCAT] CRT1611041146-004
[MANUFAC] Spectrum Lighting
[LUMCAT] SGW6LEDOS-30L-35K-EX-AR6923OS-SG-SK
[LUMINAIRE] 6" Aperture Recessed WallWasher Downlight
[TRIM] Semi-diffuse anodized cone, regressed Linear Prism Lens
[OTHER] Perpendicular Orientation
[LAMP] N/A (Gen3)
[LAMPCAT] N/A
[OTHER] Total Luminaire Wattage is approximate
[OTHER] CCT Output Multipliers: 40K x 1.0, 30K x 1.0, 27K x 0.946
[OTHER] This report updated by Spectrum Lighting

CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	2051
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	75
Total Luminaire Watts	27.5
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	1.10
Spacing Criterion (90-270)	0.84
Spacing Criterion (Diagonal)	0.86
Basic Luminous Shape	Circular
Luminous Length (0-180)	0.50 ft (Diameter)
Luminous Width (90-270)	0.50 ft (Diameter)
Luminous Height	0.00 ft

IES INDOOR REPORT
PHOTOMETRIC FILENAME : SGW6LEDOS-30L35KEX-AR6923OSSGSK.IES

LUMINANCE DATA (cd/sq.m)

Angle In Degrees	Average 0-Deg	Average 45-Deg	Average 90-Deg
45	63900	33151	13787
55	54933	17598	3371
65	51488	8553	246
75	36841	3343	0
85	19418	0	0

IES INDOOR REPORT
PHOTOMETRIC FILENAME : SGW6LEDOS-30L35KEX-AR6923OSSGSK.IES

CANDELA TABULATION

	<u>0.0</u>	<u>22.5</u>	<u>45.0</u>	<u>67.5</u>	<u>90.0</u>	<u>112.5</u>	<u>135.0</u>	<u>157.5</u>	<u>180.0</u>	<u>202.5</u>
0.0	2154.3	2154.3	2154.3	2154.3	2154.3	2154.3	2154.3	2154.3	2154.3	2154.3
2.5	2188.6	2187.6	2178.6	2163.4	2140.6	2118.6	2097.0	2080.3	2064.4	2080.3
5.0	2200.2	2194.5	2175.4	2141.1	2102.6	2057.3	2001.9	1965.1	1946.5	1965.1
7.5	2186.0	2176.4	2144.6	2095.4	2041.5	1964.3	1887.9	1825.5	1795.1	1825.5
10.0	2150.3	2132.8	2088.3	2030.1	1960.1	1858.6	1751.9	1669.5	1623.2	1669.5
12.5	2106.7	2077.6	2015.1	1943.1	1862.3	1736.8	1602.4	1498.5	1436.3	1498.5
15.0	2035.1	2006.0	1932.3	1840.0	1748.2	1609.0	1442.2	1313.5	1245.1	1313.5
17.5	1948.9	1913.5	1827.5	1720.6	1624.4	1470.8	1280.7	1126.4	1051.1	1126.4
20.0	1864.5	1817.1	1714.6	1596.5	1498.1	1328.6	1114.8	945.7	865.4	945.7
22.5	1779.3	1721.4	1606.7	1473.0	1369.8	1187.2	957.3	774.6	691.7	774.6
25.0	1695.6	1631.0	1496.1	1345.1	1240.1	1050.6	803.0	616.1	539.2	616.1
27.5	1610.7	1533.7	1375.3	1219.3	1106.9	916.7	657.1	476.0	405.6	476.0
30.0	1527.7	1434.0	1249.3	1073.1	945.5	770.3	527.4	356.5	296.7	356.5
32.5	1429.8	1320.5	1114.0	899.4	772.1	616.9	416.4	261.3	213.2	261.3
35.0	1322.2	1189.8	964.5	728.1	612.4	480.3	312.3	189.2	156.1	189.2
37.5	1193.3	1053.0	804.3	579.2	482.5	365.3	223.9	136.6	113.2	136.6
40.0	1063.0	922.8	655.9	461.0	384.1	281.3	158.4	99.2	76.2	99.2
42.5	934.6	807.1	529.2	356.3	266.4	206.6	111.3	67.4	47.2	67.4
45.0	825.0	703.0	428.0	247.6	178.0	134.5	79.7	41.6	28.2	41.6
47.5	736.1	612.5	350.3	169.5	123.2	88.4	55.6	24.1	17.5	24.1
50.0	669.3	542.1	283.0	120.6	86.0	61.0	35.5	14.5	13.0	14.5
52.5	621.1	490.6	227.8	84.4	54.8	39.6	20.8	10.4	9.1	10.4
55.0	575.3	448.2	184.3	56.0	35.3	24.0	10.8	6.8	5.7	6.8
57.5	527.5	405.0	145.8	34.9	18.6	12.4	5.7	3.8	2.8	3.8
60.0	481.0	361.8	111.9	18.4	7.1	5.1	3.1	1.3	0.5	1.3
62.5	440.7	319.4	85.5	11.0	3.6	2.5	0.9	0.0	0.0	0.0
65.0	397.3	275.6	66.0	7.4	1.9	0.7	0.0	0.0	0.0	0.0
67.5	337.7	227.8	48.9	4.6	0.3	0.0	0.0	0.0	0.0	0.0
70.0	286.4	183.1	35.0	2.6	0.0	0.0	0.0	0.0	0.0	0.0
72.5	228.1	140.0	24.3	1.0	0.0	0.0	0.0	0.0	0.0	0.0
75.0	174.1	101.8	15.8	0.0	0.0	0.0	0.0	0.0	0.0	0.0
77.5	128.6	71.7	10.4	0.0	0.0	0.0	0.0	0.0	0.0	0.0
80.0	89.5	48.2	5.5	0.0	0.0	0.0	0.0	0.0	0.0	0.0
82.5	60.6	29.0	2.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0
85.0	30.9	12.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
87.5	7.5	2.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
90.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Vert. Angles **Horizontal Angles**

	<u>225.0</u>	<u>247.5</u>	<u>270.0</u>	<u>292.5</u>	<u>315.0</u>	<u>337.5</u>	<u>360.0</u>
0.0	2154.3	2154.3	2154.3	2154.3	2154.3	2154.3	2154.3
2.5	2097.0	2118.6	2140.6	2163.4	2178.6	2187.6	2188.6
5.0	2001.9	2057.3	2102.6	2141.1	2175.4	2194.5	2200.2
7.5	1887.9	1964.3	2041.5	2095.4	2144.6	2176.4	2186.0
10.0	1751.9	1858.6	1960.1	2030.1	2088.3	2132.8	2150.3
12.5	1602.4	1736.8	1862.3	1943.1	2015.1	2077.6	2106.7
15.0	1442.2	1609.0	1748.2	1840.0	1932.3	2006.0	2035.1
17.5	1280.7	1470.8	1624.4	1720.6	1827.5	1913.5	1948.9
20.0	1114.8	1328.6	1498.1	1596.5	1714.6	1817.1	1864.5
22.5	957.3	1187.2	1369.8	1473.0	1606.7	1721.4	1779.3
25.0	803.0	1050.6	1240.1	1345.1	1496.1	1631.0	1695.6
27.5	657.1	916.7	1106.9	1219.3	1375.3	1533.7	1610.7
30.0	527.4	770.3	945.5	1073.1	1249.3	1434.0	1527.7

IES INDOOR REPORT
PHOTOMETRIC FILENAME : SGW6LEDOS-30L35KEX-AR6923OSSGSK.IES

CANDELA TABULATION - (Cont.)

32.5	416.4	616.9	772.1	899.4	1114.0	1320.5	1429.8
35.0	312.3	480.3	612.4	728.1	964.5	1189.8	1322.2
37.5	223.9	365.3	482.5	579.2	804.3	1053.0	1193.3
40.0	158.4	281.3	384.1	461.0	655.9	922.8	1063.0
42.5	111.3	206.6	266.4	356.3	529.2	807.1	934.6
45.0	79.7	134.5	178.0	247.6	428.0	703.0	825.0
47.5	55.6	88.4	123.2	169.5	350.3	612.5	736.1
50.0	35.5	61.0	86.0	120.6	283.0	542.1	669.3
52.5	20.8	39.6	54.8	84.4	227.8	490.6	621.1
55.0	10.8	24.0	35.3	56.0	184.3	448.2	575.3
57.5	5.7	12.4	18.6	34.9	145.8	405.0	527.5
60.0	3.1	5.1	7.1	18.4	111.9	361.8	481.0
62.5	0.9	2.5	3.6	11.0	85.5	319.4	440.7
65.0	0.0	0.7	1.9	7.4	66.0	275.6	397.3
67.5	0.0	0.0	0.3	4.6	48.9	227.8	337.7
70.0	0.0	0.0	0.0	2.6	35.0	183.1	286.4
72.5	0.0	0.0	0.0	1.0	24.3	140.0	228.1
75.0	0.0	0.0	0.0	0.0	15.8	101.8	174.1
77.5	0.0	0.0	0.0	0.0	10.4	71.7	128.6
80.0	0.0	0.0	0.0	0.0	5.5	48.2	89.5
82.5	0.0	0.0	0.0	0.0	2.2	29.0	60.6
85.0	0.0	0.0	0.0	0.0	0.0	12.6	30.9
87.5	0.0	0.0	0.0	0.0	0.0	2.2	7.5
90.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

IES INDOOR REPORT
PHOTOMETRIC FILENAME : SGW6LEDOS-30L35KEX-AR6923OSSGSK.IES

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	664.10	N.A.	32.40
0-30	1195.86	N.A.	58.30
0-40	1605.00	N.A.	78.30
0-60	1949.34	N.A.	95.10
0-80	2045.66	N.A.	99.80
0-90	2050.57	N.A.	100.00
10-90	1856.5	N.A.	90.50
20-40	940.91	N.A.	45.90
20-50	1165.26	N.A.	56.80
40-70	412.30	N.A.	20.10
60-80	96.31	N.A.	4.70
70-80	28.35	N.A.	1.40
80-90	4.92	N.A.	0.20
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	2050.57	N.A.	100.00

Total Luminaire Efficiency = N.A. %

ZONAL LUMEN SUMMARY

Zone	Lumens
0-10	194.07
10-20	470.03
20-30	531.76
30-40	409.14
40-50	224.35
50-60	119.99
60-70	67.96
70-80	28.35
80-90	4.92
90-100	0.00
100-110	0.00
110-120	0.00
120-130	0.00
130-140	0.00
140-150	0.00
150-160	0.00
160-170	0.00
170-180	0.00


IES INDOOR REPORT
PHOTOMETRIC FILENAME : SGW6LEDOS-30L35KEX-AR6923OSSGSK.IES

COEFFICIENTS OF UTILIZATION - ZONAL CAVITY METHOD

Effective Floor Cavity Reflectance 0.20

RC	80				70				50			30			10			0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	112	109	106	104	110	107	104	102	103	101	99	99	97	96	96	94	93	91
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	85	83
3	99	92	86	82	97	90	85	81	88	83	80	85	81	78	83	80	77	75
4	93	85	78	74	92	84	78	73	81	76	72	79	75	71	77	74	70	69
5	88	79	72	67	86	78	71	67	76	70	66	74	69	65	72	68	65	63
6	83	73	66	61	81	72	66	61	71	65	61	69	64	60	68	63	60	58
7	78	68	61	57	77	67	61	56	66	60	56	65	60	56	64	59	56	54
8	74	64	57	53	73	63	57	52	62	56	52	61	56	52	60	55	52	50
9	70	60	53	49	69	59	53	49	58	53	49	57	52	48	56	52	48	47
10	67	56	50	46	66	56	50	46	55	49	46	54	49	45	53	49	45	44

POLAR GRAPH



Maximum Candela = 2200.2 Located At Horizontal Angle = 0, Vertical Angle = 5
1 - Vertical Plane Through Horizontal Angles (0 - 180) (Through Max. Cd.)
2 - Vertical Plane Through Horizontal Angles (22.5 - 202.5)
3 - Vertical Plane Through Horizontal Angles (45 - 225)
4 - Vertical Plane Through Horizontal Angles (67.5 - 247.5)