



NOTE: WL Listing requires lamp enclosure.  
Max wattages are listed at back of section

**ORDERING DETAILS**

MODEL NO.	A	B	FLUORESCENT Ballast in Canopy	INCANDESCENT	HID* Remote Ballast	GLASS JAR Optional	JAR WIRE GUARD Optional
<input type="checkbox"/> AR0808†	8.0	8.0	1 x 13W-42W	100W	35W - 100W	GJ1	WJ1
<input type="checkbox"/> AR1012†	10.0	12.0	1 x 13W-42W	150W	35W - 150W	GJ1	WJ1
<input type="checkbox"/> AR1214†	12.0	14.0	1 x 13W-57W	200W	35W - 175W	GJ1orGJ2	WJ1orWJ2

† Specify **CF**- Compact Fluorescent; **IN**- Incandescent; **MH** Metal halide  
NOTE: Use of Glass jar limits maximum wattage. consult accessories ordering page.

**ORDER EXAMPLE:**

AR0808/INC/RD/PA23/CP-6: - 8" Angle Reflector (Incandescent) Red with formed pipe mounting, CP6 wall interface Pipe.

**PRODUCT INFORMATION**

- Angled Reflector light is perfect for a variety of sign and surface lighting applications.
- Shade-spun heavy gauge aluminum
- Solid construction
- Various lamp and color options.
- Suitable for use in damp location.
- Manufactured and tested to UL standard No. 1598/ETL Listed.
- Made in U.S.A

**OPTIONS**

- PA** - Pipe Mount (see pipe options). 1/2" Standard O.D., Heavier Fixtures Require Heavier Pipe for Stability.
- CM** - Ceiling Mount (See Canopy Mounting Options).
- GJ1, WJ1** - Jar and Jar Wire Guard Options. (up to 100 W INC/up to 32 W CF)
- GJ2, WJ2** - Jar and Jar Wire Guard Options. (up to 100 W IMH/ up to 42 watts CF)

**SUBMITTAL WORKSHEET**

FIXTURE NO.  
JOB NAME  
FIXTURE TYPE