



Report Card

(For fixtures using the Lutron Hi-lume® A-Series LED Driver)

Manufacturer:*	
Website:*	
Applicable Model Numbers:*	
Date:*	

*REQUIRED FIELDS

Fixture Manufacturer's Description		<input type="checkbox"/> Cove/Strip Light	<input type="checkbox"/> Pucklight
Type of Fixture:*	Choose from list at right ▶	<input type="checkbox"/> Downlight	<input type="checkbox"/> Sconce
Operating Voltage:	120V – 277V	<input type="checkbox"/> Linear LEDs	<input type="checkbox"/> Troffer Fixture
Control Type:	EcoSystem / 3-wire	<input type="checkbox"/> Light Engine	<input type="checkbox"/> Wallwash
Dimming Range:	100% - 1%	<input type="checkbox"/> Pendant	
Input Power (max.):*			

*REQUIRED FIELDS

Driver Manufacturer: Lutron Electronics
Product: Hi-lume A-Series LED Driver



Compatible Lutron Products

Product	Part Number	Fixtures per Dimmer		Measured Light Output Range
		120V	277V	
NovaT	NTF-10	1-59	-	100% - 1%
NovaT	NTF-103P, NTF-10-277	1-29	1-61	100% - 1%
NovaT	NTF-103P-277	-	1-46	100% - 1%
Nova	NF-10	1-59	-	100% - 1%
Nova	NF-103P, NF-10-277	1-29	1-61	100% - 1%
Nova	NF-103P-277	-	1-46	100% - 1%
Vareo	VF-10	1-29	-	100% - 1%
Skylark	SF-10P, SF-103P	1-29	-	100% - 1%
Skylark	SF-12P-277, SF-12P-277-3	-	1-46	100% - 1%
Diva	DVF-103, DVSCF-103P	1-29	-	100% - 1%
Diva	DVF-103P-277, DVSCF-103P-277	-	1-46	100% - 1%
Ariadni	AYF-103P	1-29	-	100% - 1%
Ariadni	AYF-103P-277	-	1-46	100% - 1%
Vierti	VTF-6AM	1-22	-	100% - 1%
Maestro	MAF-6AM, MAF-6AM-277, MSCF-6AM, MCSF-6AM-277	1-22	1-46	100% - 1%
Maestro Wireless	MRF2-F6AN-DV	1-22	1-46	100% - 1%
Spacer System	SPSF-6A, SPSF-6A-277, SPSF-6AM, SPSF-6AM-277	1-22	1-46	100% - 1%
Lyneo Lx	LXF-103PL	1-29	-	100% - 1%
Lyneo Lx	LXF-103PL-277	-	1-46	100% - 1%
RadioRA 2	RRD-F6AN-DV	1-22	1-46	100% - 1%
HomeWorks QS	HQRD-F6AN-DV	1-22	1-46	100% - 1%
Interfaces (1)	PHPM-3F-120, PHPM-3F-DV NGRX-FDBI-16A	1-59	1-123	100% - 1%
		1-59	-	100% - 1%
Energi Savr Node with EcoSystem	CS-1L-WM, CS-2L-WM, CS-1L-CM, CS-2L-CM,	64 per EcoSystem link		100% - 1%
GRAFIK Eye QS with EcoSystem	QSGRJ-16E	64 per EcoSystem link		100% - 1%
Quantum	Quantum	64 per EcoSystem link		100% - 1%
PowPak dimming module with EcoSystem	RMJ-ECO32-DV-B	32 per module		100% - 1%

(1) For use with 3-wire controls or Commercial Systems, RA Systems or Home Systems applications.