

SPECTRUM INDUCTION LIGHTING












QUICK REFERENCE GUIDE

Ordering INDUCTION (DU) Downlights

SERIES	WATTS	KELVIN	GENERATOR	OPTIONS	TRIM
SELECT SERIES	35w 55w 85w 165w 200w	3K (3100K) 4K (4100K) 5K (5000K)	E1-120 E2-277	SELECT OPTIONS	SELECT TRIM
SERIES		3K	E1		

- Ultra-Long Life 100,000 hours rated average life.
- Virtually maintenance free.
- Crisp White Light 80+ CRI.
- No Color Shift.
- High Reliability-Instant Hot and Cold (Re)start
- Operates in Hot and Cold Environments.
- High Lumen Output Up to 12,000 lumens.
- Manufactured and tested to UL standard no 1598.

	SERIES	APERTURE	INDUCTION WATTAGE	KELVIN TEMP	GENERATOR VOLTAGE	REFLECTOR	FINISH
RECESSED & RETROFIT LIGHTING	 SG8DU SGRM8DU (Remodel) 8" Induction Downlight Lensed Downlight	8"	35 55	3K° 4K° 5K°	G1-120V G2-277V	AR8110 AR8120	SG SG/PG
	 SG10DU SGRM8DU (Remodel) 10" Induction Downlight Lensed Downlight	10"	35 55 85	3K° 4K° 5K°	G1-120V G2-277V	AR1010 AR1020	SG SG/PG
	 SG12DU SGRM12DU (Remodel) 12" Induction Downlight Lensed Downlight	12" SQ	35 55 85	3K° 4K° 5K°	G1-120V G2-277V	AR1210 AR1220	
	 SG12SQDU SGRM12SQDU (Remodel) 12" Square Induction Prismatic lens	12" SQ	35 55 85	3K° 4K° 5K°	G1-120V G2-277V		FWPG
	 LM2424DU 2' X 2' Square for Grid ceiling	24" X 24"	55 85 165	3K° 4K° 5K°	G1-120V G2-277V	9Cell Parabolic 16Cell Parabolic	

	SERIES	SIZE	INDUCTION WATTAGE	KELVIN TEMP	GENERATOR VOLTAGE	MOUNTING	FINISH
HIGH BAY	 PRDCHDU Induction High Bay Prismatic Reflector	22" X 10"	55 85 165 250	5K°	G1-120V G2-277V	SM HM PM	GW
	 PRDCHDU Induction High Bay Aluminum Reflector	22" X 10"	55 85 165 250	5K°	G1-120V G2-277V	SM HM PM	GW
	 PA1415DU Single Housing	14" x 15"	35 55	5K°	G1-120V G2-277V	HM PM	GW
	PA1415x2DU Double Housing	14" x 15" each fixture	85				
	PA1415x3DU Triple Housing	14" x 15" each fixture					
	PA1415x4DU Quad Housing	14" x 15" each fixture					
CYLINDERS	 SPC1216DU Induction Cylinder	12" X 16"	35 55 85	3K° 4K° 5K°	G1-120V G2-277V	SM HM PM	GW GB BZ
	SPC1418DU Induction Cylinder	14" X 18"	35 55 85 165	3K° 4K° 5K°	G1-120V G2-277V	SM HM PM	GW GB BZ