



MODEL NO SHOWN: **PREX16442EX/CD36/PR16/RS16**

BEFORE



**REFLECTOR-SHIELD INFORMATION**

- Fits over all prismatic refractor sizes
- Changes up/light component to 15% of total fixture output-softening ceiling illumination.
- Will work with wire guards lenses and other accessories.
- Spun of .063 aluminum for durability and sleek function.
- Contrasting or matching finishes available
- Available when ordering HI- Bay fixtures, or for adding a new look to existing installations.
- Suitable for use in damp location
- Manufactured to UL standards



**ORDERING**

<i>"Lumen max"</i>	DIA.	USE REFLECTOR SHIELD.
SP-PROCT12*	12.0	<b>RS-12</b>
SP-PROCT16*	16.0	<b>RS-16</b>
SP-PROCT22*	22.0	<b>RS-22</b>
SP-PRDCH12*	12.0	<b>RS-12</b>
SP-PRDCH16*	16.0	<b>RS-16</b>
SP-PRDCH22*	22.0	<b>RS-22</b>
SP-PRDCHRM12*	12.0	<b>RS-12</b>
SP-PRDCHRM16*	16.0	<b>RS-16</b>
SP-PRDCHRM22*	22.0	<b>RS-22</b>
SP-PRDDH12*	12.0	<b>RS-12</b>
SP-PRDDH16*	16.0	<b>RS-16</b>
SP-PRDDH22*	22.0	<b>RS-22</b>
SP-PREXT12*	12.0	<b>RS-12</b>
SP-PREXT16*	16.0	<b>RS-16</b>

\* Specify: CF or MH

**SUBMITTAL WORKSHEET**

FIXTURE NO.:

JOB NAME:

FIXTURE TYPE