









MEASURE: Critical dimensions:

- A-** Aperture(with trim removed)
- B/C-** Clearance above Ceiling.
- D-** Ceiling Thickness

STRATEGY: Which remodel type will work best?

- SGRT-(EASY)** Works when existing frame is used.
- SGRM-(MODERATE)** Retrofit without existing frame.
- SGRX-(EASY)** Works with existing hole in drop ceiling.
- SGRE-(EASY)** Fits into existing "can" fixture.
- SGRF-(MODERATE)** Top access condition or odd size aperture

ORDER: Type, Lamping, Aperture, Voltage, Reflector Finish

SERIES		MEASUREMENTS
<p>SGRT-RETROFIT REFLECTOR SERIES</p> <p>WHEN USED: When using existing can or frame.</p> <p>FEATURES: Reflector holds using SPECTRUM RT clips. Integral -line ballast box wiring compartment, whip with power leads and quick connect fitting..</p> <p>ADVANTAGES: Fast installation using existing fixture frame or can. Works well with plaster ceilings.</p>		
<p>SGRM-REMODEL RING SERIES</p> <p>WHEN USED: No existing hole, existing or non existing frame.</p> <p>FEATURES: Round ring remodeler. Removable J-box/ballast, whip, clips to installed ring. Ring fastens to ceiling with adjustable bars which mechanically lock. Stop flanges at bottom. Ring adjusts +/- .5 (1/2") for uneven hole installation.</p> <p>ADVANTAGES: Works in uneven holes and uneven ceilings up to 1 1/2" thick.</p>		
<p>SGRX-RETROFIT ROCKET SERIES</p> <p>WHEN USED: When using existing can frame or hole, clips anchor above ceiling.</p> <p>FEATURES: RX retrofit holds to ceiling using patent pending "rocket" spring clips. Integral in-line ballast box/wiring compartment, whip with power leads and quick connect connector.</p> <p>ADVANTAGES: Fast secure installation using existing frame or hole.</p>		
<p>SGRE-RETROFIT ENCLOSED SERIES</p> <p>WHEN USED: When enclosed un-removable cans are to be re-fitted.</p> <p>FEATURES: Ballast & power-feed integral with reflector. Power from existing medium base socket. Uses RTV or RTH retrofit clips or existing clips. Provided with MBS-(Medium base adaptor) or standard power connection options.</p> <p>ADVANTAGES: Retrofits hard to remove can-style fixtures.</p>		
<p>SGRF-REMODEL FRAME SERIES</p> <p>WHEN USED: No existing hole, no existing frame, oversize hole, Top access.</p> <p>FEATURES: Pan-style flat remodeler. Integral J-box, ballast, whip. Clips to ceiling with adjustable integral "L" brackets. Cutaway allows frame to fit through up to 1" thick ceiling. 4 Holes for support to structure.</p> <p>ADVANTAGES: Strong frame good for weight bearing. Simple design looks like new construction when installed. Works well installed from below or above ceiling.</p>	