



A	B	C	D	E
6.4	.625	4.0	10L-13L: 13.2	9.5
162.6 mm	15.2 mm	101.6 mm	20L: 19.2	241.3 mm

RAZI4XT - TRIMLESS / IC RATED

APPLICATION

Versatile 4" Round aperture recessed LED accent light for Insulated Ceiling installations with flangeless trim and a wide range of lumens and optical controls.

FEATURES

LED module tilts 35°, rotates 360°. Two-stage optical system for smooth light distribution and focus control. Quick change LED module with interchangeable optics for job site adjustment and fixture maintenance. Shallow plenum design. Tool-less driver and j-box access. Posi-lock trim retention torsion springs.

TRIM FINISH

A variety of architectural powdercoat and anodized finishes are available.

Plaster mesh fitter included.

ELECTRONICS

LED system features Xicato LED module with proprietary phosphor technology that provides consistent, stable color with CCT control of +/- 100K over life of the light engine. Base CRI is 83 with 2-step MacAdam Ellipse binning. High CRI is 98 with 1x2-step MacAdam Ellipse binning. Variety of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Housing/frame constructed of #20 ga. galvanized steel to resist corrosion. Flangeless one piece trim spun from 0.063" thick high purity aluminum and finished to specification.

CODE COMPLIANCE

BAA Compliant. IC rated. UL certified to meet US and Canadian standards. Suitable for dry or damp locations. Optional Wet location. Manufactured and tested to UL standards No. 1598/8750.

WATTAGE TO LUMENS UPDATE					
CURRENT PART NUMBER EXAMPLE	PREVIOUS PART NUMBER EXAMPLE	SOURCE LUMENS ¹	DELIVERED LUMENS ²	SYSTEM WATTS	LPW
RAZI4XT10L	RAZI4LEDX115W	1000	733	11.1	66
RAZI4XT13L	RAZI4LEDX120W	1300	988	15.0	66
RAZI4XT20L	RAZI4LEDX133W	2000	1520	23.7	64

SERIES	LUMENS ¹	CCT	OPTICS	DRIVER / DIMMING / VOLTAGE ⁴	OPTIONS ⁵	TRIM	FINISH	TRIM OPTIONS ¹¹			
RAZI4XT	83 CRI		XN ⁸ 10°	E_ Electronic Driver	1 120V	BH27 ⁹ 27" Solid Bars	RA4NXT ³	SG ⁶ Semi-Diffuse	SOX ¹² Micro Prism Solite™ Lens		
	10L 1000 Lm	27K 2700K								ND 27°	DS10_ 10% 0-10V
	13L 1300 Lm	30K 3000K	MD 40°	DO10_ 1% 0-10V		H06 6" - 12" Expandable Bars				MW Matte White	PGX Prismatic Glass Lens
	20L 2000 Lm	35K 3500K	WD 45°	DS2W1 1% ELV/MLV, 120V		CB24 24" C-Channel Bars				MB Matte Black	FGX Frosted Glass Lens
		40K 4000K	XW 50°	DL3E_ 1% Lutron® EcoSystem®, Fade		EMRM Remote Emergency Battery Pack				PT Platinum Silver	
				EL10_ 1%, eldoLED		FS Fusing				OB Oil Rubbed Bronze	SOW Micro Prism Solite™ Lens
				ED01_ 0.1%, eldoLED		EB Black Housing				CH Charcoal	Wet Location
				DALI_ DALI Control		CR Corrosion Resistant				AC Anodic Champagne	GLW Clear Glass Lens
						PR ⁷ Deep Ceiling Extension				AS Anodic Sapphire	Wet Location
						CCEA Chicago Ceiling Plenum Rated				AM Anodic Malachite	PGW Prismatic Glass Lens
					AMB Anti Microbial Finish	SN Sun Gold	Wet Location				
						CO Copper Metallic	FGW Frosted Glass Lens				
						GH Graphite	Wet Location				
						AMB Anti Microbial Finish					
						CC ¹⁰ Custom Color					

EXAMPLE: RAZI4XT10L35KNDE1/H12/RA4NXTSG

NOTES:

1 Nominal Source Lumens at Any CCT 2 Nominal Delivered Lumens 83 CRI at Any CCT with ND-SG, No Lens, Aimed at 0° 3 XN 13L Max at 83 and 98 CRI 4 Contact Factory for Additional Options 5 See Product Options Page for Details 6 Standard Bar Hangers 7 Contact Factory 8 "N" Indicates Flangeless Trim 9 Standard Finish 10 Contact Factory for Special Finishes 11 Contact Factory for Special Lenses/Louvers 12 Standard Lens for MD, WD, XW 13 Standard Lens for XN and ND

PROJECT: _____

QUANTITY: _____ TYPE: _____

