




SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS.
SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.

TRIM OPTIONS


FT - FLUSH TRIM

Finished appearance at ceiling level, allows interior color to be visible. (Lenses on individual heads.)




RT - REGRESSED TRIM

Regression increases reflective surfaces and creates finished look. (Lenses on individual heads.)



NF - NO FLANGE TRIMLESS

Trimless and flangeless recessed trim for plaster installation. (Lenses on individual heads.)




LENSES

- SO34 - SOLITE DIFFUSION
- GL34 - CLEAR
- FG34 - FROSTED
- SK34 - LINEAR
- HL34 - HEX LOUVER
- SN34 - SNOOT
- LN34 - COLOR LENS*
- 3AC - 3 ACCESSORY HOLDER


*See Lens Guide

BAR HANGERS

BH27 - 27" SOLID BARS



CB24 / CB48 - C-CHANNEL BARS



ADDITIONS


FS - FUSING

Slow blow type fuse protects fixture against voltage surges. Factory installed.




PD - PULL DOWN

Rotating assembly allows full rotation and pulls down 2" and allows for 45° tilt.



PR - DEEP CEILING EXTENSION

Fixtures have standard 5/8" plaster neck and are designed to work in up to 1.25" thick ceiling. For deeper / thicker ceilings the PR plaster ring option adds up to 4" deep collar (Specify Depth in Inches). Spectrum will ensure optics and trims fit to specification.



EMERGENCY BATTERY

UL 1310 Certified, Class 2 Compliant. Rated for 10 year service life. Recyclable Ni-Cad battery. Includes single-piece TBTS test switch and charge indicator accessory. Constant power supply for superior lumen maintenance. Rated for 90 minute operation. This product has been tested on our OS, XT and GV LED systems and maintains 5-year warranty. Listed for use in damp locations and in enclosed and gasketed fixtures. May be ordered as remote mount for field installation up to 20' from fixture.

LED SERIES	EMRMLED5W SOURCE LUMENS (90 MIN)	EMRMLED7W* SOURCE LUMENS (90 MIN)	EMRMLED12W SOURCE LUMENS (90 MIN)
OS	500 Lm	700 Lm	1100 Lm
XT	600 Lm	800 Lm	1300 Lm
GV	700 Lm	900 Lm	1600 Lm

*Standard Wattage Shipped

EMRMLED5W

5W Remote Emergency Battery for LED 120v/277v



EMRMLED7W*

7W Remote Emergency Battery for LED 120v/277v



EMRMLED12W

12W Remote Emergency Battery for LED 120v/277v



Dimensions shown are nominal. Spectrum Lighting is continually improving products and reserves the right to make changes that will not alter performance or appearance with or without written notice.

PROJECT:	TYPE:
CAT. NO.:	