



A	B	C	D	S1	S2
4.1 104.1 mm	.625 15.9 mm	13.3 337.8 mm	7.9 200.7 mm	4.0 101.6 mm	5.4 137.2 mm

## SGW4LEDGV - TRIM FLANGE / NON-IC RATED

### APPLICATION

4" Round aperture shallow recessed LED wall wash for general illumination.

### FEATURES

Two-stage optical system with medium depth reflector design delivers smooth glare-free general illumination. Tool-less LED module, driver, and J-Box access. Multi-Bar mounting brackets. BH27 Standard mounting bars included. Posi-lock trim retention springs. Integral 0.625" collar, with Deep Ceiling Extension (PR), consult factory.

### TRIM FINISH

A variety of architectural powdercoat and anodized finishes are available.

Matte White flange is standard.

### ELECTRONICS

GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 85+. Higher CRI, R9 and custom LED configurations are available; consult factory. A variety of electronic 120V/277V and dimming drivers available.

### CONSTRUCTION

Housing/frame constructed of #20 ga. galvanized steel to resist corrosion. Self-flanged one piece trim spun from 0.063" thick high purity aluminum and finished to specification. Passive machined aluminum heatsink.

### CODE COMPLIANCE

BAA Compliant. Non-IC rated. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.

WATTAGE TO LUMENS UPDATE			
CURRENT PART NUMBER EXAMPLE	PREVIOUS PART NUMBER EXAMPLE	SOURCE LUMENS <sup>1</sup>	SYSTEM WATTS
SGW4LEDGV15L	SGW4LEDGV14W	1500	13.3
SGW4LEDGV27L	SGW4LEDGV26W	2700	22.3
SGW4LEDGV37L	SGW4LEDGV37W	3700	29.1
SGW4LEDGV55L	SGW4LEDGV55W	5500	42.6

SERIES	LUMENS <sup>1</sup>	CCT	DRIVER / VOLTAGE <sup>2</sup>	OPTIONS <sup>3</sup>	TRIM	FINISH <sup>6</sup>	TRIM OPTIONS	
SGW4LEDGV	15L 1500 Lm	27K 2700K	E Electronic Driver 1 120V 2 277V	BH27 <sup>7</sup> 27" Solid Bars H12 12" - 24" Expandable Bars H06 6" - 12" Expandable Bars CB24 24" C-Channel Bars EM Integral Emergency Battery FS Fusing EB Black Housing CR Corrosion Resistant PR <sup>5</sup> Deep Ceiling Extension GR Goof Ring AMB Anti Microbial Finish	AR4922GV <sup>7</sup>	SG <sup>8</sup> Semi-Diffuse HZ Haze Full Diffuse MW Matte White MB Matte Black PT Platinum Silver OB Oil Rubbed Bronze CH Charcoal AC Anodic Champagne AS Anodic Sapphire AM Anodic Malachite SN Sun Gold CO Copper Metallic GH Graphite AMB Anti Microbial Finish CC Custom Color	SK <sup>9</sup> Skytex™ Lens GS Gasket	
	27L 2700 Lm	30K 3000K						DS10 10% 0-10V
	37L 3700 Lm	35K 3500K						DO10 1% 0-10V
	55L 5500 Lm	40K 4000K						DS2W1 1% ELV/MLV, 120V
		50K 5000K						DLTE1 1% Lutron® 2-Wire Forward Phase, 120V DL3E 1% Lutron® EcoSystem®, Fade EL10 1%, eldoLED ED01 0.1%, eldoLED DALI DALI Control

**EXAMPLE:** SGW4LEDGV37L30KE1BH27/AR4922GVMWSK

NOTES:  
1 Nominal Source Lumens at 35K 2 Contact Factory for Additional Options 3 See Product Options Page For Details 4 Standard Bar Hangers 5 Contact Factory 6 Contact Factory for Special Finishes  
7 Matte White Flange Standard 8 Standard Finish 9 Standard Lens



PROJECT: \_\_\_\_\_  
TYPE: \_\_\_\_\_



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.