



DECORATIVE

MINI ESPRESSO
DIRECT / INDIRECT
DAMP LOCATION
GV SERIES

PROJECT: _____

QUANTITY: _____ TYPE: _____



ME0713UDGV
 GB - Gloss Black
 PLI - Purple Interior



ME0713UDGV
 PT - Platinum Silver
 MWI - Matte White Interior



ME0713UDGV
 MB - Matte Black
 MWI - Matte White Interior



ME0713UDGV
 MW - Matte White
 TQI - Turquoise Interior

SERIES	LUMENS ¹	CCT	DRIVER / DIMMING ²	OPTIONS ³	MOUNTING ⁵	INTERIOR ⁸	FINISH ⁸
ME0713UDGV	15L 1500 Lm 27L 2700 Lm	27K 2700K 30K 3000K 35K 3500K 40K 4000K	EX Electronic Driver, 120V/277V D010X 1%, 0-10V, 120V/277V	ENL⁴ 0-10V Control Module FS Fusing	RDC5 Small Driver Canopy CD3X₆ 3 Cable Mount with Cord EMCR⁷ 10W Canopy Mounted EM EMRM 7W Remote EM EMEN 7W Remote with Enclosure	MWI⁹ Matte White CCI Custom Color FCI Fixture Color Interior	MW⁹ Matte White MB⁹ Matte Black PT⁹ Platinum Silver CC Custom Color

EXAMPLE: ME0713UDGV27L35EX/RDC5CD3x36MWIMW

NOTES:
 1 Normal Source Lumens at 35K 2 Contact Factory for Additional Options 3 See Product Options Page For Details 4 Not Available with EM Options
 5 See Mounting Page for Details on Components and Finishes 6 Specify Length in Inches: See Mounting Page for Available Lengths 7 EMCR Replaces RDC5
 8 Reference Color Sheet Located on Product Webpage for Full List of Available Colors 9 Standard Finishes






MINI ESPRESSO
DIRECT / INDIRECT
DAMP LOCATION
GV SERIES

DECORATIVE

LUMENS / WATTAGE DATA				
PART NUMBER	SOURCE LUMENS ¹	DELIVERED LUMENS ²	SYSTEM WATTS	LPW
ME0713UDGV15L15L	3000	1896	20	95
ME0713UDGV27L27L	5400	3326	36	92

¹ Nominal Source Lumens at 35K ² Nominal Delivered Lumens at 35K

HOUSING DIMENSIONS



A	B
7.5	13.0
190.5 mm	330.2 mm

APPLICATION

Mini Espresso pendant features a unique hourglass shape for direct/indirect lighting.

FEATURES

SpecLume series fixtures offer contemporary style with functional luminaire performance. Fixtures are designed and manufactured in our factory. Passive integral heat sink. LED module and drivers are replaceable and upgradable. CT temps may be mixed to create daylight upright and warm downlight or other combinations.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. See mounting and color pages for standard finishes. Interior is Matte White unless specified. Custom Color interior finish available.

ELECTRONICS

GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 85+. Higher CRI, R9 and custom LED configurations are available; consult factory. Variety of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Fixtures are spun in our factory from 0.063 high purity aluminum. Passive machined aluminum heatsink for optimal thermal management.

CODE COMPLIANCE

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.

SERIES SIZES

ME0713UDGV



CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

CD3X

3X CORD / CABLE MOUNT



ME0713UDGV SHOWN WITH RDC5CD3X





MINI ESPRESSO
DIRECT / INDIRECT
DAMP LOCATION
 GV SERIES / PHOTOMETRIC DATA

ME0713UDGV 27L 27L 35K EX MWI

CANDLEPOWER CURVE TEST SP-00718_7	INTENSITY CANDELA 0° AZIMUTH	ZONAL LUMENS	SINGLE UNIT: PERFORMANCE INITIAL FOOTCANDLES BASED ON IES BEAM ANGLE	MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT																												
	0.00°		Mounting Height AFF	<table border="1"> <thead> <tr> <th rowspan="2">Ceiling Height</th> <th rowspan="2">Fixture Spacing</th> <th colspan="2">RCR 2</th> <th colspan="2">RCR 4</th> </tr> <tr> <th>FC +</th> <th>W/Sq. Ft.</th> <th>FC +</th> <th>W/Sq. Ft.</th> </tr> </thead> <tbody> <tr> <td>9'</td> <td>6'</td> <td>89</td> <td>1.19</td> <td>45</td> <td>0.76</td> </tr> <tr> <td>12'</td> <td>8'</td> <td>37</td> <td>0.50</td> <td>43</td> <td>0.72</td> </tr> <tr> <td>16'</td> <td>10'</td> <td>25</td> <td>0.33</td> <td>20</td> <td>0.33</td> </tr> </tbody> </table>	Ceiling Height	Fixture Spacing	RCR 2		RCR 4		FC +	W/Sq. Ft.	FC +	W/Sq. Ft.	9'	6'	89	1.19	45	0.76	12'	8'	37	0.50	43	0.72	16'	10'	25	0.33	20	0.33
	Ceiling Height	Fixture Spacing	RCR 2				RCR 4																									
			FC +	W/Sq. Ft.	FC +	W/Sq. Ft.																										
	9'	6'	89	1.19	45	0.76																										
	12'	8'	37	0.50	43	0.72																										
	16'	10'	25	0.33	20	0.33																										
	0.00° 903	0° - 20° 348 10%	6.5'	21 fc	Delivered Illuminance Rating: (DIR)																											
	20.00° 906	20° - 50° 983 30%	7.5'	16 fc																												
	40.00° 400	50° - 80° 369 11%	8.5'	12 fc	1' Suspension Length Square rooms used for multiple units: - RCR 2: Length & Width = Ceiling Ht. - 3.5' x 5.00 - RCR 4: Length & Width = Ceiling Ht. - 3.5' x 2.50 + Average Footcandles at 2.5' Above Floor																											
	60.00° 160	80° - 90° 14 0%	10.0'	9 fc																												
	80.00° 30	0° - 90° 1,714 52%	12.0'	6 fc																												
	90.00° 1	90° - 120° 298 9%	14.0'	5 fc																												
	100.00° 34	120° - 150° 845 25%	16.0'	4 fc																												
110.00° 136	Total 3,326 100%	20.0'	2 fc																													
120.00° 242																																
140.00° 424																																
160.00° 560																																
180.00° 611																																

Delivered Lumens: **3,326**
 Luminaire Watts: **36**
 LER: **92.39**

CP at 0deg (Nadir): **903**
 CRI: **80+**

Lumen Multiplier: **15L x 0.57**
 CCT Multiplier: **27K x 0.97, 30K x 0.98, 40K x 1.03**




MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.
NOTE: THIS IS TYPICAL OF SPEC LUME SPECIFICATION FOR PENDANT MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.




CEILING MOUNTING

RDC5 - SMALL DRIVER CANOPY (STANDARD)
MOUNTS TO 4" OCTO J-BOX




CD3X
3X CORD / CABLE MOUNT
SJ CORD WITH 1/16 SS CABLE

ORDER: **CD3X** (Length)
SPECIFY LENGTH:
CD3×36 - 36"
CD3×72 - 72"
CD3×144 - 144"
CD3XLC(XX)
Custom Length
(Specify in Inches)




EMERGENCY BATTERY OPTIONS

EMCR - LARGE DRIVER CANOPY FOR
TOW EMERGENCY BATTERY
(FOR ROUND CEILING MOUNT TYPES)




REMOTE EMERGENCY BATTERY OPTIONS

EMRM* - 7W REMOTE EMERGENCY BATTERY
(50' MAX)



A	B	C
1.3	12.6	13.0

EMEN* - 7W REMOTE EMERGENCY BATTERY
WITH ENCLOSURE (50' MAX)



A	B	C
2.0	17.0	6.2

*OTHER EM BATTERY SIZES AVAILABLE, CONSULT FACTORY