



WAREHOUSE DOME
DAMP / WET LOCATION
CLASSIC SHAPES

PROJECT: _____
QUANTITY: _____ TYPE: _____



WD1812GV
EG - Evergreen



WD1812GV
OR - Orange



WD1812GV
GW - Gloss White



WD1812GV
TQ - Turquoise

SERIES	LUMENS ¹	CCT	DRIVER / DIMMING ²	ACCESSORIES ³	MOUNTING ⁵	INTERIOR ⁸	FINISH ⁸	WET KIT
WD1611GV WD1812GV WD2015GV	15L 1500 Lm 27L 2700 Lm 37L 3700 Lm 55L 5500 Lm	80 CRI 27K 2700K 30K 3000K 35K 3500K 40K 4000K 90 CRI 27HK 2700K 30HK 3000K 35HK 3500K 40HK 4000K	EX Electronic Driver, 120V/277V DS10X 10%, 0-10V, 120V/277V DO10X 1%, 0-10V, 120V/277V DS2W1 ELV/MLV, 120V	TF2 ⁴ 4" Frosted Dome TG2 4" Dome Wire Guard MF2 4" Frosted Mini MG2 4" Short Wire Guard FJ2 4" Frosted Tall FG2 4" Tall Wire Guard DOORS & LENSES DR (See 2 nd Page for Ordering Details)	WALL MOUNT CP6 Wall Mount Cover SP90 ⁴ Straight Arm PA ⁴ Mounting Arm Style CEILING MOUNT HM ⁷ Hang Straight AT ⁷ Hang Straight All Thread PM ⁷ Rigid Pendant Mount CD ⁷ Cord / Cable Mount CM ⁷ Cord Mount EMCR 10W Large Driver Canopy EM EMRM 7W Remote EM EMEN 7W Remote with Enclosure	MWF ⁹ Matte White CCI Custom Color FCI Fixture Color Interior See Page 5 for Full Range of Color Options (83-90082)	MW ⁹ Matte White MB ⁹ Matte Black PT ⁹ Platinum Silver CC Custom Color See Page 5 for Full Range of Color Options (83-90082)	WLKA Wet Location Kit

EXAMPLE: WD1812GV15L30KEXTF2/HM36MWICH

NOTES:
1 Nominal Source Lumens at 35K 2 Contact Factory for Additional Options 3 Enclosure, Wire Guard Required - Choose One Option 4 Standard Enclosure
5 See Mounting Page for Details on Components and Finishes 6 See Mounting Page for Available Arm Options 7 Specify Length in Inches: See Mounting Page for Available Lengths
8 See Color Page for More Options/Consult Factory for Special Finishes 9 Standard Finishes






WAREHOUSE DOME DAMP / WET LOCATION CLASSIC SHAPES

LUMENS / WATTAGE DATA				
PART NUMBER	SOURCE LUMENS ¹	DELIVERED LUMENS ²	SYSTEM WATTS	LPW
WD1611GV15L	1500	1091	10	109
WD1611GV27L	2700	1906	18	106
WD1611GV37L	3700	2800	26	108
WD1611GV55L	5500	4117	39	106

¹ Nominal Source Lumens at 35K ² Nominal Delivered Lumens at 35K

HOUSING DIMENSIONS



Dimensioned with **WD1812GV**

SERIES	A	B
WD1611GV	16.5	14.0
WD1812GV	17.9	14.6
WD2015GV	20.0	13.7

APPLICATION

The Warehouse Dome is designed for decorative general illumination.

FEATURES

Spectrum Lighting's RLM Classics are inspired by vintage lighting fixtures redesigned with modern LED light sources and materials. The wide range of options for illumination, mounting, enclosures, guards and finishes allows for creative fixture specification and design. LED driver is integral to fixture, special driver canopy is required. LED module and driver are serviceable for future replacement. Available in three sizes.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. Variety of standard and custom finishes are available. Interior is Matte White unless specified. Custom Color interior finish available.

ELECTRONICS

GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 80+. Higher CRI, R9 and custom LED configurations are available; consult factory. Choice of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Fixture shades are spun in our factory from 0.063 high purity aluminum. Wall mount canopies are die-cast aluminum with stainless steel hardware. Wall arms are formed 3/4 NPT aluminum pipe and may be field cut.

CODE COMPLIANCE

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Wet Location Option. Manufactured and tested to UL standards No. 1598/8750.

SERIES SIZES

WD1611GV



WD1812GV



WD2015GV



ENCLOSURES

TF2

4" FROSTED DOME



MF2

4" FROSTED MINI



FJ2

4" FROSTED TALL



TG2

4" FROSTED DOME
WIRE GUARD - FITS TF2



MG2

4" FROSTED MINI
WIRE GUARD - FITS MF2



FG2

4" FROSTED TALL
WIRE GUARD - FITS FJ2



DOORS

DR16C LD16WA - 16" Ø DOOR WITH DOMED MATTE WHITE ACRYLIC

DR18B LD18WA - 18" Ø DOOR WITH DOMED MATTE WHITE ACRYLIC



WD1812GV SHOWN WITH DR18B LD18WA

WALL MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & DIMENSIONS.)

PA_

MOUNTING ARM STYLE



WD1812GV SHOWN WITH PA23

CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

HM / AT / PM

HANG STRAIGHT / ALL THREAD / PENDANT



WD1812GV SHOWN WITH HM

CD

CORD / CABLE MOUNT



WD1812GV SHOWN WITH CD

CM

CORD MOUNT




WD1812GV SHOWN WITH CM



WAREHOUSE DOME
DAMP / WET LOCATION
CLASSIC SHAPES / PHOTOMETRIC DATA

WD1611GV-55L-35K-EX-TF2-MWI

CANDLEPOWER CURVE	INTENSITY	ZONAL LUMENS	SINGLE UNIT: PERFORMANCE INITIAL FOOTCANDLES BASED ON IES BEAM ANGLE	MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT																																																																
 <p>Delivered Lumens: 4,116 Luminaire Watts: 39 LER: 105.54</p>	0.00°	0° - 10°	176	4%	<table><tr><th>Mounting Height AFF</th><th>FC at Center on Floor</th><th>Beam Diameter</th><th>FC at Beam Edge</th></tr><tr><td>6.0 ' *</td><td>51 fc</td><td>15.1 ' *</td><td>19 fc</td></tr><tr><td>8.0 ' *</td><td>29 fc</td><td>20.2 ' *</td><td>11 fc</td></tr><tr><td>10.0 ' *</td><td>18 fc</td><td>25.2 ' *</td><td>7 fc</td></tr><tr><td>12.0 ' *</td><td>13 fc</td><td>30.3 ' *</td><td>5 fc</td></tr><tr><td>14.0 ' *</td><td>9 fc</td><td>35.3 ' *</td><td>3 fc</td></tr><tr><td>16.0 ' *</td><td>7 fc</td><td>40.4 ' *</td><td>3 fc</td></tr><tr><td>20.0 ' *</td><td>5 fc</td><td>50.5 ' *</td><td>2 fc</td></tr><tr><td>24.0 ' *</td><td>3 fc</td><td>60.5 ' *</td><td>1 fc</td></tr></table>	Mounting Height AFF	FC at Center on Floor	Beam Diameter	FC at Beam Edge	6.0 ' *	51 fc	15.1 ' *	19 fc	8.0 ' *	29 fc	20.2 ' *	11 fc	10.0 ' *	18 fc	25.2 ' *	7 fc	12.0 ' *	13 fc	30.3 ' *	5 fc	14.0 ' *	9 fc	35.3 ' *	3 fc	16.0 ' *	7 fc	40.4 ' *	3 fc	20.0 ' *	5 fc	50.5 ' *	2 fc	24.0 ' *	3 fc	60.5 ' *	1 fc	<table><tr><th colspan="2">RCR 2</th><th colspan="2">RCR 4</th></tr><tr><th>FC *</th><th>W/Sq. Ft.</th><th>FC *</th><th>W/Sq. Ft.</th></tr><tr><td>14' *</td><td>12' *</td><td>27</td><td>0.28</td><td>22</td><td>0.28</td></tr><tr><td>18' *</td><td>14' **</td><td>21</td><td>0.21</td><td>11</td><td>0.14</td></tr><tr><td>22' *</td><td>16' ***</td><td>13</td><td>0.13</td><td>15</td><td>0.18</td></tr></table> <p>Delivered Illuminance Rating: (DIR) 99 FC per W/Sq. Ft. 80 FC per W/Sq. Ft.</p> <p>2' Suspension Length Square rooms used for multiple units: - RCR 2: Length & Width = Ceiling Ht. - 4.5' x 5.00 - RCR 4: Length & Width = Ceiling Ht. - 4.5' x 2.50 * Average Footcandles at 2.5' Above Floor * Exceeds spacing criteria by 4% ** Exceeds spacing criteria by -14% *** Exceeds spacing criteria by -24%</p>	RCR 2		RCR 4		FC *	W/Sq. Ft.	FC *	W/Sq. Ft.	14' *	12' *	27	0.28	22	0.28	18' *	14' **	21	0.21	11	0.14	22' *	16' ***	13	0.13	15	0.18
	Mounting Height AFF	FC at Center on Floor	Beam Diameter	FC at Beam Edge																																																																
	6.0 ' *	51 fc	15.1 ' *	19 fc																																																																
	8.0 ' *	29 fc	20.2 ' *	11 fc																																																																
	10.0 ' *	18 fc	25.2 ' *	7 fc																																																																
	12.0 ' *	13 fc	30.3 ' *	5 fc																																																																
	14.0 ' *	9 fc	35.3 ' *	3 fc																																																																
	16.0 ' *	7 fc	40.4 ' *	3 fc																																																																
	20.0 ' *	5 fc	50.5 ' *	2 fc																																																																
	24.0 ' *	3 fc	60.5 ' *	1 fc																																																																
RCR 2		RCR 4																																																																		
FC *	W/Sq. Ft.	FC *	W/Sq. Ft.																																																																	
14' *	12' *	27	0.28	22	0.28																																																															
18' *	14' **	21	0.21	11	0.14																																																															
22' *	16' ***	13	0.13	15	0.18																																																															
0.00° 1,828	0° - 20°	669	16%																																																																	
5.00° 1,827	0° - 30°	1,401	34%																																																																	
10.00° 1,797	0° - 40°	2,269	55%																																																																	
15.00° 1,751	0° - 60°	3,770	92%																																																																	
20.00° 1,681	0° - 80°	4,092	99%																																																																	
30.00° 1,489	0° - 90°	4,116	100%																																																																	
40.00° 1,286	Total	4,116	100%																																																																	
50.00° 1,005																																																																				
60.00° 361																																																																				
70.00° 138																																																																				
80.00° 57																																																																				
90.00° 1																																																																				


MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION. NOTE: THIS IS TYPICAL OF RLM SPECIFICATION FOR MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.




WALL MOUNTING

CP6 - SMALL DRIVER CANOPY (STANDARD)
MAY BE USED AS SPICE BOX FOR DIRECT FEED
NOT AVAILABLE W/ PA16 & PA16F




CUSTOM AND OTHER WALL ARMS AVAILABLE - CONTACT FACTORY. ARMS MAY BE FIELD CUT ON WALL SIDE - FIXTURE SIDE THREADED 3/4" NPT REQUIRES SEALANT FOR WET LOCATION.




CEILING MOUNTING

HM*
HANG STRAIGHT
45° SWIVEL 5/8" OD STEM - 3/8" IP




ORDER: HM (Length)
SPECIFY LENGTH:
HM3 - 3"
HM6 - 6"
HM12 - 12"
HM18 - 18"
HMLC(XX)
Custom Length
(Specify in Inches)

PM*
RIGID PENDANT MOUNT
RIGID 5/8" OD STEM - 3/8" IP




ORDER: PM (Length)
SPECIFY LENGTH:
PM3 - 3"
PM6 - 6"
PM12 - 12"
PM18 - 18"
PMLC(XX)
Custom Length
(Specify in Inches)

AT**
HANG STRAIGHT ALL THREAD
45° SWIVEL 5/8" OD STEM - 1/4" IP



ORDER: AT (Length)
SPECIFY LENGTH:
AT12 - 12"
AT24 - 24"
AT36 - 36"
AT48 - 48"
AT60 - 60"
AT72 - 72"
FIELD CUT THREADED PIPE TO LENGTH W/ FIELD CUT PIPE COVER 3/4" SHORTER THAN THREADED PIPE

CD
CORD / CABLE MOUNT
SJ CORD WITH 1/16 SS CABLE



ORDER: CD (Length)
SPECIFY LENGTH:
CD36 - 36"
CD72 - 72"
CD144 - 144"
CDLC(XX)
Custom Length
(Specify in Inches)

CM
CORD MOUNT
SJ CORD WITH STRAIN RELIEF




ORDER: CM (Length)
SPECIFY LENGTH:
CM36 - 36"
CM72 - 72"
CM144 - 144"
CMLC(XX)
Custom Length
(Specify in Inches)

*MAXIMUM ONE PIECE STEM LENGTH IS 72". **MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS. **ORDER IN 12" INCREMENTS. ODD SIZES MAY BE FIELD CUT


EMERGENCY BATTERY OPTIONS

EMCR - LARGE DRIVER CANOPY FOR 10W EMERGENCY BATTERY
(FOR ROUND CEILING MOUNT TYPES)



REMOTE EMERGENCY BATTERY OPTIONS

EMRM* - 7W REMOTE EMERGENCY BATTERY
(50' MAX)



EMEN* - 7W REMOTE EMERGENCY BATTERY WITH ENCLOSURE
(50' MAX)



*OTHER EM BATTERY SIZES AVAILABLE. CONTACT FACTORY.



COLOR OPTIONS - POWDER COAT PAINT FINISHES

NOTE: NO PRINTED IMAGE CAN EQUAL THE EXACT COLOR OF FINISH ON METAL.
SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.



STANDARD CORD / STEM / CANOPY FINISHES

FIXTURE COLOR	STANDARD CORD COLOR	STANDARD CANOPY / STEM COLOR
Matte White, Textured White	Matte White	Matte White
Gloss White	Matte White	Gloss White
Matte Black, Gloss Black, Textured Black	Matte Black	Matte Black
All Others	Matte Black	Same Color as Fixture
Custom Color	Contact Factory	Contact Factory

PAINT TIMES

TIER	COST	AVERAGE PAINT TIME*
Tier 1 - Standard Finishes	\$	①
Tier 2 - Typical Finishes	\$\$	①①
Tier 3 - Special Metal Finishes	\$\$\$	①①①
Custom Color	Contact Factory	Contact Factory

*CONTACT FACTORY FOR SPECIFIC PRODUCT LEAD TIMES

TIER 1 - STANDARD FINISHES

MW Matte White	GW Gloss White	PT Platinum Silver	MB Matte Black	GB Gloss Black	BZ Bronze

TIER 2 - TYPICAL FINISHES

TW Textured White	TB Textured Black	MT* Textured Silver	OB* Oil Rubbed Bronze	SN Sun Gold	CO Copper Metallic	BR Brecchia	GH Graphite	CH Charcoal	AL Almond	VE Verde Green
BL Blue Streak	RD Red Baron	OR Orange	CM Carnel	PL Purple	PG Pub Green	TQ Turquoise	SF Sea Foam	PK Pink	AY Aero Yellow	EG Evergreen
LG Lime Green	LB Light Blue	BY Burgundy	AK Anodic Black	AM Anodic Malachite	AZ Anodic Bronze	AS Anodic Sapphire	AN Anodic Natural	AC Anodic Champagne		

TIER 3 - SPECIAL METAL FINISHES

NOT AVAILABLE ON ALL FIXTURES. PLEASE CONSULT SPECIFICATION SHEETS OR FACTORY FOR AVAILABILITY.

GA* Galvanized	BA**/** Brushed Aluminum	GF* Gold Flake

CUSTOM COLOR FINISHES

CONTACT FACTORY

CC
Custom Color



*UNAVAILABLE FOR WET LOCATION

** UNAVAILABLE FOR INTERIOR

