

A	B	C
22.5	7.4	8.2
571.5 mm	188.0 mm	208.3 mm

### WJ1LEDTX2

#### APPLICATION

The XI Series LED Vapor Tight series with T-fitting for twin fixture mount.

#### FEATURES

Spectrum Lighting's RLM Classics are reproductions of early American lighting fixtures reimagined with modern LED light sources and materials. The wide range of combinations for lamping, mounting, enclosures, guards and finishes allows for creative fixture specification and design. Frosted lamp enclosure (FJ1) is standard. A variety of colored lamp enclosures are available as well as guards and light shields. LED module and driver are serviceable for future replacement.

#### FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. A wide variety of standard and custom finishes are available. All exposed materials are chromate pretreated to resist corrosion.

#### ELECTRONICS

LED system features Xicato LED module with proprietary phosphor technology that converts high brightness blue LEDs into uniform white light. Designed to provide consistent, stable color with CCT control of +/- 100K over life of the light engine. Base CRI is 80 with 90, 95 CRI and Vivid™ options. Variety of electronic 120v/277v and dimming drivers.

#### CONSTRUCTION

Fixture is constructed of spun and die-cast heavy gauge aluminum.


#### CODE COMPLIANCE

ARRA Compliant. ETL/UL/CSA for damp locations. Optional Wet location.

Manufactured and tested to UL standards No. 1598/8750.

#### REMOTE DRIVER ENCLOSURE (RME)\*

	A	B	C
2 DRIVERS	13.7	3.5	2.1



SERIES	WATTS	CCT	DRIVER	LED ENCLOSURE	GUARDS	MOUNTING	FINISH
WJ1LEDTX2 Wall Mounted	LEDX12X7W 800 Lumens*	27K-2700° K 30K-3000° K 35K-3500° K 40K-4000° K	E1-Electronic, 120v E2-Electronic, 277v	FJ1-Frosted Glass Enclosure 3" Standard	CG1-Cast Wire Guard SS1-Side Lamp Shield BS1-Half Round Bottom Lamp Shield WL-Wet Location	CP6-Wall Mount With Remote Driver CP106-Wall Mount With Driver in J-Box	GW-Gloss White GB-Gloss Black BZ-Bronze OB-Oil Rubbed Bronze PT-Platinum SI-Silver GA-Galvanized CH-Charcoal GH-Graphite AM-Anodic Malachite SN-Sun Gold EG-Evergreen VE-Verde Green BL-Blue Streak RD-Red Baron OR-Orange CO-Copper Metallic Consult Factory for Custom or Metal Finishes
	LEDX12X11W 1400 Lumens*		DS101-Spectrum 0-10v Dimming, 120v to 10%	PJ3-Prismatic Lamp Enclosure 3" AJ1-Amber Lamp Enclosure 3" RDJ1-Red Lamp Enclosure 3" GRJ1-Green Lamp Enclosure 3" BLJ1-Blue Lamp Enclosure 3"			
	LEDX12X15W 2000 Lumens*		DS102-Spectrum 0-10v Dimming, 277v to 10%	WJ1-Wire Guard			
	LEDX12X20W 2600 Lumens*		RMD-Remote Driver Enclosure Requires CP6				
	*Nominal Source Lumens at Any CCT					May be Oriented Horizontally or Vertically on Wall	

#### EXAMPLE: WJ1LEDTX2LEDX11W27KE1/FJ1X2CG/CP106SI

Dimensions shown are nominal. Spectrum Lighting is continually improving products and reserves the right to make changes that will not alter performance or appearance with or without written notice.

PROJECT:	TYPE:
CAT. NO.:	