

## SAFO6PC - TRIM FLANGE / NON IC RATED

### APPLICATIONS

6" square LED adjustable accent light with finished trim flange for Non-IC installations.

### FEATURES

LED module tilts 35°, rotates 360°. Two-stage interchangeable optical and lens systems for smooth light distribution. Zhaga LED module for ease of maintenance and replacement. Shallow plenum design. Tool-less LED module, driver, and J-Box access. Multi-Bar mounting brackets. BH27 Standard aluminum mounting bars included. Posi-lock trim retention torsion springs. Integral .625" collar with deep ceiling option for up to 2" thick ceiling (PR).

### TRIM FINISH

A variety of architectural powdercoat and anodized finishes are available. Matte White flange is standard.

### ELECTRONICS

LED module features high brightness Philips LEDs. 3-step MacAdam Ellipse binning and 80 and 90 CRI available. Variety of electronic 120V/277V and dimming drivers.


### CONSTRUCTION

Housing/frame constructed of #20 ga. galvanized steel to resist corrosion. Self-Flanged one piece trim die cast high purity aluminum and finished to specification.

### CODE COMPLIANCE

BAA Compliant. Non-IC rated. UL listed for damp locations. Optional Wet location. Manufactured and tested to UL standards No. 1598/8750.

WATTAGE TO LUMENS UPDATE			
CURRENT PART NUMBER EXAMPLE	PREVIOUS PART NUMBER EXAMPLE	SOURCE LUMENS <sup>1</sup>	SYSTEM WATTS
SAFO6PC10L	SAFO6OC10L	1100	15.2
SAFO6PC20L	SAFO6OC20L	2100	23.2
SAFO6PC30L	SAFO6OC30L	3000	31.0



LED MODULE TILTS AND LOCKS TO 35° AND ROTATES AND LOCKS 360° WHILE MAINTAINING CENTER BEAM FOCUS

SERIES	LUMENS <sup>1</sup>	CCT	OPTICS	DRIVER / VOLTAGE <sup>2</sup>	OPTIONS <sup>3</sup>	TRIM	FINISH	TRIM OPTIONS <sup>8</sup>
SAFO6PC	84 CRI		ND 20°	E Electronic Driver	1 120V 2 277V BH27 <sup>4</sup> 27" Solid Bars H12 12" - 24" Expandable Bars H06 6" - 12" Expandable Bars CB24 24" C-Channel Bars EM 7W Emergency Battery Test Switch Remote	SA6FPC <sup>5</sup>	MW <sup>6</sup> Matte White MB Matte Black PT Platinum BZ Bronze CH Charcoal AS Anodic Sapphire AM Anodic Malachite SN Sun Gold CO Copper Metallic GH Graphite CC <sup>7</sup> Custom Color	SOX <sup>9</sup> Micro Prism Solite™ Lens GLX <sup>10</sup> Clear Glass Lens PGX Prismatic Glass Lens FGX Frosted Glass Lens SOW Micro Prism Solite™ Lens Wet Location GLW Clear Glass Lens Wet Location PGW Prismatic Glass Lens Wet Location FGW Frosted Glass Lens Wet Location PF <sup>11</sup> Polished Flange AMB Anti Microbial Finish
	10L 1100 Lm	27K 2700K	MD 30°					
	20L 2100 Lm	30K 3000K	WD 40°	DO10_ 1%, 0-10V				
	30L 3100 Lm	35K 3500K	XW 50°					
	90 CRI							
	10L 1000 Lm	27HK 2700K						
	20L 2000 Lm	30HK 3000K						

EXAMPLE: SAFO6PC10L35KNDE1/H12/SA6FPCMW

NOTES:  
 1 Nominal Source Lumens at 30K 2 Contact Factory for Additional Options 3 See Product Options Page for Details 4 Standard Bar Hangers 5 "F" Indicates Self-Flange Trim, Matte White Standard 6 Standard Finish  
 7 Contact Factory for Special Finishes 8 Contact Factory for Special Lenses / Louvers 9 Standard Lens for MD, WD, XW 10 Standard Lens for ND 11 Flange and Reflector Same Finish



PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.