



6" ROUND RETROFIT WALL WASH OS SERIES / 4500 LUMENS MAX



A	B	C
6.0	7.5	7.4
152.4 mm	190.5 mm	188.0 mm

Ceiling Cutout: Ø 6 1/8"

SGRTW6LEDOS - TRIM FLANGE / NON-IC RATED

APPLICATION

Round OS general illumination series LED wall wash for retrofit or remodel applications.

FEATURES

One piece spun housing seals ceiling aperture preventing light leaks. Two-stage optical system for smooth light distribution. Zhaga International Standard LED module for ease of maintenance and replacement. Tool-less LED module, driver, and J-Box access. Posi-lock trim retention torsion springs. Includes set of three retrofit clips to accommodate most installations. Goof ring available for oversized or damaged ceiling installations. Fixture will work in up to 1" thick ceiling¹.

TRIM FINISH

A variety of architectural powdercoat and anodized finishes are available. Matte White flange is standard.

ELECTRONICS

LED module features high brightness white Osram LEDs. 3-step MacAdam Ellipse binning and CRI 84 minimum. Full range of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Housing/frame constructed of .060 aluminum and powdercoat white to resist corrosion. Self-flanged one piece trim spun from 0.063" thick high purity aluminum and finished to specification. Passive machined aluminum heatsink.

CODE COMPLIANCE

BAA Compliant. Non-IC rated. ETL listed for damp locations. Optional Wet location. LM79/LM80/TM21 data available. Manufactured and tested to UL standards No. 1598/8750.

WATTAGE / LUMENS DATA					
CURRENT PART NUMBER EXAMPLE	PREVIOUS PART NUMBER EXAMPLE	SOURCE LUMENS ²	DELIVERED LUMENS ³	SYSTEM WATTS	LPW
SGRTW6LEDOS10L	SGRTW6LEDOS14W	1100	702	11	64
SGRTW6LEDOS15L	N/A	1500	884	13	68
SGRTW6LEDOS20L	SGRTW6LEDOS25W	2000	1492	20	75
SGRTW6LEDOS30L	SGRTW6LEDOS35W	3000	2051	28	73
SGRTW6LEDOS45L	N/A	4500	3035	41	74

SERIES	LUMENS ²	CCT	DRIVER / VOLTAGE ⁴	OPTIONS ⁵	TRIM	FINISH	TRIM OPTIONS	
SGRTW6LEDOS	10L	1100 Lm	27K 2700K	E Electronic Driver	1 120V	AR6923OS	MW ⁶ Matte White	SK ¹¹ Skytex™ Lens
	15L	1500 Lm	30K 3000K	DS10_ 10%, 0-10V	2 277V	MB Matte Black	GS Gasket	GS Gasket
	20L	2000 Lm	35K 3500K	DO10_ 1%, 0-10V		SG Semi-Diffuse	WL Wet Location	WL Wet Location
	30L	3000 Lm	40K 4000K	DS2W1 1%, ELV/MLV, 120V		PT Platinum Silver	PF ¹² Polished Flange	PF ¹² Polished Flange
	45L	4500 Lm		DLTE1 1% Lutron® 2-Wire Forward Phase, 120V		BZ Bronze	EMIT ⁸ Emergency Test Switch in Trim	EMIT ⁸ Emergency Test Switch in Trim
			DL3E_ 1% Lutron® EcoSystem®, Fade		OB Oil Rubbed Bronze	AMB Anti-Microbial Finish	AMB Anti-Microbial Finish	
			EL10_ 1%, eldoLED		CH Charcoal			
			ED01_ 0.1%, eldoLED		AS Anodic Sapphire			
			DALL_ DALI Control		AN Anodic Natural			
					AC Anodic Champagne			
					AM Anodic Malachite			
					CO Copper Metallic			
					GH Graphite			
					CC ¹⁰ Custom Color			

EXAMPLE: SGRTW6LEDOS20L35KE1/AR6923OSMWSK

NOTES:
 1 Consult Factory for Thicker Ceiling 2 Nominal Source Lumens at 35K 3 Nominal Delivered Lumens at 35K with AR6923OSSGSK 4 Contact Factory for Additional Options 5 See Product Options Page for Details 6 Order DS10/2 When Specifying ZIG or BLU 7 Standard EM 8 EMIT Suffix Required on Trim and Housing 9 Standard Finish 10 Contact Factory for Special Colors 11 Standard Lens 12 Flange and Reflector Same Finish



PROJECT: _____
 TYPE: _____



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.