



SARH 3" TRACKLIGHT

THEATRICAL PRO SERIES / 2000 LUMENS



SARHXT

APPLICATION

Theatrical Pro SARH Series Tracklight for accent display lighting and decorative lighting application.

FEATURES

Side mounted driver accepts all Spectrac dimming and control options. Hinged front door for easy accessories or optics change. Rotates 359° with locking option on TEK series adaptors. Tilts and locks with high friction Teflon bushings. Accepts up to three accessories at once. Passive cooled Zhaga compliant LED module for future maintenance or upgrade. Quick twist LED optics for field adjustment. Track series available with a variety of surface, pendant and cord/clamp mounting.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. A wide variety of standard and custom finishes are available. All exposed materials are chromate pretreated to resist corrosion.

CONSTRUCTION


Spun, fabricated and extruded aluminum construction.

ELECTRONICS

LED system features Xicato LED module with proprietary phosphor technology that provides consistent, stable color with CCT control of +/- 100K over life of the module. Base CRI is 83 with 2 MacAdam Ellipse binning. High CRI is 98 with 1 MacAdam Ellipse binning. Variety of electronic 120V/277V and dimming drivers.

CODE COMPLIANCE

BAA Compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL Standards No. 1598/8750.



A	B
9.0 228.6 mm	5.3 134.6 mm

WATTAGE / LUMENS DATA

PART NUMBER	PREVIOUS PART NUMBER EXAMPLE	SOURCE LUMENS ¹	DELIVERED LUMENS ²	SYSTEM WATTS	LPW
SARHXT10L	SAR20LEDXT10L	1000	752	9.1	83
SARHXT13L	SAR20LEDXT13L	1300	1013	13.0	78
SARHXT20L	SAR20LEDXT20L	2000	1559	21.7	72

SERIES	LUMENS ¹	CCT	BEAM	DRIVER / VOLTAGE ⁴	ADAPTOR / MOUNTING	FINISH ⁹	ACCESSORIES ¹¹	
SARHXT	10L	1000 Lm	83 CRI	XN ³ 10°	1 120V 2 277V TEK100 Global TEK 2 CIR/2 NEUT 120V HTEK100 Global TEK 2 CIR/2 NEUT 277V GES66 Global GES 1 CIR/1 NEUT 120V TP3⁷ Global XTSC 3 CIR/1 NEUT 120V, 0-10V Dimmable PC1 Pipe Clamp CP6 6" Straight Cord & Plug CP24 24" Straight Cord & Plug CCP6 6" Coil Cord & Plug CP5 5" Round Surface Mount Canopy (120V/277V) MPT3⁸ Monopoint Canopy	MW¹⁰ Matte White MB¹⁰ Matte Black PT¹⁰ Platinum Silver CC Custom Color See Page 3 for Full Range of Color Options (83-90102)	LN20¹² Lens SN20 Snoot BD20 Barn Doors HL20 Hex Louver NSP No Barn Door Springs	
	13L	1300 Lm	27K 2700K	ND 26°				DS10⁶ 10% 0-10V Dimming
	20L	2000 Lm	30K 3000K	MD 48°				DO10⁶ 1% 0-10V Dimming
			35K 3500K	WD 60°				ED01⁶ .1% 0-10V Dimming
			40K 4000K					DS2W1 ELV MLV 1% Phase Dimming, 120V Only
			98 CRI					DLTE1 Lutron® 2-Wire Forward Phase (MLV), 120V
			27HK 2700K					DL3E⁶ 1%, Lutron® EcoSystem®, Fades to Black, 120V/277V
			30HK 3000K					DALI⁶ DALI Control Dimming
			35HK 3500K					
			40HK 4000K					

EXAMPLE: SARHXT20L35KMDE1/TEK100/MB/LN20/SN20

NOTES:
 1 Nominal Source Lumens at Any CCT 2 Nominal Delivered Lumens at 83 CRI at Any CCT With ND, No Lens 3 9mm, 13L Max, All XN Draw More Watts Than Other Optics; See Photometry 4 Contact Factory for Additional Options
 5 277V Requires HTEK 277V Track and Adaptor 6 Requires TP3 Adaptor and XTSC PULSE Track System, 120V Only 7 120V 0-10V Only 8 120V Only / GES66 Adaptor 9 See Color Page for More Options/Consult Factory for Special Finishes
 10 Standard Finishes 11 Accessory Finish Will Match Fixture 12 See Lens Page for Options



PROJECT: _____
 TYPE: _____



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.



SARH 3" TRACKLIGHT

THEATRICAL PRO SERIES / FIXTURE OPTIONS

STANDARD FINISHES

Black adaptor standard for all finishes excluding MW which comes with white adaptor.

MW - MATTE WHITE



MB - MATTE BLACK



PT - PLATINUM




FIXTURE DIMENSIONS

NO BARN DOORS (STANDARD)




SIDE VIEW




A	B	C
6.2	2.2	4.8
157.5 mm	55.9 mm	121.9 mm

0° POSITION




A	B
9.9	5.3
251.5 mm	134.6 mm

45° TILT



A	B
9.0	5.3
228.6 mm	134.6 mm

90° TILT




A	B
9.5	4.8
241.3 mm	121.9 mm

BARN DOORS




SIDE VIEW




A	B	C
6.2	4.7	5.7
157.5 mm	119.4 mm	144.8 mm

0° POSITION




A	B
10.9	5.7
276.9 mm	144.8 mm

45° TILT



A	B
11.5	7.8
292.1 mm	198.1 mm

90° TILT



A	B
8.8	7.2
223.5 mm	182.9 mm

COLOR OPTIONS - POWDER COAT PAINT FINISHES

NOTE: NO PRINTED IMAGE CAN EQUAL THE EXACT COLOR OF FINISH ON METAL.
SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.



STANDARD CORD / STEM / CANOPY FINISHES / TRACK ADAPTER


FIXTURE COLOR	STANDARD CORD COLOR / TRACK ADAPTER	STANDARD CANOPY / STEM COLOR
Matte White	Matte White	Matte White
Matte Black	Matte Black	Matte Black
All Others	Matte Black	Same Color as Fixture
Custom Color	Contact Factory	Contact Factory

PAINT TIMES

TIER	COST	AVERAGE PAINT TIME*
Tier 1 - Standard Finishes	\$	🕒
Custom Color	Contact Factory	Contact Factory

*CONTACT FACTORY FOR SPECIFIC PRODUCT LEAD TIMES

TIER 1 - STANDARD FINISHES



CUSTOM COLOR FINISHES

CONTACT FACTORY

CC
Custom Color

