





6" ROUND ADJUSTABLE ACCENT BX SERIES / 8000 LUMENS MAX



A	B	S1	S2
11.2	10.1	5.7	7.6
284.5 mm	256.5 mm	144.8 mm	193.0 mm

Ceiling Cutout: Ø 6.2"

SGRTA6BX - TRIM FLANGE / NON-IC RATED

APPLICATION

6" round open aperture deep regressed Retrofits high output LED adjustable accent for high ceiling illumination in malls, churches and commercial applications.

FEATURES

LED module tilts 35°, rotates 360°. Two-stage optical system for smooth light distribution and focus control. Quick change LED module with interchangeable optics for job site adjustment and fixture maintenance. Tool-less driver and j-box access. Posi-lock trim retention torsion springs.

TRIM FINISH

A variety of architectural powdercoat and anodized finishes are available.

ELECTRONICS

LED module features high brightness white Bridgelux® LEDs. 3-step MacAdam Ellipse binning and CRI 80 or 90. 2-step MacAdam Ellipse binning available, consult factory. 1% 0-10V dimming offered standard.


CONSTRUCTION

Housing constructed of #20 ga. galvanized steel to resist corrosion. Self-flanged one piece trim spun from 0.063" thick high purity aluminum and finished to specification.

CODE COMPLIANCE

BAA Compliant. Non-IC rated. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Complies with CUL. Manufactured and tested to UL standards No. 1598/8750.

LUMENS / WATTAGE DATA (AIMED 20°)		
PART NUMBER	SOURCE LUMENS ¹	SYSTEM WATTS
SGRTA6BX60L	6000	40
SGRTA6BX70L	7000	49
SGRTA6BX80L	8000	58



WHILE MAINTAINING CENTER BEAM, LED MODULE TILTS 35° AND ROTATES 360°

SERIES	LUMENS ¹	CCT	OPTICS	DRIVER / VOLTAGE ²	OPTIONS ⁵	TRIM	FINISH	FLANGE FINISH		
SGRTA6BX	60L	6000 Lm	80 CRI	DO10_ 1%, 0-10V DS2W1 1%, ELV/MLV, 120V DLTE1³ 1% Lutron® 2-Wire Forward Phase, 120V DL3E_3 1% Lutron® EcoSystem®, Fade EL10_ 1%, eldoLED ED01_ 0.1%, eldoLED DALI_ DALI Control DMXS^{3/4} DMX Standard Configuration DMXC^{3/4} DMX Non-Standard Custom BLU Bluetooth LE	1 120V 2 277V 3⁴ 347V	FS Fusing GR Goof Ring EM Integral Emergency Battery	RA6FBX	SG² Semi-Diffuse MW Matte White MB Matte Black PT Platinum Silver CH Charcoal AC Anodic Champagne AS Anodic Sapphire AM Anodic Malachite SN Sun Gold CO Copper Metallic GH Graphite CC⁷ Custom Color	WF White Flange MF⁸ Matching Flange	
	70L	7000 Lm	27K 2700K							
	80L	8000 Lm	30K 3000K							MD 40°
			35K 3500K							WD 55°
			40K 4000K							XW 66°
			90 CRI							
			27HK 2700K							
			30HK 3000K							
			35HK 3500K							
			40HK 4000K							

EXAMPLE: SGRTA6BX60L30KMDDO101/RA6FBXSGMF

NOTES:

1 Nominal Source Lumens 2 Contact Factory for Additional Options 3 60L Max 4 Contact Factory 5 See Product Options Page for Details 6 Standard Finish 7 Contact Factory for Special Finishes 8 Flange Same Color as Inside of Trim



PROJECT: _____
TYPE: _____



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.