




4" SQUARE DOWNLIGHT / NON-IC

ILLUMITECH DECORATIVE / 4000 LUMENS



A	B	C	D	TRIM	S1	S2	S3
10L-20L: 5.1 30L-40L: 6.0	0.625 15.2 mm	13.2 335.3 mm	9.5 241.3 mm	1TFGSQ 1TCGSQ 1TFGSQOC 1TCGSQOC	3.9 99.1 mm	5.5 139.7 mm	1.0 25.4 mm

SDFO4XT - DECORATIVE TRIM / NON-IC RATED

APPLICATION

Illumitech decorative recessed series offers four suspended glass elements. These create visual focus and ceiling brightness while functioning as a performance downlight.

FEATURES

Decorative glass tier suspended by four machined chrome standoffs. Glass is tempered and finished to a jewel like polish. Two-stage optical system for smooth light distribution and focus control. Quick change LED module with interchangeable optics for job site adjustment and fixture maintenance. Posi-lock trim retention torsion springs.

TRIM FINISH

A variety of architectural powdercoat and anodized finishes are available. Matte White flange is standard.

ELECTRONICS

LED system features Xicato LED module with proprietary phosphor technology that provides consistent, stable color with CCT control of +/- 100K over life of the light engine. Base CRI is 83 with 2-step MacAdam Ellipse binning. High CRI is 98 with 1x2-step MacAdam Ellipse binning. Variety of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Self-Flanged one piece trim formed from high purity aluminum and finished to specification. Glass is .125 thick tempered edge polished and finished to specification.

CODE COMPLIANCE

BAA Compliant. Non-IC rated. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Optional Wet location. Manufactured and tested to UL standards No. 1598/8750.

WATTAGE TO LUMENS UPDATE			
CURRENT PART NUMBER EXAMPLE	PREVIOUS PART NUMBER EXAMPLE	SOURCE LUMENS ¹	SYSTEM WATTS
SDFO4XT10L	SGE4SQLEDX15W	1000	11.1
SDFO4XT13L	SGE4SQLEDX120W	1300	15.0
SDFO4XT20L	SGE4SQLEDX133W	2000	23.7
SDFO4XT30L	SGE4SQLEDX152W	3000	34.6
SDFO4XT40L	N/A	4000	39.9

SERIES	LUMENS ¹	CCT	OPTICS	DRIVER / VOLTAGE ³	OPTIONS ⁴	TRIM	FINISH	TRIM OPTIONS		
SDFO4XT	83 CRI		XN ² 10° ND 27° MD 40° WD 45° XW 50°	E Electronic Driver	1 120V 2 277V	BH27 ⁵ 27" Solid Bars	SD4FXT ⁷ MW ⁸ Matte White MB Matte Black SC ⁹ Semi-Diffuse HZ ⁹ Haze Full Diffuse PT Platinum Silver BZ Bronze CH Charcoal AS Anodic Sapphire AM Anodic Malachite SN Sun Gold CO Copper Metallic Graphite AMB Anti Microbial Finish CC ¹⁰ Custom Color	SO Micro Prism Solite™ Lens GS Gasket WL Wet Location		
	10L	1000 Lm		27K		2700K			DS10 10% 0-10V	BH6 12" - 24" Expandable Bars
	13L	1300 Lm		30K		3000K			DO10 1% 0-10V	BH12 6" - 12" Expandable Bars
	20L	2000 Lm		35K		3500K			DS2W1 1% ELV/MLV, 120V	CB24 24" C-Channel Bars
	30L	3000 Lm		40K		4000K			DLTE1 1% Lutron® 2-Wire Forward Phase, 120V	FS Fusing
	40L	4000 Lm		40K		4000K			DL3E 1% Lutron® EcoSystem®, Fade	EM Emergency Battery Pack
	98 CRI				EL10 1% eldoLED	CR Corrosion Resistant	DECORATIVE TRIM			
	10L	1000 Lm	27HK	2700K	ED01 0.1% eldoLED	PR ⁶ Deep Ceiling Extension	1TFGSQ Square Tier Frosted Glass			
	13L	1300 Lm	30HK	3000K	DALI_ DALI Control	TBC T-bar Clips (for BH27)	1TCGSQ Square Tier Clear Glass			
	20L	2000 Lm	35HK	3500K		GR Goof Ring	1TFGSQOC Square Open Center Tier Frosted Glass			
	30L	3000 Lm	40HK	4000K		ENL Enlighten Control Interface	1TCGSQOC Square Open Center Tier Clear Glass			
						EB Black Housing				

EXAMPLE: SDFO4XT20L30KE1/BH27/SD4FXTMWSO1TFGSQOC

NOTES:
 1 Nominal Source Lumens at Any CCT 2 XN 13L Max at 83 and 98 CRI 3 Contact Factory for Additional Options 4 See Product Options Page for Details 5 Standard Bar Hangers 6 Contact Factory 7 "F" Indicates Self-Flange Trim, Matte White Standard 8 Standard Finish 9 Anodized Reflector with Matte White Flange 10 Contact Factory for Special Finishes



PROJECT: _____
 TYPE: _____



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.