





203 2 mm

101.6 mm

PINHOLE TRIM

165 1 mm

0.6

15.8 mm



PAR20 SERIES / 50 WATT MAX INC

4" ROUND DOWNLIGHT



SGD4INC

APPLICATION

4" Round PAR20 downlight for Incandescent lamps.

Efficient reflector design with a variety of lens options. Integral 5/8" (0.625) plaster ring. Maximum wattage label (MWL) for low wattage Incandescent or LED lamps. Multi-bar adjustable mounting brackets.

Variety of powdercoat and anodized finishes available on trim. Eco Black (EB) finish available on frame/ housing.

ELECTRONICS

120 Volt is standard. Use option T277 for 277V supply feed.

CONSTRUCTION

Frame constructed of 20 ga. aluminum. Trim spun from .063 high purity aluminum and finished to specification.

LABELS

ETL Listed for Damp Locations. Wet location available. Manufactured and tested to

SERIES	OPTIONS ¹		TRIM/FINISH ⁵		TRIM OPTIONS ⁷		FIXTURE LAMPING ⁹	
SGD4INC	BH27 ²	27" Bar Hangers	AR4550-SG6	Semi-Diffuse Low Iridescent	GL	Clear Glass Lens	LAMP	MAX WATT
	CB24	C-Channel Bars	CL	Clear Bright Alzak	GS	Gasket	PAR20 ¹⁰	50w
	CCEA	Chicago Ceiling Plenum	GO	Gold Alzak	SO	Micro Prism Solite™ Lens		SUW
	CR	Corrosion Resistant	HZ	Matte Low Iridescent	PG	Prismatic (T73) Lens		
	T277	Step Down Transformer	PW	Pewter Alzak	PH ⁸	Pin Hole Trim		
		277v to 120v	UM	Umber Alzak	LN	See Recessed Fixtures/Lens		
	FS	Fuse Holder and Fuse	WE	Wheat Alzak		Options for Lens, Louver		
	PR ³	Plaster Ring	BK	Black Finish		and Filter Accessories		
	MWL ⁴	Max Wattage Label	WH	White Finish	WL	Wet Location		
	EB	Eco Black Housing Finish	PF	Polished Flange				
	TBC	T-Bar Clips	BB	Black Micro Baffle				
	TR	Top Relamping Option	WB	White Micro Baffle				

EXAMPLE: SGD4INC/AR4550 SG

NOTES:
1 For Available Louvers and Lenses Consult Factory 2 BH27 Bar Hangers Standard 3 Special Depth 4 Specify Wattage 5 White Flange is Standard 6 Semi-Diffuse Low Iredescent Standard 7 Specify PH/MB for Matte Black 8 Matte White Standard 9 For Available Decorative Architectural Trims, Consult Factory 10 Medium Base



PROJECT:



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may after the performance or appearance of products.

80

203.2 mm

330.2 mm