



14" SQUARE LED AREA LIGHT

OA SERIES / 4400 LUMENS MAX LED



FITS SIZES	A	B	C	D
14.0 - 14.5	16.125 Sq 409.575 mm	14.0 Sq 341.732 mm	5.0 127.0 mm	2.125 53.98 mm

RT14SQLEDOA & NC14SQLEDOA

APPLICATION

14" Square aperture area light for retrofit or new construction.

FEATURES

Order as retrofit or new construction. Retrofit designed to fit most recessed square soffit lights (14.125"-15.875"). Shallow Plenum housing design. All LED modules and drivers are replaceable and up-gradeable. Removable J-Box/Driver housing. Multiple mounting points. Passive thermal management. New Construction version has 27" flat mounting bars (BH27).

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. A wide variety of standard and custom finishes are available. All exposed materials are chromate pretreated to resist corrosion.

ELECTRONICS

LED module features high brightness Osram LED system (LED board + driver). 3-step MacAdam Ellipse binning and CRI 80 minimum. Variety of electronic 120V/277V and dimming drivers. Osram LED system designed to exceed L70 standards.

CONSTRUCTION

Housing constructed of .050 5052-H32 aluminum and powdercoated glass white to resistant corrosion. Trim fabricated from aluminum extrusion and finished to specification. Standard lens is matte white optical acrylic and 90% transmissive.

CODE COMPLIANCE

BAA Compliant. Non-IC rated. ETL listed for damp locations. Optional Wet location. Manufactured and tested to UL standards No. 1598/8750.

WATTAGE TO LUMENS UPDATE					
CURRENT PART NUMBER EXAMPLE	PREVIOUS PART NUMBER EXAMPLE	SOURCE LUMENS ¹	DELIVERED LUMENS ²	SYSTEM WATTS	LPW
RT14SQLEDOA11L	RT14SQLEDOA11W	1100	977	11W	89
RT14SQLEDOA22L	RT14SQLEDOA22W	2200	1917	22W	91
RT14SQLEDOA33L	RT14SQLEDOA33W	3300	2864	33W	95
RT14SQLEDOA44L	RT14SQLEDOA44W	4400	3810	44W	95

SERIES	LUMENS ¹	CCT	DRIVER / VOLTAGE ³	OPTIONS ⁴	TRIM	FINISH	OPTIONS				
RT14SQLEDOA 14" Square Retrofit Construction	11L	1100 Lm	40K 4000K	E_ Electronic Driver DS10_ 10% 0-10V Dimming	1 120V 2 277V	BH27 ⁵ 27" Mounting Bars CB24 ⁵ C-Channel Bars FS Fusing WL Wet Location EM Integral Emergency Battery EMRM Remote Emergency Battery Pack CR Corrosion Resistant	FT0114 Flush Extruded Aluminum Door	FINISH		LENS	
	22L	2200 Lm						MW ⁶ Matte White	FO ⁷ Matte White Acrylic		
	33L	3300 Lm						GW Gloss White	SO Solite Lens		
NC14SQLEDOA 14" Square New Construction	44L	4400 Lm				GB Gloss Black	WL Wet Location				
						BZ Bronze PT Platinum CC Custom Color					

EXAMPLE: RT14SQLEDOA33L40KE1/FT0114MWF090

NOTES:
1 Nominal Source Lumens 2 Nominal Delivered Lumens 3 Contact Factory for Additional Options 4 See Product Options Page for Details 5 New Construction Only 6 Standard Finish 7 Standard Lens



PROJECT: _____
TYPE: _____



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.