

**SR14SQLEDOA**

**APPLICATION**

14" square recessed LED downlight LED features soffit/area light for optimal performance.

**FEATURES**

Efficient, powerful LED light source, designed to exceed 50,000 hours of life (L70). Multi-Bar mounting brackets. All LED modules and drivers are replaceable and up-gradeable. New and Retrofit/Remodeler options. Wet location use screws fasteners. (4)

**FINISH**

A variety of architectural powdercoat and anodized finishes are available. Matte White flange is standard.

**ELECTRONICS**

LED module features high brightness white Nichia LEDs. 3-step MacAdam Ellipse binning and CRI 84 minimum. Variety of electronic 120V/277V and dimming drivers.



**CONSTRUCTION**

Housing constructed of .050 5052-H32 aluminum. Trim fabricated from aluminum extrusion and finished to specification.

**CODE COMPLIANCE**

BAA Compliant. Non-IC rated. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Optional Wet location. Manufactured and tested to UL standards No. 1598/8750.

WATTAGE TO LUMENS UPDATE			
CURRENT PART NUMBER EXAMPLE	PREVIOUS PART NUMBER EXAMPLE	SOURCE LUMENS <sup>1</sup>	SYSTEM WATTS
SR14SQLEDOA11L	SR14SQLEDOA11W	1100	14W
SR14SQLEDOA22L	SR14SQLEDOA18W	2200	26W
SR14SQLEDOA33L	SR14SQLEDOA25W	3300	37W
SR14SQLEDOA44L	SR14SQLEDOA34W	4400	47W



SERIES	LUMENS <sup>1</sup>	CCT	DRIVER / VOLTAGE <sup>2</sup>	OPTIONS <sup>3</sup>	TRIM	FINISH <sup>5</sup>	OPTIONS
SR14SQLEDOA	11L 1100 Lm	30K 3000K	E Electronic Driver DS10 10%, 0-10V	1 120V 2 277V	BH27 <sup>4</sup> 27" Solid Bars H12 12" - 24" Expandable Bars CB24 24" C-Channel Bars FS Fusing EM Integral Emergency Battery CR Corrosion Resistant RM Remodeler Housing	MW <sup>6</sup> Matte White GW Gloss White MB Matte Black GB Gloss Black BZ Bronze PT Platinum CC Custom Color	FO <sup>7</sup> Matte White Acrylic Lens 90% Efficient SO Solite Lens WL <sup>8</sup> Wet Location
	22L 2200 Lm	35K 3500K					
	33L 3300 Lm	40K 4000K					
	44L 4400 Lm	50K 5000K					

**EXAMPLE:** SR14SQLEDOA44L35KE1BH27/FT1414GW/FO

NOTES:  
1 Nominal Source Lumens 2 Contact Factory for Additional Options 3 See Product Options Page for Details 4 Standard Bar Hangers 5 Standard Finish 6 Contact Factory for Special Finishes  
7 Standard Lens 8 Trim Secured with 4 Screws



PROJECT: \_\_\_\_\_  
TYPE: \_\_\_\_\_



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.