



CAPPUCCINO
DAMP LOCATION
 CAFÉS

PROJECT: _____

QUANTITY: _____ TYPE: _____



BU40GV
 AC - Anodic Champagne
 MWI - Matte White Interior



BU40GV
 GW - Gloss White
 MBI - Matte Black Interior



BU40GV
 CO - Copper Metallic
 ASI - Anodic Sapphire Interior



BU40GV
 BR - Brecchia
 MBI - Matte Black Interior

SERIES	LUMENS ¹	CCT	DRIVER / DIMMING ²	ACCESSORIES	MOUNTING ⁴	INTERIOR ⁹	FINISH ⁸		
BU40GV	15L 1500 Lm	27K 30K 35K 40K	2700K 3000K 3500K 4000K	EX DS2W1 DO10X	Electronic Driver, 120V/277V ELV/MLV, 120V 1%, 0-10V, 120V/277V	FJO ³ 2" Frosted Tall MFO 2" Frosted Mini	WALL MOUNT CP104 ⁵ Small Driver Canopy CP6/RMD Remote Mount Driver PA ⁶ Mounting Arm Style SP90 ⁶ Straight Arm	MWI ⁹ Matte White CCI Custom Color FCI Fixture Color Interior	MW ⁹ Matte White MB ⁹ Matte Black PT ⁹ Platinum Silver CC Custom Color
							CEILING MOUNT RDC5 Small Driver Canopy HM ⁷ Hang Straight AT ⁷ Hang Straight All Thread PM ⁷ Rigid Pendant Mount CD ⁷ Cord / Cable Mount CM ⁷ Cord Mount		

EXAMPLE: BU40GV15L35KEXFJO/RDC5PM24MWIMW

NOTES:
 1 Nominal Source Lumens at 35K 2 Contact Factory for Additional Options 3 Standard Enclosure 4 See Mounting Page for Details on Components and Finishes
 5 Contact Factory for Knock Out Holes 6 See Mounting Page for Available Arm Options 7 Specify Length in Inches: See Mounting Page for Available Lengths
 8 See Color Page for More Options/Consult Factory for Special Finishes 9 Standard Finishes






CAPPUCCINO
DAMP LOCATION
CAFÉS

DECORATIVE

LUMENS / WATTAGE DATA				
PART NUMBER	SOURCE LUMENS ¹	DELIVERED LUMENS ²	SYSTEM WATTS	LPW
BU40GV15L	1500	744	11	68

¹ Nominal Source Lumens at 35K ² Nominal Delivered Lumens at 35K

HOUSING DIMENSIONS



A	B
6.4	8.7
162.6 mm	221.0 mm

APPLICATION

The Cafés offer a playful variety of fixture shapes. GV products are designed for damp or dry locations.

FEATURES

SpecLume series fixtures offer contemporary style with functional luminaire performance. Passive integral heat sink. LED module and drivers are replaceable and upgradable. Standard diffuser for visual comfort and to eliminate LED source visibility. A variety of mounting options are available.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. See mounting and color pages for standard finishes. Interior is Matte White unless specified. Custom Color interior finish available.

ELECTRONICS

GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 80+. Higher CRI, R9 and custom LED configurations are available; consult factory. Variety of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Fixtures are spun in our factory from 0.063 high purity aluminum. Die-cast aluminum heat sink for optimal thermal management. Low profile frosted diffuser over LEDs to eliminate direct source visibility.

CODE COMPLIANCE

BAA compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.

SERIES SIZES


BU40GV



WALL MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & DIMENSIONS.)

PA_
MOUNTING ARM STYLE



BU40GV SHOWN WITH CP104PA23

CEILING MOUNT

(SEE MOUNTING PAGES FOR MORE OPTIONS & CANOPY DIMENSIONS.)

HM / AT / PM
HANG STRAIGHT / ALL THREAD / PENDANT



BU40GV SHOWN WITH RDC5PM

CD
CORD / CABLE MOUNT



BU40GV SHOWN WITH RDC5CD

CM
CORD MOUNT



BU40GV SHOWN WITH RDC5CM





CAPPUCCINO
DAMP LOCATION
 CAFÉS / PHOTOMETRIC DATA

DECORATIVE

BU40GV 15L 35K XX MF0 XX MWI

CANDLEPOWER CURVE TEST SP-00976	INTENSITY CANDELA 0° AZIMUTH	ZONAL LUMENS	SINGLE UNIT: PERFORMANCE INITIAL FOOTCANDLES BASED ON IES BEAM ANGLE	MULTIPLE UNITS: PERFORMANCE 80/50/20% REFLECTANCES INITIAL FOOTCANDLES AND WATTS PER SQUARE FOOT
	0.00°	0° - 10° 38 5%	Mounting Height AFF	Ceiling Height
	0.00° 388	0° - 20° 150 20%	FC at Center on Floor	Fixture Spacing
	5.00° 390	0° - 30° 312 42%	Beam Diameter	RCR 2
	10.00° 394	0° - 40° 449 60%	FC at Beam Edge	RCR 4
	15.00° 399	0° - 60° 651 88%		FC + W/Sq. Ft.
	20.00° 392	0° - 80° 738 99%		FC + W/Sq. Ft.
	30.00° 288	0° - 90° 744 100%		FC + W/Sq. Ft.
	40.00° 172	Total 744 100%		Delivered Illuminance Rating: (DIR)
	50.00° 123			1' Suspension Length
	60.00° 80			Square rooms used for multiple units:
	70.00° 41			- RCR 2: Length & Width = Ceiling Ht. - 3.5' x 5.00
	80.00° 13			- RCR 4: Length & Width = Ceiling Ht. - 3.5' x 2.50
90.00° 1			+ Average Footcandles at 2.5' Above Floor	
Delivered Lumens: 744	CP at 0deg (Nadir): 388	Beam Angle: 72.93	Lumen Multiplier: N/A	
Luminaire Watts: 11	CRI: 80	Spacing Ratio: 1.13	CCT Multiplier: 27K x 0.97, 30K x 0.99, 40K x 1.03	
LER: 67.64				



MOUNTING & ACCESSORIES

SOME OPTIONS NOT AVAILABLE ON ALL FIXTURES. CONSULT SPECIFICATION SHEETS. SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.
NOTE: THIS IS TYPICAL OF SPECLUME SPECIFICATION FOR PENDANT MOUNTING. INDIVIDUAL FIXTURES OR PROJECTS MAY HAVE SPECIALIZED REQUIREMENTS.



WALL MOUNTING

CP104 - SMALL DRIVER CANOPY (STANDARD)
MAY BE USED AS SPLICE BOX FOR DIRECT FEED

Ø 5.5
4.0

CUSTOM AND OTHER WALL ARMS AVAILABLE - CONTACT FACTORY. ARMS MAY BE FIELD CUT ON WALL SIDE - FIXTURE SIDE THREADED 3/4" NPT REQUIRES SEALANT FOR WET LOCATION.

PA16 - Front Wall Mount

15.0
13.0
25.0
WALL

CP6/RMD - REMOTE MOUNT DRIVER
MOUNTS DIRECTLY TO WALL OR OCTAGON STYLE J-BOX

Ø 4.7
1.8

PA15

15.0
9.8
8.3

PA24

15.0
18.0
9.5
24.0

PA32

32.6
19.5
10.5
30.0
32.2

PA16F - Back Wall Mount

15.0
13.0
25.0
WALL

PA17

17.0
7.0

PA26

28.5
12.7

PA36

36.0
7.0

PA16F - Back Wall Mount

20.0
13.0
25.0
WALL

PA22

22.0
7.5
5.0
12.5

SP90(XX)
Designed for Straight Arm Mounting
SPECIFY LENGTH

EXAMPLE: SP9024 - STRAIGHT PIPE 24" LONG

PA23

23.0
7.0

PA90(WXX)(DXX)
SPECIFY LENGTH (Wxx)
SPECIFY DROP (6.5 Minimum) (Dxx)

EXAMPLE: PA90W20D07 - 90° PIPE 20 LONG 7" DEEP THREADED AT FIXTURE END

PA23(XX)
SPECIFY LENGTH

EXAMPLE: PA2330 - 30" PA23

PA48

48.0
7.0

PA901212

12.0
12.0

CEILING MOUNTING

<p>RDC5 - SMALL DRIVER CANOPY (STANDARD) MOUNTS TO 4" OCTO J-BOX</p> <p>Ø 5.3 2.5</p>	<p>HM* HANG STRAIGHT 45° SWIVEL 1/2" STEM - 3/8" NPT</p> <p>45°</p> <p>ORDER: HM (Length) SPECIFY LENGTH: HM3 - 3" HM24 - 24" HM6 - 6" HM36 - 36" HM12 - 12" HM48 - 48" HM18 - 18" HM72 - 72" HMLC(XX) Custom Length (Specify in Inches)</p>	<p>AT** HANG STRAIGHT ALL THREAD 45° SWIVEL 1/2" STEM - 1/4" IP</p> <p>45°</p> <p>FIELD CUTTABLE</p> <p>ORDER: AT (Length) SPECIFY LENGTH: AT12 - 12" AT48 - 48" AT24 - 24" AT60 - 60" AT36 - 36" AT72 - 72"</p> <p><small>FIELD CUT THREADED PIPE TO LENGTH NEEDED CUT PIPE COVER 2/8" SHORTER THAN THREADED PIPE SLIP "PIPE COVER" OVER THREADED PIPE</small></p>	<p>PM* RIGID PENDANT MOUNT RIGID 1/2" STEM - 3/8" NPT</p> <p>0°</p> <p>ORDER: PM (Length) SPECIFY LENGTH: PM3 - 3" PM24 - 24" PM6 - 6" PM36 - 36" PM12 - 12" PM48 - 48" PM18 - 18" PM72 - 72" PMLLC(XX) Custom Length (Specify in Inches)</p>	<p>CD CORD / CABLE MOUNT SJ CORD WITH 1/16 SS CABLE</p> <p>ADJUST AND LOCKS</p> <p>ORDER: CD (Length) SPECIFY LENGTH: CD36 - 36" CD72 - 72" CD144 - 144" CDLC(XX) Custom Length (Specify in Inches)</p>	<p>CM CORD MOUNT SJ CORD WITH STRAIN RELIEF</p> <p>ORDER: CM (Length) SPECIFY LENGTH: CM36 - 36" CM72 - 72" CM144 - 144" CMLC(XX) Custom Length (Specify in Inches)</p>
--	---	--	--	--	--

*MAXIMUM ONE PIECE STEM LENGTH IS 72". **MAXIMUM ONE PIECE STEM LENGTH IS 36". LONGER LENGTHS ARE POSSIBLE USING MULTIPLE STEMS AND COUPLERS.
**ORDER IN 12" INCREMENTS, ODD SIZES MAY BE FIELD CUT

COLOR OPTIONS - POWDER COAT PAINT FINISHES

NOTE: NO PRINTED IMAGE CAN EQUAL THE EXACT COLOR OF FINISH ON METAL.
SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.



STANDARD CORD / STEM / CANOPY FINISHES

FIXTURE COLOR	STANDARD CORD COLOR	STANDARD CANOPY / STEM COLOR
Matte White, Textured White	Matte White	Matte White
Gloss White	Matte White	Gloss White
Matte Black, Gloss Black, Textured Black	Matte Black	Matte Black
All Others	Matte Black	Same Color as Fixture
Custom Color	Contact Factory	Contact Factory

PAINT TIMES

TIER	COST	AVERAGE PAINT TIME*
Tier 1 - Standard Finishes	\$	⓪
Tier 2 - Typical Finishes	\$\$	⓪⓪
Tier 3 - Special Metal Finishes	\$\$\$	⓪⓪⓪
Custom Color	Contact Factory	Contact Factory

*CONTACT FACTORY FOR SPECIFIC PRODUCT LEAD TIMES


TIER 1 - STANDARD FINISHES



TIER 2 - TYPICAL FINISHES



TIER 3 - SPECIAL METAL FINISHES



CUSTOM COLOR FINISHES

CONTACT FACTORY

CC
Custom Color



*UNAVAILABLE FOR WET LOCATION

**UNAVAILABLE FOR INTERIOR

