




**CLOUD 11" SQUARE
SURFACE LIGHT**
GV SERIES / 1500 LUMENS



A	B
3.9	11.0
99.1 mm	279.4 mm

PROJECT: _____
QUANTITY: _____ TYPE: _____

SX1003SQLEDGV

APPLICATION

Cloud 11" surface square light for area illumination.

FEATURES

Speculume series fixtures offer contemporary style with functional luminaire performance. Fixtures designed and manufactured in our factory. Fixture produces horizontal and vertical illumination. Designed for through wiring. Reflective gloss white reflector behind LED for enhanced light output. Interchangeable LED module for ease of maintenance. A variety of mounting options are available.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. See mounting and color pages for standard finishes.

ELECTRONICS

GV LED system features high brightness white Samsung LED's. 3 step MacAdam Ellipse binning. Standard CRI: 85+. Higher CRI, R9 and custom LED configurations are available; consult factory. Variety of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Fixtures are fabricated in our factory from .063 high purity aluminum. Passive aluminum heatsink for optional thermal management. Formed UV stabilized opal white acrylic diffuser.

CODE COMPLIANCE

BAA Compliant. ETL listed for damp locations. ADA Compliant. Manufactured and tested to UL standards No. 1598/8750.

WATTAGE TO LUMENS UPDATE			
CURRENT PART NUMBER EXAMPLE	PREVIOUS PART NUMBER EXAMPLE	SOURCE LUMENS ¹	SYSTEM WATTS
SX1003SQLEDGV15L	SX1003SQLEDGV14W	1500	9

SERIES	LUMENS ¹	CCT	DRIVER / DIMMING ²	OPTIONS ³	MOUNTING ⁴	DIFFUSER	FINISH ⁶
SX1003SQLEDGV	15L 1500 Lm	27K 2700K	EX Electronic Driver, 120V/277V DS10X 10% 0-10V Dimming, 120V/277V DO10X 1% 0-10V Dimming, 120V/277V DS2W1 2 Wire Phase Dimming, 120V	FS Fuse Holder and Fuse GS Ceiling Level Gasket	SM Surface Mount HM ⁵ Hang Straight PM ⁵ Swivel Fitting PM ⁵ Pendant Mount WM Wall Mount	OP White Opal Acrylic POP White Opal Polycarbonate	MW ⁷ Matte White
		30K 3000K					MB ⁷ Matte Black
		35K 3500K					PT ⁷ Platinum
		40K 4000K					TW Textured White
							TB Textured Black
							MT Textured Silver
							BZ Bronze
							OB Oil Rubbed Bronze
							CH Charcoal
							GH Graphite
							AC Champagne
							SN Sun Gold
							BR Brecchia Rust
							AN Anodic Natural
							CO Copper Metallic
							CC Custom Color

EXAMPLE: SX1003SQLEDGV15L35KEXSMOPMW

NOTES:
1 Nominal Source Lumens at 3500K 2 Contact Factory for Additional Options 3 See Product Options Page for Details 4 See Mounting Page for Details on Components and Finishes
5 Specify Length in Inches: See Mounting Page for Available Lengths 6 Contact Factory for Special Finishes 7 Standard Finishes



COLOR OPTIONS - POWDER COAT PAINT FINISHES

NOTE: NO PRINTED IMAGE CAN EQUAL THE EXACT COLOR OF FINISH ON METAL.
SEE INDIVIDUAL SPECIFICATION SHEETS OR CONSULT FACTORY FOR ADDITIONAL INFORMATION.



STANDARD CORD / STEM / CANOPY FINISHES


FIXTURE COLOR	STANDARD CORD COLOR	STANDARD CANOPY / STEM COLOR
Matte White, Textured White	Matte White	Matte White
Gloss White	Matte White	Gloss White
Matte Black, Gloss Black, Textured Black	Matte Black	Matte Black
All Others	Matte Black	Same Color as Fixture
Custom Color	Contact Factory	Contact Factory

PAINT TIMES


TIER	COST	AVERAGE PAINT TIME*
Tier 1 - Standard Finishes	\$	⓪
Tier 2 - Typical Finishes	\$\$	⓪⓪
Custom Color	Contact Factory	Contact Factory

*CONTACT FACTORY FOR SPECIFIC PRODUCT LEAD TIMES

TIER 1 - STANDARD FINISHES



TIER 2 - TYPICAL FINISHES



CUSTOM COLOR FINISHES

CONTACT FACTORY

CC
Custom Color



*UNAVAILABLE FOR WET LOCATION

