



A	B	C	D	E
6.4	.625	6.0	10L-13L: 13.2	9.5
162.6 mm	15.2 mm	152.4 mm	20L: 19.2	241.3 mm

## RAZI6XT - TRIMLESS / IC RATED

### APPLICATION

Versatile 6" Round aperture recessed LED accent light for Insulated Ceiling installations with flangeless trim and a wide range of lumens and optical controls.

### FEATURES

LED module tilts 30°, rotates 360°. Two-stage optical system for smooth light distribution and focus control. Quick change LED module with interchangeable optics for job site adjustment and fixture maintenance. Shallow plenum design. Tool-less driver and j-box access. Posi-lock trim retention torsion springs.

### TRIM FINISH

A variety of architectural powdercoat and anodized finishes are available.

Plaster mesh fitter included.

### ELECTRONICS

LED system features Xicato LED module with proprietary phosphor technology that provides consistent, stable color with CCT control of +/- 100K over life of the light engine. Base CRI is 83 with 2-step MacAdam Ellipse binning. High CRI is 98 with 1x2-step MacAdam Ellipse binning. Variety of electronic 120V/277V and dimming drivers.

### CONSTRUCTION

Housing/frame constructed of #20 ga. galvanized steel to resist corrosion. Flangeless one piece trim spun from 0.063" thick high purity aluminum and finished to specification.

### CODE COMPLIANCE

BAA Compliant. IC rated. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Optional Wet location. Manufactured and tested to UL standards No. 1598/8750.

WATTAGE TO LUMENS UPDATE					
CURRENT PART NUMBER EXAMPLE	PREVIOUS PART NUMBER EXAMPLE	SOURCE LUMENS <sup>1</sup>	DELIVERED LUMENS <sup>2</sup>	SYSTEM WATTS	LPW
RAZI6XT10L	RAZI6LEDX15W	1000	833	11.1	75
RAZI6XT13L	RAZI6LEDX120W	1300	1122	15.0	75
RAZI6XT20L	RAZI6LEDX133W	2000	1727	23.7	73

SERIES	LUMENS <sup>1</sup>	CCT	OPTICS	DRIVER / DIMMING / VOLTAGE <sup>4</sup>	OPTIONS <sup>5</sup>	TRIM	FINISH	TRIM OPTIONS <sup>11</sup>			
RAZI6XT	83 CRI		<b>XN<sup>3</sup></b> 10° <b>ND</b> 26° <b>MD</b> 45° <b>WD</b> 50° <b>XW</b> 55°	<b>E_</b> Electronic Driver <b>DS10_</b> 10% 0-10V <b>DO10_</b> 1% 0-10V <b>DS2W1</b> 1%, ELV/MLV, 120V <b>DL3E_</b> 1% Lutron® EcoSystem®, Fade <b>EL10_</b> 1%, eldoLED <b>EDO1_</b> 0.1%, eldoLED <b>DALI_</b> DALI Control	<b>1</b> 120V <b>2</b> 277V	<b>BH27<sup>6</sup></b> 27" Solid Bars <b>H12</b> 12" - 24" Expandable Bars <b>H06</b> 6" - 12" Expandable Bars <b>CB24</b> 24" C-Channel Bars <b>EMRM</b> Remote Emergency Battery Pack <b>FS</b> Fusing <b>EB</b> Black Housing <b>CR</b> Corrosion Resistant <b>PR<sup>7</sup></b> Deep Ceiling Extension <b>CCEA</b> Chicago Ceiling Plenum Rated <b>AMB</b> Anti Microbial Finish	<b>RA6NXT<sup>9</sup></b>	<b>SG<sup>9</sup></b> Semi-Diffuse <b>HZ</b> Haze Full Diffuse <b>MW</b> Matte White <b>MB</b> Matte Black <b>PT</b> Platinum Silver <b>OB</b> Oil Rubbed Bronze <b>CH</b> Charcoal <b>AC</b> Anodic Champagne <b>AS</b> Anodic Sapphire <b>AM</b> Anodic Malachite <b>SN</b> Sun Gold <b>CO</b> Copper Metallic <b>GH</b> Graphite <b>AMB</b> Anti Microbial Finish <b>CC<sup>10</sup></b> Custom Color	<b>SOX<sup>12</sup></b> Micro Prism Solite™ Lens <b>GLX<sup>13</sup></b> Clear Glass Lens <b>PGX</b> Prismatic Glass Lens <b>FGX</b> Frosted Glass Lens  <b>SOW</b> Micro Prism Solite™ Lens Wet Location <b>GLW</b> Clear Glass Lens Wet Location <b>PGW</b> Prismatic Glass Lens Wet Location <b>FGW</b> Frosted Glass Lens Wet Location		
	10L	1000 Lm								27K	2700K
	13L	1300 Lm								30K	3000K
	20L	2000 Lm								35K	3500K
										40K	4000K
	98 CRI										
	10L	1000 Lm								27HK	2700K
	13L	1300 Lm								30HK	3000K
	20L	2000 Lm								35HK	3500K
										40HK	4000K

### EXAMPLE: RAZI6XT10L35KNDE1/H12/RA6NXTSG

**NOTES:**  
 1 Nominal Source Lumens at Any CCT 2 Nominal Delivered Lumens 83 CRI at Any CCT with ND-SG, No Lens, Aimed at 0° 3 XN 13L Max at 83 and 98 CRI 4 Contact Factory for Additional Options 5 See Product Options Page for Details  
 6 Standard Bar Hangers 7 Contact Factory 8 "\*" Indicates Flangeless Trim 9 Standard Finish 10 Contact Factory for Special Finishes 11 Contact Factory for Special Lenses/Louvers 12 Standard Lens for MD, WD, XW  
 13 Standard Lens for XN and ND

PROJECT: \_\_\_\_\_  
 QUANTITY: \_\_\_\_\_ TYPE: \_\_\_\_\_

