



SGS6SQLEDOS - TRIM FLANGE / NON-IC RATED

APPLICATION

6" LED Recessed shallow plenum square aperture downlight for general downlighting.

FEATURES

Two-stage optical system for smooth light distribution. Zhaga International Standard LED module for ease of maintenance and replacement. Shallow plenum design. Tool-less LED module, driver and J-Box access. Multi-Bar mounting brackets. BH27 Standard mounting bars included. Posi-lock trim retention torsion springs. Integral 0.625" collar.

TRIM FINISH

A variety of powdercoat and anodized finishes are available. Matte white flange is standard.

ELECTRONICS

LED module features high brightness white Osram LEDs. 3-step MacAdam Ellipse binning and CRI 84 minimum. Variety of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Housing/frame constructed of #20 ga. galvanized steel to resist corrosion. Self-Flanged one piece trim die-cast high purity aluminum and finished to specification. Passive machined aluminum heatsink.

CODE COMPLIANCE

BAA Compliant. Non-IC rated. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Optional Wet location. LM79/LM80/TM21 data available. Manufactured and tested to UL standards No. 1598/8750.

WATTAGE / LUMENS DATA		
PART NUMBER	SOURCE LUMENS ¹	SYSTEM WATTS
SGS6SQLEDOS10L	1100	11
SGS6SQLEDOS15L	1500	13
SGS6SQLEDOS20L	2000	20
SGS6SQLEDOS30L	3000	28
SGS6SQLEDOS45L	4500	41

SERIES	LUMENS ¹	CCT	DRIVER / VOLTAGE ²	OPTIONS ³	TRIM	FINISH	TRIM OPTIONS
SGS6SQLEDOS	10L 1100 Lm	27K 2700K	E Electronic Driver DS10_ 10%, 0-10V DO10_ 1%, 0-10V DS2W1 1%, ELV/MLV, 120V DLTE1 1% Lutron® 2-Wire Forward Phase, 120V DL3E_ 1% Lutron® EcoSystem®, Fade EL10_ 1%, eldoLED ED01_ 0.1%, eldoLED DALI_ DALI Control	1 BH27 ⁴ 27" Solid Bars 2 H12 12" - 24" Expandable Bars H06 6" - 12" Expandable Bars CB24 24" C-Channel Bars FS Fusing EB Fixture Painted Black CR Corrosion Resistant PR ⁵ Deep Ceiling Extension GR Goof Ring ZIG ZigBee Module BLU Bluetooth LE EM ⁶ 7W Emergency Battery Switch Remote EMIT ⁷ 7W Emergency Battery Switch in Trim AMB Anti-Microbial Finish	CAS0366OS	MW ⁸ Matte White MB Matte Black PT Platinum Silver BZ Bronze OB Oil Rubbed Bronze CH Charcoal AS Anodic Sapphire AN Anodic Natural AC Anodic Champagne AZ Anodic Bronze AK Anodic Black AM Anodic Malachite SN Sun Gold CO Copper Metallic GH Graphite CC ⁹ Custom Color	SO ¹⁰ Micro Prism Solite™ Lens FG Frosted Glass Lens FGCC Frosted Glass Clear Center FO90 White Optical Acrylic GS Gasket WL Wet Location EMIT ⁷ Emergency Test Switch in Trim WF ¹¹ White Flange AMB Anti-Microbial Finish
	15L 1500 Lm	30K 3000K					
	20L 2000 Lm	35K 3500K					
	30L 3000 Lm	40K 4000K					
	45L 4500 Lm						

EXAMPLE: SGS6SQLEDOS30L35KE1/CAS0366OSMWSO

NOTES:
¹ Nominal Source Lumens at 35K ² Contact Factory for Additional Options ³ See Product Options Page for Details ⁴ Standard Bar Hangers ⁵ Contact Factory ⁶ Standard EM ⁷ EMIT Suffix Required on Trim and Housing
⁸ Standard Finish ⁹ Contact Factory for Special Finishes ¹⁰ Standard Lens ¹¹ Otherwise Flange Is Same Color As Interior Of Trim



PROJECT: _____
 TYPE: _____



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.