



A	B	C	D	E	F
5.6 142.2 mm	625 15.2 mm	6.0 152.4 mm	7.5 191.0 mm	13.2 335.3 mm	9.5 241.3 mm

## SWFO6PC - TRIM FLANGE / NON-IC RATED

### APPLICATION

Versatile 6" Square aperture recessed LED wall wash with a wide range of lumens and control options.

### FEATURES

Two-stage optical system for smooth light distribution and focus control. Quick change LED module with interchangeable optics for job site adjustment and fixture maintenance. Shallow plenum design. Tool-less driver and j-box access. Posi-lock trim retention torsion springs. See RWZO4 series for trimless plaster or wood ceiling.

### TRIM FINISH

A variety of architectural powdercoat and anodized finishes are available.

Matte white flange is standard.

### ELECTRONICS

LED module features high brightness Philips LEDs. 3-step MacAdam Ellipse binning and 80 and 90 CRI available. Variety of electronic 120V/277V and dimming drivers.

### CONSTRUCTION

Housing/frame constructed of #20 ga. galvanized steel to resist corrosion. Self-Flanged one piece trim spun from 0.063" thick high purity aluminum and finished to specification.

### CODE COMPLIANCE

BAA Compliant. Non-IC rated. UL certified to meet US and Canadian standards. Suitable for dry or damp locations. Optional Wet location. Manufactured and tested to UL standards No. 1598/8750.

### WATTAGE TO LUMENS UPDATE

CURRENT PART NUMBER EXAMPLE	SOURCE LUMENS <sup>1</sup>	SYSTEM WATTS
SWFO6PC10L	1100	15.2
SWFO6PC20L	2100	23.2
SWFO6PC30L	3000	31.0

SERIES	LUMENS <sup>1</sup>	CCT	OPTICS	DRIVER / VOLTAGE <sup>2</sup>	OPTIONS <sup>3</sup>	TRIM	FINISH	TRIM OPTIONS <sup>5</sup>				
SWFO6PC	80 CRI		XW Extra Wide	E <sub>-</sub> Electronic Driver DS10 <sub>-</sub> 10% 0-10V DO10 <sub>-</sub> 1% 0-10V	1 120V 2 277V	BH27 <sup>4</sup> 27" Solid Bars H12 12" - 24" Expandable Bars H06 6" - 12" Expandable Bars CB24 24" C-Channel Bars EM 7W Emergency Battery Test Switch Remote	SW6FPC <sup>5</sup>	MW <sup>6</sup> Matte White MB Matte Black PT Platinum Silver OB Oil Rubbed Bronze CH Charcoal AC Anodic Champagne AS Anodic Sapphire AM Anodic Malachite SN Sun Gold CO Copper Metallic GH Graphite AMB Anti Microbial Finish CC <sup>7</sup> Custom Color				
	10L	1100 Lm							27K	2700K	SKW <sup>8</sup>	Linear Wall Wash Lens
	20L	2100 Lm							30K	3000K	SKW	Linear Wall Wash Lens Wet Location
	30L	3100 Lm							35K	3500K		
									40K	4000K		
	90 CRI											
10L	1000 Lm	27HK	2700K									
20L	2000 Lm	30HK	3000K									

**EXAMPLE:** SWFO6PC10L35KWDE1/BH27/SW6FPCMWSKX

#### NOTES:

1 Nominal Source Lumens at Any CCT 2 Contact Factory for Additional Options 3 See Product Options Page for Details 4 Standard Bar Hangers 5 "F" Indicates Self-Flange Trim, Matte White Standard 6 Standard Finish 7 Contact Factory for Special Finishes 8 Contact Factory for Special Lenses/Louvers 9 Standard Lens 10 Flange and Reflector Same Finish



PROJECT: \_\_\_\_\_  
TYPE: \_\_\_\_\_



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.