



A	B	C	D	S1	S2
5.0 127.0 mm	.625 15.9 mm	13.3 337.8 mm	7.9 200.7 mm	5.8 147.3 mm	7.5 190.5 mm

SGW6LEDGV - TRIM FLANGE / NON-IC RATED

APPLICATION

6" Round aperture shallow recessed LED wall wash for general illumination.

FEATURES

Two-stage optical system with medium depth reflector design delivers smooth glare-free general illumination. Tool-less LED module, driver, and J-Box access. Multi-Bar mounting brackets. BH27 Standard mounting bars included. Posi-lock trim retention springs. Integral 0.625" collar, with Deep Ceiling Extension (PR), consult factory.

TRIM FINISH

A variety of architectural powdercoat and anodized finishes are available.

Matte White flange is standard.

ELECTRONICS

GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 85+. Higher CRI, R9 and custom LED configurations are available; consult factory. A variety of electronic 120V/277V and dimming drivers available.

CONSTRUCTION

Housing/frame constructed of #20 ga. galvanized steel to resist corrosion. Self-flanged one piece trim spun from 0.063" thick high purity aluminum and finished to specification. Passive machined aluminum heatsink.

CODE COMPLIANCE

BAA Compliant. Non-IC rated. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.

WATTAGE TO LUMENS UPDATE			
CURRENT PART NUMBER EXAMPLE	PREVIOUS PART NUMBER EXAMPLE	SOURCE LUMENS ¹	SYSTEM WATTS
SGW6LEDGV15L	SGW6LEDGV14W	1500	13.3
SGW6LEDGV27L	SGW6LEDGV26W	2700	22.3
SGW6LEDGV37L	SGW6LEDGV37W	3700	29.1
SGW6LEDGV55L	SGW6LEDGV55W	5500	42.6

SERIES	LUMENS ¹	CCT	DRIVER / VOLTAGE ²	OPTIONS ³	TRIM	FINISH ⁶	TRIM OPTIONS
SGW6LEDGV	15L 1500 Lm	27K 2700K	E Electronic Driver	BH27 ⁴ 27" Solid Bars	AR6922GV ⁷	SG ⁸ Semi-Diffuse	SK ⁹ Skytex™ Lens
	27L 2700 Lm	30K 3000K	DS10 10% 0-10V	H12 12" - 24" Expandable Bars			
	37L 3700 Lm	35K 3500K	DO10 1% 0-10V	H06 6" - 12" Expandable Bars			
	55L 5500 Lm	40K 4000K	DS2W1 1% ELV/MLV, 120V	CB24 24" C-Channel Bars			
			DLTE1 1% Lutron® 2-Wire Forward Phase, 120V	EM Integral Emergency Battery			
	50K 5000K	DL3E 1% Lutron® EcoSystem®, Fade	FS Fusing	EB Black Housing	OB Oil Rubbed Bronze	CH Charcoal	
		EL10 1%, eldoLED	CR Corrosion Resistant	EB Black Housing	AC Anodic Champagne	AS Anodic Sapphire	
		ED01 0.1%, eldoLED	PR ⁵ Deep Ceiling Extension	CR Corrosion Resistant	AM Anodic Malachite	SN Sun Gold	
		DALI DALI Control	GR Goof Ring	PR ⁵ Deep Ceiling Extension	CO Copper Metallic	GH Graphite	
				GR Goof Ring	AMB Anti Microbial Finish	CC Custom Color	
				AMB Anti Microbial Finish			

EXAMPLE: SGW6LEDGV37L30KE1BH27/AR6922GVMWSK

NOTES:
1 Nominal Source Lumens at 35K 2 Contact Factory for Additional Options 3 See Product Options Page For Details 4 Standard Bar Hangers 5 Contact Factory 6 Contact Factory for Special Finishes
7 Matte White Flange Standard 8 Standard Finish 9 Standard Lens



PROJECT: _____
TYPE: _____



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.