



8" ROUND LED WALL WASH

OS SERIES / 4500 LUMENS MAX



A	B	C	D	S1	S2
4.7	0.625	14.0	9.38	7.5	9.2
119.38 mm	15.9 mm	355.6 mm	238.3 mm	190.5 mm	233.68 mm

SGW8LEDOS - TRIM FLANGE / NON-IC RATED

APPLICATION

8" LED Recessed wall wash aperture downlight for general illumination.

FEATURES

Two-stage optical system for smooth light distribution. Zhaga International Standard LED module for ease of maintenance and replacement. Shallow plenum design. Tool-less LED module, driver and J-Box access. Multi-Bar mounting brackets. BH27 Standard mounting bars included. Posi-lock trim retention torsion springs. Integral 0.625" collar.

TRIM FINISH

A variety of architectural powdercoat and anodized finishes are available. Matte white flange is standard.

ELECTRONICS

LED module features high brightness white Osram LEDs. 3-step MacAdam Ellipse binning and CRI 84 minimum. Full range of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Housing/frame constructed of #20 ga. galvanized steel to resist corrosion. Self-flanged one piece trim spun from 0.063" thick high purity aluminum and finished to specification. Passive machined aluminum heatsink.

CODE COMPLIANCE

BAA Compliant. Non-IC rated. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Optional Wet location. LM79/LM80/TM21 data available. Manufactured and tested to UL standards No. 1598/8750.

WATTAGE TO LUMENS UPDATE					
CURRENT PART NUMBER EXAMPLE	PREVIOUS PART NUMBER EXAMPLE	SOURCE LUMENS ¹	DELIVERED LUMENS ²	SYSTEM WATTS	LPW
SGW8LEDOS10L	SGW8LEDOS14W	1100	654	11	59
SGW8LEDOS15L	N/A	1500	819	13	63
SGW8LEDOS20L	SGW8LEDOS25W	2000	1390	20	70
SGW8LEDOS30L	SGW8LEDOS35W	3000	1910	28	68
SGW8LEDOS45L	N/A	4500	2828	41	69

SERIES	LUMENS ¹	CCT	DRIVER / VOLTAGE ³	OPTIONS ⁴	TRIM	FINISH	TRIM OPTIONS		
SGW8LEDOS	10L	1100 Lm	27K 2700K 30K 3000K 35K 3500K 40K 4000K	E Electronic Driver DS10_ 10%, 0-10V DO10_ 1%, 0-10V DS2W1 1%, ELV/MLV, 120V DLTE1 1% Lutron® 2-Wire Forward Phase, 120V DL3E_ 1% Lutron® EcoSystem®, Fade EL10_ 1%, eldoLED ED01_ 0.1%, eldoLED DALI_ DALI Control	1 120V 2 277V	BH27 ⁵ 27" Solid Bars H12 12" - 24" Expandable Bars H06 6" - 12" Expandable Bars CB24 24" C-Channel Bars FS Fusing EB Fixture Painted Black CR Corrosion Resistant PR ⁶ Deep Ceiling Extension GR Goof Ring ZIG ⁷ ZigBee Module BLU ⁷ Bluetooth LE EM ⁸ 7W Emergency Battery Test Switch Remote EMIT ⁹ 7W Emergency Battery Test Switch in Trim AMB Anti-Microbial Finish	AR8923OS	MW ¹⁰ Matte White MB Matte Black SG Semi-Diffuse HZ Haze Full Diffuse PT Platinum Silver BZ Bronze OB Oil Rubbed Bronze CH Charcoal AS Anodic Sapphire AN Anodic Natural AC Anodic Champagne AZ Anodic Bronze AK Anodic Black AM Anodic Malachite SN Sun Gold CO Copper Metallic GH Graphite CC ¹¹ Custom Color	SK ¹² Skytext™ Lens GS Gasket WL Wet Location EMIT ⁹ Emergency Test Switch in Trim PF ¹³ Polished Flange AMB Anti-Microbial Finish
	15L	1500 Lm							
	20L	2000 Lm							
	30L	3000 Lm							
	45L	4500 Lm							

EXAMPLE: SGW8LEDOS10L30KE1/AR8923OSSGSK

NOTES:
 1 Nominal Source Lumens at 35K 2 Nominal Delivered Lumens at 35K with SG-SK 3 Contact Factory for Additional Options 4 See Product Options Page for Details 5 Standard Bar Hangers 6 Contact Factory
 7 Order DS101/2 When Specifying ZIG or BLU 8 Standard EM 9 EMIT Suffix Required on Trim and Housing 10 Standard Finish 11 Contact Factory for Special Finishes 12 Standard Lens 13 Flange and Reflector Same Finish



PROJECT: _____
 TYPE: _____



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.