

**SR10SQLEDOA**

**APPLICATION**

10" square recessed LED downlight LED features soffit/area light for optimal performance.

**FEATURES**

Efficient, powerful LED light source, designed to exceed 50,000 hours of life (L70). Multi-Bar mounting brackets. All LED modules and drivers are replaceable and up-gradeable. New and Retrofit/Remodeler options. Wet location use screws fasteners. (4)

**FINISH**

A variety of architectural powdercoat and anodized finishes are available. Matte White flange is standard.

**ELECTRONICS**

LED module features high brightness white Nichia LEDs. 3-step MacAdam Ellipses binning and CRI 84 minimum. Variety of electronic 120V/277V and dimming drivers.



**CONSTRUCTION**

Housing constructed of .050 5052-H32 aluminum. Trim fabricated from aluminum extrusion and finished to specification.

**CODE COMPLIANCE**

BAA Compliant. Non-IC rated. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Optional Wet location. Manufactured and tested to UL standards No. 1598/8750.

WATTAGE TO LUMENS UPDATE			
CURRENT PART NUMBER EXAMPLE	PREVIOUS PART NUMBER EXAMPLE	SOURCE LUMENS <sup>1</sup>	SYSTEM WATTS
SR10SQLEDOA10L	SR10SQLEDOA12W	1100	12W
SR10SQLEDOA20L	SR10SQLEDOA22W	2200	22W
SR10SQLEDOA30L	SR10SQLEDOA33W	3300	33W
SR10SQLEDOA40L	SR10SQLEDOA42W	4000	42W



SERIES	LUMENS <sup>1</sup>	CCT	DRIVER / VOLTAGE <sup>2</sup>	OPTIONS <sup>3</sup>	TRIM	FINISH <sup>5</sup>	OPTIONS		
SR10SQLEDOA	10L	1000 Lm	E Electronic Driver DS10 10%, 0-10V	1 120V 2 277V	BH27 <sup>4</sup> 27" Solid Bars H12 12" - 24" Expandable Bars H06 6" - 12" Expandable Bars CB24 24" C-Channel Bars FS Fusing EM Integral Emergency Battery CR Corrosion Resistant RM Remodeler Housing	MW <sup>6</sup> Matte White GW Gloss White MB Matte Black GB Gloss Black BZ Bronze PT Platinum CC Custom Color	FO <sup>7</sup> Matte White Acrylic Lens 90% Efficient SO Solite Lens WL <sup>8</sup> Wet Location		
	20L	2000 Lm						30K	3000K
	30L	3000 Lm						40K	4000K
	40L	4000 Lm						50K	5000K

**EXAMPLE:** SR10SQLEDOA20L30KE1BH27/FT1010GW/FO

**NOTES:**  
1 Nominal Source Lumens 2 Contact Factory for Additional Options 3 See Product Options Page for Details 4 Standard Bar Hangers 5 Contact Factory for Special Finishes  
6 Standard Finish 7 Standard Lens 8 Trim Secured with 4 Screws



PROJECT: \_\_\_\_\_  
TYPE: \_\_\_\_\_



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.