



**2' X 4' FLAT PANEL**  
**DAMP LOCATION**  
 PANELUME SERIES / 6500 LUMENS

PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_



SERIES	LUMENS <sup>1</sup>	CCT	DRIVER / VOLTAGE
PL2448	65L 6500 Lm	30K 3000K 40K 4000K 50K 5000K	DX 1%, 0-10V, 120V/277V

EXAMPLE: PL244865L40KDX

NOTES:  
 1 Nominal Delivered Lumens at 40K



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.




**2' X 4' FLAT PANEL**  
**DAMP LOCATION**  
 PANELUME SERIES / 6500 LUMENS

LUMENS / WATTAGE DATA			
PART NUMBER	DELIVERED LUMENS <sup>1</sup>	SYSTEM WATTS	LPW
PL244865L40KDX	6500	50	130

<sup>1</sup> Nominal Source Lumens at 40K

**HOUSING DIMENSIONS**



A	B	C
47.75	23.75	2.125
1213.0 mm	603.0 mm	54.0 mm

Weight: 7 Lbs

**APPLICATION**

2' x 4' rectangular recessed flat panel for general illumination.

**FEATURES**

Designed for recessed grid ceiling installation. Edge led acrylic produces uniform lens illumination. Shallow construction is ideal for spaces with restricting plenum heights.

**FINISH**

Platinum Silver powdercoat is standard.

**ELECTRONICS**

LED system features high brightness white LED's. CRI is 80 with 3-step MacAdam Ellipse binning. 0-10V 10% 120V/277V dimming driver standard.

**CONSTRUCTION**

Housing constructed of extruded anodized aluminum. Etched acrylic lens is optimized for edge lighting.

**CODE COMPLIANCE**

Non-IC rated. ETL listed for damp locations. Manufactured and tested to UL standards No. 1598/8750.

