



A	B
12.0 304.8 mm	13.8 350.5 mm

ANGLED REFLECTOR QUICK SHIP

INTERIOR SIGN LIGHT SERIES



AR1214GV - CEILING MOUNT

QUICK SHIP

Quick Ship Surface highlights products that can ship in 5 - 10 working days. See standard specification sheet for full range of options.

APPLICATION

Angled Reflector light is perfect for a variety of sign and surface lighting applications. GV Series is designed for damp or dry locations.

FEATURES

Spectrum Lighting's RLM Classics are reproductions of early American lighting fixtures reimagined with modern LED light sources and materials. LED module and driver are serviceable for future replacement.

FINISH

Multi-stage polyester powder-coat process applied on our dedicated paint lines. Interior is Matte White.

ELECTRONICS

GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 85+. Choice of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Fixture shades are spun in our factory from 0.063 high purity aluminum. Wall mount canopies are die-cast aluminum with stainless steel hardware. Wall arms are formed 3/4 NPT aluminum pipe.

CODE COMPLIANCE

BAA Compliant. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.

LUMENS / WATTAGE DATA		
PART NUMBER	SOURCE LUMENS ¹	SYSTEM WATTS
AR1214GV15L	1500	11.3
AR1214GV27L	2700	20.3

SERIES	LUMENS ¹		CCT		DRIVER / DIMMING		ACCESSORIES		MOUNTING ³		FINISH	
AR1214GV	15L	1500 Lm	35K	3500K	EX DS10X	Electronic Driver, 120V/277V 10%, 0-10V, 120V/277V	TF1	3" Frosted Dome	WALL MOUNT		MW	Matte White
	27L	2700 Lm	40K	4000K					CP104 PA23	Small Driver Canopy Mounting Arm Style		

EXAMPLE: AR1214GV15L35KEXTF1/CP104PA23MW

NOTES:
1 Nominal Source Lumens at 35K



PROJECT: _____
TYPE: _____



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.