



A	B	C1	C	D	E	F
3.43	.625	2.5	3.63	4.5	9.5	7.64
87.1 mm	15.9 mm	63.5 mm	92.2 mm	114.3 mm	241.3 mm	194.1 mm

Ceiling Cutout:  $\varnothing$  4"

### RDFO3LEDOC - TRIM FLANGE / NON-IC RATED

#### QUICK SHIP

Quick Ship highlights products that can ship in 3 - 5 working days. See standard specification sheet for full range of options.

#### APPLICATION

Versatile shallow plenum 3" round aperture recessed LED fixture features downlight, wall wash and adjustable accent trim options that are installed in one universal housing.

#### FEATURES

Two-stage optical system for smooth glare-free light distribution. Zhaga International Standard LED module for ease of maintenance and replacement. Shallow plenum design. Tool-less LED module, driver, and J-Box access. Multi-Bar mounting brackets. Posi-lock trim retention springs. Integral 0.625" collar.

#### TRIM FINISH

Matte White standard finish.

#### ELECTRONICS

LED module features high brightness white Philips LEDs. 3-step MacAdam Ellipse binning and CRI 84 minimum. Variety of electronic 120V/277V and dimming drivers.

#### CONSTRUCTION

Extruded and machined 6063-H32 aluminum passive heatsink. Carbon gasket for optimal thermal management. Housing/frame constructed of #20 ga. galvanized steel to resist corrosion. Self-flanged one piece die cast aluminum trim.

#### CODE COMPLIANCE

BAA Compliant. Non-IC rated. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.

SERIES	LUMENS	DRIVER / VOLTAGE	OPTIONS	TRIM	LUMENS	CCT	BEAM	FINISH	TRIM OPTIONS
RDFO3LED	OC10L	1100 Lm	<b>E</b> Electronic Driver 10%, 0-10V <b>DS10_</b> <b>DO10_</b> 1%, 0-10V <b>DS2W1</b> ELV/MLV, 120V	<b>1</b> 120V <b>2</b> 277V <b>H12</b> Expandable Bar Hangers, 12" - 24" <b>EM</b> 7W Emergency Battery Test Switch Remote	RD3F Downlight	1100 Lm	<b>27HK</b> 2700K <b>30HK</b> 3000K <b>35K</b> 3500K	<b>ND</b> <sup>1</sup> 20° <b>MD</b> 28° <b>WD</b> 36° <b>XW</b> 48°	<b>MW</b> Matte White  <b>NL</b> No Lens <b>SO</b> Micro Prism Solite™ Lens <b>GL</b> Clear Glass Lens
	OC20L	2100 Lm			2100 Lm	<b>27HK</b> 2700K <b>30HK</b> 3000K <b>35K</b> 3500K	<b>ND</b> <sup>1</sup> 20° <b>MD</b> 28° <b>WD</b> 36° <b>XW</b> 48°		

**EXAMPLE:** RDFO3LEDOC10LDS2W1H12/RD3FOC10L27HKNDMWGL

NOTES:  
1 GL Lens Only

Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.



<b>PROJECT:</b>	<b>TYPE:</b>
<b>CAT. NO.:</b>	

