




6" DEEP CUT OFF DOWNLIGHT

OS SERIES / 4500 LUMENS MAX



A	B	C	D	S1	S2
6.6	0.625	13.3	7.9	6.3	7.5
167.6 mm	15.9 mm	337.8 mm	200.66 mm	160.0 mm	190.5 mm

SGE6DLEDOS - TRIM FLANGE / NON-IC RATED

APPLICATION

6" LED Recessed open aperture deep cut off downlight for general downlighting.

FEATURES

Two-stage optical system for smooth light distribution. Zhaga International Standard LED module for ease of maintenance and replacement. Shallow plenum design. Tool-less LED module, driver and J-Box access. Multi-Bar mounting brackets. BH27 Standard mounting bars included. Posi-lock trim retention torsion springs. Integral 0.625" collar.

TRIM FINISH

A variety of architectural powdercoat and anodized finishes are available. Matte white flange is standard.

ELECTRONICS

LED module features high brightness white Osram LEDs. 3-step MacAdam Ellipse binning and CRI 84 minimum. Full range of electronic 120V/277V and dimming drivers.

CONSTRUCTION

Housing/frame constructed of #20 ga. galvanized steel to resist corrosion. Self-flanged one piece trim spun from 0.063" thick high purity aluminum and finished to specification. Passive machined aluminum heatsink.

CODE COMPLIANCE

BAA Compliant. Non-IC rated. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Optional Wet location. LM79/LM80/TM21 data available. Manufactured and tested to UL standards No. 1598/8750.

WATTAGE TO LUMENS UPDATE

CURRENT PART NUMBER EXAMPLE	PREVIOUS PART NUMBER EXAMPLE	SOURCE LUMENS ¹	SYSTEM WATTS
SGE6DLEDOS10L	SGE6LEDOS14W	1100	11
SGE6DLEDOS15L	N/A	1500	13
SGE6DLEDOS20L	SGE6LEDOS25W	2000	20
SGE6DLEDOS30L	SGE6LEDOS35W	3000	28
SGE6DLEDOS45L	N/A	4500	41

SERIES	LUMENS ¹	CCT	DRIVER / VOLTAGE ²	OPTIONS ³	TRIM	FINISH	TRIM OPTIONS	
SGE6DLEDOS	10L 1100 Lm	27K 2700K	E_ Electronic Driver DS10_ 10%, 0-10V DO10_ 1%, 0-10V DS2W1 1%, ELV/MLV, 120V DLTE1 1%, Lutron® ELV/MLV, 120V DL3E_ 1%, Lutron® EcoSystem® Fade EL10_ 1%, eldoLED ED01_ 0.1%, eldoLED DALI_ DALI Control	1 120V 2 277V	BH27 ⁴ 27" Solid Bars H12 12" - 24" Expandable Bars H06 6" - 12" Expandable Bars CB24 24" C-Channel Bars FS Fusing EB Fixture Painted Black CR Corrosion Resistant PR ⁵ Deep Ceiling Extension GR Goof Ring ZIG ⁶ ZigBee Module BLU ⁶ Bluetooth LE EM ⁷ 7W Emergency Battery Test Switch Remote EMIT ⁸ 7W Emergency Battery Test Switch in Trim AMB Anti-Microbial Finish	AR6224OS 6" Deep Trim	MW ⁹ Matte White MB Matte Black SG Semi-Diffuse HZ Haze Full Diffuse PT Platinum Silver BZ Bronze OB Oil Rubbed Bronze CH Charcoal AS Anodic Sapphire AN Anodic Natural AC Anodic Champagne AZ Anodic Bronze AK Anodic Black AM Anodic Malachite SN Sun Gold CO Copper Metallic GH Graphite CC ¹⁰ Custom Color	SO ¹¹ Micro Prism Solite™ Lens GL Clear Glass Lens FG Frosted Glass Lens GS Gasket WL Wet Location EMIT ⁸ Emergency Test Switch in Trim PF ¹² Polished Flange AMB Anti-Microbial Finish
	15L 1500 Lm	30K 3000K						
	20L 2000 Lm	35K 3500K						
	30L 3000 Lm	40K 4000K						
	45L 4500 Lm							

EXAMPLE: SGE6DLEDOS20L35KE1/AR6224OSSGSO

NOTES:

1 Nominal Source Lumens at 35K 2 Contact Factory for Additional Options 3 See Product Options Page for Details 4 Standard Bar Hangers 5 Contact Factory 6 Order DS10/2 When Specifying ZIG or BLU 7 Standard EM 8 EMIT Suffix Required on Trim and Housing 9 Standard Finish 10 Contact Factory for Special Finishes 11 Standard Lens 12 Flange and Reflector Same Finish



PROJECT: _____
TYPE: _____



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.