



A	B	C	D	E
7.0	0.6	4.0	10.8	8.0
177.8 mm	15.8 mm	101.6 mm	260.4 mm	203.2 mm

# 4" OPEN REFLECTOR/BAFFLE

PAR SERIES / 75 WATT MAX INC



## SG4IN

### APPLICATION

4" aperture series with deep cutoff for Incandescent lamps.

### FEATURES

Efficient reflector design optimized for Incandescent lamps. Posi-lock reflector attachment. Integral 5/8" (0.625) plaster ring. Maximum wattage label (MWL) for low wattage Incandescent or LED lamps. Tool-less ballast access. Multi-bar adjustable mounting brackets.

### FINISH

Variety of powdercoat and anodized finishes available on reflector. Eco Black (EB) finish available on frame/ housing.

### ELECTRONICS

120 Volt is standard. Use option T277 for 277V supply feed.

### CONSTRUCTION

Frame constructed of 20 ga. galvanized steel. Reflectors spun from .063 high purity aluminum and finished to specification.

### LABELS

Manufactured and tested to UL Standard No. 1598. ETL listed for Damp locations.

Max Ceiling Thickness:	1.5 (38.1 mm)
Ceiling Cutout:	4.2 Ø (108.0 mm Ø)
Fixture Weight:	4.0 lbs

SERIES	OPTIONS	TRIM / FINISH	TRIM OPTIONS	FIXTURE LAMPING*												
<b>SG4IN-</b> Spectrum Gold 4" Vertical	<b>BH27</b> -27" Bar Hangers (Supplied) <b>CB24</b> -C-Channel Bars <b>CCEA</b> -Chicago Ceiling Plenum <b>CR</b> -Corrosion Resistant <b>T277</b> -Step Down Transformer 277V to 120V <b>FS</b> -Fuse Holder and Fuse <b>IC</b> -Insulation Contact (See IC Options Pages for Dimensions) <b>PR</b> -Plaster Ring (Special Depth) <b>TBC</b> -T-bar Clips (Fit BH27) <b>MWL</b> -Max Wattage Label (Specify Wattage) <b>EB</b> -Eco Black Housing Finish	<b>AR4415-SG</b> -Semi-Diffuse Low-Iridescent (Standard) <b>CL</b> -Clear Bright Alzak <b>GO</b> -Gold Alzak <b>HZ</b> -Matte Low Iridescent <b>PW</b> -Pewter Alzak <b>UM</b> -Umber Alzak <b>WE</b> -Wheat Alzak <b>BK</b> -Black Finish <b>WH</b> -White Finish <b>PF</b> -Polished Flange  Note: White Flange is Standard.	<b>GS</b> -Gasket <b>BB</b> -Black Micro Baffle <b>WB</b> -White Micro Baffle	<table border="1"> <thead> <tr> <th>LAMP</th> <th>MAX. WATTAGE</th> </tr> </thead> <tbody> <tr> <td>A19</td> <td>75w</td> </tr> <tr> <td>PAR20</td> <td>50w</td> </tr> <tr> <td>PAR20LED</td> <td>50w</td> </tr> <tr> <td>R20</td> <td>50w</td> </tr> <tr> <td colspan="2">*Medium Base</td> </tr> </tbody> </table> <p>* Accepts PAR20 LED lamps.</p> <p>*For Available <b>Decorative Architectural Trims</b>, Consult Factory.</p>	LAMP	MAX. WATTAGE	A19	75w	PAR20	50w	PAR20LED	50w	R20	50w	*Medium Base	
LAMP	MAX. WATTAGE															
A19	75w															
PAR20	50w															
PAR20LED	50w															
R20	50w															
*Medium Base																

EXAMPLE: SG4IN/ AR4415 SG



PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.