



A	B	C	D	E	F
6.5	0.6	4.0	8.0	13.0	8.0
165.1 mm	15.8 mm	101.6 mm	203.2 mm	330.2 mm	203.2 mm

## 4" SQUARE ACCENT LIGHT ADJUSTABLE PAR16 / PAR20 LAMP 50 WATT MAX INCANDESCENT



### SGA4SQIN

#### APPLICATION

4" Square PAR20 accent light for incandescent lamps.

#### FEATURES

Efficient trim design with a variety of lens options. Trim rotates/ locks 360°. Lamp tilts/ locks 35°. Integral 5/8" (0.625) plaster ring. Maximum wattage label (MWL) for low wattage Incandescent or LED lamps. Multi-bar adjustable mounting brackets.

#### FINISH

Variety of powdercoat and anodized finishes available on trim. Eco Black (EB) finish available on frame/ housing.

#### ELECTRONICS

120 Volt is standard. Use option T277 for 277V supply feed.

#### CONSTRUCTION

Frame constructed of 20 ga. aluminum. Trim formed from .050 high purity aluminum and finished to specification.

#### LABELS

UL/ ETL Listed for Damp locations. Wet location available. Manufactured and tested to UL Standard No. 1598.

Max Ceiling Thickness:	1.0 (25.4 mm)
Ceiling Cutout:	5.0 <sup>2</sup> (127.0 mm) <sup>2</sup>
Fixture Weight:	4.7 lbs

SERIES	OPTIONS	TRIM / FINISH	TRIM OPTIONS	FIXTURE LAMPING*						
<b>SGA4SQIN-</b> Spectrum Gold 4" Vertical Adjustable Square	<b>BH27</b> - 27" Bar Hangers (Supplied) <b>CB24</b> - C-Channel Bars <b>CCEA</b> - Chicago Ceiling Plenum <b>CR</b> - Corrosion Resistant <b>T277</b> - Step Down Transformer 277v to 120v <b>FS</b> - Fuse Holder and Fuse <b>PR</b> - Plaster Ring (Special Depth) <b>MWL</b> - Max Wattage Label (Specify Wattage) <b>EB</b> - Eco Black Housing Finish <b>TBC</b> - T-Bar Clips <b>TR</b> - Top Relamping Option  *For Available Louvers and Lenses Consult Factory.	<b>AR0204-SG</b> -Semi-Diffuse Low-Iridescent (Standard) <b>GM</b> -Corrugated Soft Glow <b>GO</b> -Gold Alzak <b>MB</b> -Matte Black <b>MW</b> -Matte White <b>PW</b> -Pewter Alzak <b>UM</b> -Umber Alzak <b>WE</b> -Wheat Alzak <b>BF</b> -Black Flange <b>WF</b> -White Flange <b>CC</b> -Custom Color  Note: Polished Flange is Standard.	<b>GL</b> -Clear Glass Lens <b>GS</b> -Gasket <b>SO</b> -Micro Prism Solite™ Lens <b>PG</b> -Prismatic (173) Lens <b>LN</b> -See Recessed Fixtures/ Lens Options for Lens, Louver and Filter Accessories <b>WL</b> -Wet Location	<table border="1"> <thead> <tr> <th>LAMP</th> <th>MAX. WATTAGE</th> </tr> </thead> <tbody> <tr> <td>PAR16</td> <td>45W</td> </tr> <tr> <td>PAR20</td> <td>50W</td> </tr> </tbody> </table> *Medium Base	LAMP	MAX. WATTAGE	PAR16	45W	PAR20	50W
LAMP	MAX. WATTAGE									
PAR16	45W									
PAR20	50W									

### EXAMPLE: SGA4SQIN/AR0204 SG

Dimensions shown are nominal. Spectrum Lighting is continually improving products and reserves the right to make changes that will not alter performance or appearance with or without written notice.



PROJECT:	TYPE:
CAT. NO.:	

