



A	B	C	D	E	F
4.7	0.625	4.5	8.0	12.0	8.0
120.6 mm	19.0 mm	114.3 mm	203.2 mm	304.8 mm	203.2 mm

3.5" MINI ROUND VERSA LIGHT SERENE CEILING MR16 LAMP 65 WATT MAX INCANDESCENT



SGDG4F

APPLICATION

3.5 Versa light MR16 for Flush fit plaster installation.

FEATURES

- Versa Light housing accepts variety of trims.
- Trim rotates 360° for easy alignment, lamp tilts and locks to 45°.
- Fits flush to ceiling with PZ4RP fitter.
- Integral 5/8" (0.625) plaster ring.
- Maximum wattage label (MWL) for low wattage Halogen or LED lamps.
- Tool-less access for ease of maintenance.
- Multi-bar adjustable mounting brackets.

FINISH

Variety of powdercoat and anodized finishes available on reflector. Eco Black (EB) finish available on frame/ housing.

ELECTRONICS

120v Electronic transformer is standard.

CONSTRUCTION

Frame constructed of 20 ga. aluminum. Trim fabricated from .063 aluminum and finished to specification.

LABELS

UL/ ETL Listed for Damp Locations. Manufactured and tested to UL standard No. 1598.

Max Ceiling Thickness:	1.5 (38.1 mm)
Ceiling Cutout:	4.25 Ø (107.9 mm Ø)
Fixture Weight:	4.0 lbs

SERIES	TRANSFORMER	OPTIONS	TRIMLESS	TRIM / FINISH	OPTIONS	FIXTURE	LAMPING
SGDG4F- Spectrum Gold 3.5" Round Downlight	E1 -Electronic, 120V	BH27 -27" Bar Hangers (Supplied)	PZ4RP -Trimless 4" Round Fitter	AR3200-SAPHZ -Pinhole, 2.0" SASLPZ -Slot Aperture SALWPZ -Wall Wash SAWLPPZ -Wet Location MW -Matte White TW -Textured White GW -Gloss White MB -Matte Black CC -Custom Color	GL-Clear Glass Lens (Standard) GS-Gasket SO-Micro Prism Solite™ Lens PG-Prismatic (T73) Lens LN16-See Recessed Fixtures/ Lens Options for Lens, Louver, and Filter Accessories	LAMP	MAX. WATTAGE
	E2 -Electronic, 277V	BH6 -Expandable Bar Hangers, 6" - 12" BH12 -Expandable Bar Hangers, 12" - 24" CB24 -C-Channel Bars CCEA -Chicago Ceiling Plenum CCEA CR -Corrosion Resistant FS -Fuse Holder and Fuse IC -Insulation Contact (See IC Options) MWL(**) -Maximum Wattage Dedicated Transformer and Label (20w, 37w, 50w) PR -Plaster Ring TBC -T-bar Clips TR -Top Relamping Option EB -Eco Black Housing Finish					
	MGN1 -Magnetic Transformer 120V MGN2 -Magnetic Transformer 277V E1LED -Transformer for use with LED MR16 lamps 120v NTR - No Transformer					MR16	65w

*For Available Decorative Architectural Trims, Consult Factory.

EXAMPLE: SGDG4FE1/PZ4RP/AR3200SAPHZMWGL

Dimensions shown are nominal. Spectrum Lighting is continually improving products and reserves the right to make changes that will not alter performance or appearance with or without written notice.



PROJECT:	TYPE:
CAT. NO.:	

