



A	B	C	D	E	F
11.0 279.4 mm	0.6 15.8 mm	7.3 185.4 mm	11.5 292.1 mm	16.0 406.4 mm	11.5 292.1 mm

8" PULL DOWN ACCENT PAR30 / 38 LAMP

150 WATT MAX INCANDESCENT



SGP8IN/PDWH

APPLICATION

Adjustable Pull Down PAR30/ PAR38 accent light for Incandescent lamps.

FEATURES

Fixture rotates 360°/ locks 35°/ pulls down 6". Can be set fully recessed or fully pulled down. Integral 5/8" (0.625) plaster ring. Maximum wattage label (MWL) for low wattage Incandescent or LED lamps. Tool-less ballast access. Multi-bar adjustable mounting brackets.

FINISH

Variety of powdercoat and anodized finishes available on trim. Eco Black (EB) finish available on frame/housing.

ELECTRONICS

120 Volt is standard. Use option T277 for 277V supply feed.

CONSTRUCTION

Frame constructed of 20 ga. aluminum. Trim spun from .063 high purity aluminum and finished to specification.

LABELS

UL/ETL Listed for Damp locations. Manufactured and tested to UL Standard No. 1598.

Max Ceiling Thickness:	1.5 (38.1 mm)
Ceiling Cutout:	8.0 Ø (203.2 mm Ø)
Fixture Weight:	6.0 lbs

SERIES	OPTIONS	INSIDE BULLET	TRIM / FINISH	TRIM OPTIONS	FIXTURE LAMPING*						
SGP8IN Spectrum Gold 8" Pull Down	BH27 - 27" Bar Hangers (Supplied) CB24 - C-Channel Bars CCEA - Chicago Ceiling Plenum CR - Corrosion Resistant T277 - Step Down Transformer 277v to 120v FS - Fuse Holder and Fuse PR - Plaster Ring (Special Depth) MWL - Max Wattage Label (Specify Wattage) EB - Eco Black Housing Finish TBC - T-Bar Clips TR - Top Relamping Option	MWI -Matte White (Interior) MBI (Interior) GBI -Matte Black (Interior) GBI (Interior) CCI -Custom Color (Interior) BL WH	AR8402-SG -Semi-Diffuse Low-Iridescent (Standard) CL -Clear Bright Alzak GO -Gold Alzak HZ -Matte Low Iridescent PW -Pewter Alzak UM -Umber Alzak WE -Wheat Alzak PF -Polished Flange BB -Black Baffle WB -White Baffle	GS -Gasket LN -See Recessed Fixtures/ Lens Options for Lens, Louver and Filter Accessories	<table border="1"> <thead> <tr> <th>LAMP</th> <th>MAX. WATTAGE</th> </tr> </thead> <tbody> <tr> <td>PAR30L</td> <td>75W</td> </tr> <tr> <td>PAR38</td> <td>150W</td> </tr> </tbody> </table> <p>*Medium Base</p>	LAMP	MAX. WATTAGE	PAR30L	75W	PAR38	150W
LAMP	MAX. WATTAGE										
PAR30L	75W										
PAR38	150W										
		Note: White Ceiling Flange is Standard.	Note: White Ceiling Flange is Standard.								

EXAMPLE: SGP8IN/ AR8402 SG

Dimensions shown are nominal. Spectrum Lighting is continually improving products and reserves the right to make changes that will not alter performance or appearance with or without written notice.



PROJECT:	TYPE:
CAT. NO.:	

