



A	B	C	D	E
5.0 127.0 mm	0.6 15.8 mm	4.0 101.6 mm	10.8 260.4 mm	8.0 203.2 mm

# 4" OPEN REFLECTOR/BAFFLE

PAR SERIES / 75 WATT MAX INC



## SGS4IN

### APPLICATION

Small aperture series with medium cutoff.

### FEATURES

Efficient reflector design optimized for Incandescent lamps. Posi-lock reflector attachment. Integral 5/8" (0.625) plaster ring. Maximum wattage label (MWL) for low wattage Incandescent or LED lamps. Tool-less ballast access. Multi-bar adjustable mounting brackets.

### FINISH

Variety of powdercoat and anodized finishes available on reflector. Eco Black (EB) finish available on frame/housing.

### ELECTRONICS

120 Volt is standard. Use option T277 for 277V supply feed.

### CONSTRUCTION

Frame constructed of 20 ga. galvanized steel. Reflectors spun from .063 high purity aluminum and finished to specification.

### LABELS

ETL listed for Damp locations. Manufactured and tested to UL Standard No. 1598.

## SERIES

SERIES	OPTIONS	TRIM / FINISH	TRIM OPTIONS	FIXTURE LAMPING*								
<b>SGS4IN-</b> Spectrum Gold 4" Vertical	<b>BH27</b> - 27" Bar Hangers (Supplied) <b>CB24</b> - C-Channel Bars <b>CCEA</b> - Chicago Ceiling Plenum <b>CR</b> - Corrosion Resistant <b>T277</b> - Step Down Transformer 277V to 120V <b>FS</b> - Fuse Holder and Fuse <b>IC</b> - Insulation Contact (See IC Options Pages for Dimensions) <b>PR</b> - Plaster Ring (Special Depth) <b>TBC</b> - T-bar Clips (Fit BH27) <b>MWL</b> - Max Wattage Label (Specify Wattage) <b>EB</b> - Eco Black Housing Finish	<b>AR4115-SG</b> - Semi-Diffuse Low-Iridescent (Standard) <b>CL</b> - Clear Bright Alzak <b>GO</b> - Gold Alzak <b>HZ</b> - Matte Low Iridescent <b>PW</b> - Pewter Alzak <b>UM</b> - Umber Alzak <b>WE</b> - Wheat Alzak <b>BK</b> - Black Finish <b>WH</b> - White Finish <b>PF</b> - Polished Flange  Note: White Flange is Standard.	<b>GS</b> - Gasket <b>BB</b> - Black Micro Baffle <b>WB</b> - White Micro Baffle	<table border="1"> <thead> <tr> <th>LAMP</th> <th>MAX. WATTAGE</th> </tr> </thead> <tbody> <tr> <td>PAR 20</td> <td>50w</td> </tr> <tr> <td>R 20</td> <td>75w</td> </tr> <tr> <td colspan="2">*Medium Base</td> </tr> </tbody> </table> *For Available <b>Decorative Architectural Trims</b> , Consult Factory.	LAMP	MAX. WATTAGE	PAR 20	50w	R 20	75w	*Medium Base	
LAMP	MAX. WATTAGE											
PAR 20	50w											
R 20	75w											
*Medium Base												

EXAMPLE: SGS4IN/ AR4115 SG WB



PROJECT: \_\_\_\_\_  
TYPE: \_\_\_\_\_



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.