



A	B	C
14.0 355.6 mm	15.2 386.1 mm	6.2 157.5 mm

SERIES	LUMENS <sup>2</sup>		CCT		DRIVER / VOLTAGE <sup>3</sup>		OPTIONS <sup>5</sup>		TRIM	FINISH		TRIM OPTIONS		
	15L	27L	27K	30K	E	1	FS	AR1466GV		SG <sup>6</sup>	SO <sup>8</sup>			
SGRTE14LEDGV	15L	1500 Lm	27K	2700K	E	Electronic Driver	1	120V	FS	Fusing	SG <sup>6</sup>	Semi-Diffuse	SO <sup>8</sup>	Micro Prism Solite™ Lens
	27L	2700 Lm	30K	3000K	DS10_	10%, 0-10V	2	277V	EM	Emergency Battery	HZ	Haze Full Diffuse	FG	Frosted Glass Lens
	37L	3700 Lm	35K	3500K	DO10_	1%, 0-10V			CR	Corrosion Resistant	MW	Matte White	GS	Gasket for Flange
	55L	5500 Lm	40K	4000K	DS2W1	1%, ELV/MLV, 120V			GR	Goof Ring	MB	Matte Black	WL	Wet Location
	60L	6000 Lm	50K	5000K	DLTE1	1%, Lutron® ELV/MLV, 120V					PT	Platinum Silver	PF <sup>9</sup>	Polished Flange
					DL33_	1%, Lutron® Hi Lume					OB	Oil Rubbed Bronze		
				DL3E_	1%, Lutron® EcoSystem®					CH	Charcoal			
				LDE1_	1%, Lutron® EcoSystem® Fade					AC	Anodic Champagne			
				EL10_	1%, eldoLED					AS	Anodic Sapphire			
				ED01_	0.1%, eldoLED					AM	Anodic Malachite			
				DAL_	DALI Control					SN	Sun Gold			
				DMXS <sup>4</sup>	DMX Standard Configuration					CO	Copper Metallic			
				DMXC <sup>4</sup>	DMX Non-Standard Custom					GH	Graphite			
										AMB	Anti Microbial Finish			
										CC <sup>7</sup>	Custom Color			

**EXAMPLE:** SGRTE14LEDGV27L30KE1/AR1466GVMW50

**NOTES:**  
 1 Consult Factory for Thicker Ceiling 2 Nominal Source Lumens at 35K 3 Contact Factory for Additional Options 4 Contact Factory 5 See Product Options Page For Details 6 Standard Finish 7 Contact Factory for Special Finishes  
 8 SO Lens Reduces Output 10% 9 Flange and Reflector Same Finish



PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.