



A	B	C	S1	S2
6.6	5.9	6.6	6.0	7.4
167.6 mm	149.9 mm	167.6 mm	152.4 mm	188.0 mm

SGRTVW6GV - TRIM FLANGE / NON-IC RATED

APPLICATION

Round GV series LED wall wash for retrofit or remodelight applications.

FEATURES

Designed to retrofit into existing fixture or remodel with no existing fixture. Single stage optical system with deep reflector design delivers smooth glare-free general illumination. Tool-less LED module, driver, and J-Box access. Multi-Bar mounting brackets. Intended for Non-IC new construction. BH27 Standard mounting bars included. Posi-lock trim retention torsion springs. Integral 0.625" collar, with plaster option (PR) for up to 3" thick ceiling.

TRIM FINISH

A variety of architectural powdercoat and anodized finishes are available.

Matte White flange is standard.

ELECTRONICS

GV LED system features high brightness white Samsung LED's. 3-step MacAdam Ellipse binning. Standard CRI: 85+. Higher CRI, R9 and custom LED configurations are available; consult factory. A variety of electronic 120V/277V and dimming drivers available.

CONSTRUCTION

Housing/frame constructed of .060" aluminum to resist corrosion. Die-cast aluminum heat sink. Self-flanged one piece trim spun from 0.060" thick high purity aluminum and finished to specification.

CODE COMPLIANCE

BAA Compliant. Non-IC rated. ETL certified to meet US and Canadian standards. Suitable for dry or damp locations. Manufactured and tested to UL standards No. 1598/8750.

LUMENS / WATTAGE DATA		
PART NUMBER	SOURCE LUMENS ²	SYSTEM WATTS
SGRTVW6LEDGV15L	1500	13
SGRTVW6LEDGV27L	2700	22
SGRTVW6LEDGV37L	3700	29
SGRTVW6LEDGV55L	5500	43
SGRTVW6LEDGV60L	6000	49

SERIES	LUMENS ¹	CCT	DRIVER / VOLTAGE ²	OPTIONS ⁴	TRIM	FINISH	TRIM OPTIONS	
SGRTVW6GV	15L	1500 Lm	27K 2700K	E_ Electronic Driver	1 120V	AR6790GV	MW Matte White MB Matte Black SG Semi-Diffuse PT Platinum Silver CC ⁵ Custom Color	
	27L	2700 Lm	30K 3000K	DS10_ 10%, 0-10V	2 277V			SK SkytEX™ Lens
	37L	3700 Lm	35K 3500K	DO10_ 1%, 0-10V	EM Emergency Battery			GS Gasket for Flange
	55L	5500 Lm	40K 4000K	DS2W1 1%, ELV/MLV, 120V	CR Corrosion Resistant			PF ⁶ Polished Flange
	60L	6000 Lm	50K 5000K	DLTE1 1% Lutron® 2-Wire Forward Phase, 120V	GR Goof Ring			
				DL3E 1% Lutron® EcoSystem®, Fade				
			EL10_ 1%, eldoLED					
			ED01_ 0.1%, eldoLED					
			DALI_ DALI Control					
			DMXS ³ DMX Standard Configuration					
			DMXC ³ DMX Non-Standard Custom					

EXAMPLE: SGRTVW6GV37L27KE1/AR6790GVMWSK

NOTES:
 1 Nominal Source Lumens at 35K 2 Contact Factory for Additional Options 3 Contact Factory 4 See Product Options Page For Details 5 Consult Factory for Special Finishes 6 Flange and Reflector Same Finish



PROJECT: _____
 TYPE: _____



Dimensions and values shown are nominal. Spectrum Lighting continually works to improve products and reserves the right to make changes which may alter the performance or appearance of products.